


NASA/TM-1999-209130



Computational Test Cases for a Rectangular Supercritical Wing Undergoing Pitching Oscillations

*Robert M. Bennett and Charlotte E. Walker
Langley Research Center, Hampton, Virginia*

April 1999

The NASA STI Program Office ... in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the lead center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA counterpart of peer-reviewed formal professional papers, but having less stringent limitations on manuscript length and extent of graphic presentations.
- **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.


- **CONFERENCE PUBLICATION.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or co-sponsored by NASA.
- **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized databases, organizing and publishing research results ... even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at <http://www.sti.nasa.gov>
- E-mail your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA STI Help Desk at (301) 621-0134
- Phone the NASA STI Help Desk at (301) 621-0390
- Write to:
NASA STI Help Desk
NASA Center for AeroSpace Information
7121 Standard Drive
Hanover, MD 21076-1320

NASA/TM-1999-209130



Computational Test Cases for a Rectangular Supercritical Wing Undergoing Pitching Oscillations

Robert M. Bennett and Charlotte E. Walker
Langley Research Center, Hampton, Virginia

National Aeronautics and
Space Administration

Langley Research Center
Hampton, Virginia 23681-2199

April 1999

Acknowledgment

Appreciation is extended to David A. Seidel of the Boeing Company, Seattle WA for making the data files available from the NASA Langley archives.

The use of trademarks or names of manufacturers in the report is for accurate reporting and does not constitute an official endorsement, either expressed or implied, of such products or manufacturers by the National Aeronautics and Space Administration.

Available from:

NASA Center for AeroSpace Information (CASI)
7121 Standard Drive
Hanover, MD 21076-1320
(301) 621-0390

National Technical Information Service (NTIS)
5285 Port Royal Road
Springfield, VA 22161-2171
(703) 605-6000

Abstract

Proposed computational test cases have been selected from the data set for a rectangular wing of panel aspect ratio two with a twelve-percent-thick supercritical airfoil section that was tested in the NASA Langley Transonic Dynamics Tunnel. The test cases include parametric variation of static angle of attack, pitching oscillation frequency, and Mach numbers from subsonic to transonic with strong shocks. Tables and plots of the measured pressures are presented for each case. This report provides an early release of test cases that have been proposed for a document that supplements the cases presented in AGARD Report 702.

Nomenclature

c	local chord
c_r	wing root chord, ft (m)
C_p	pressure coefficient, $(p-p_\infty)/q_\infty$
C_p^*	pressure coefficient for sonic flow
f	frequency, Hz
H_o	freestream total pressure, psf (kPa)
k	reduced frequency, $\omega c_r/(2V_\infty)$
p	pressure, psf (kPa)
p_∞	freestream static pressure, psf (kPa)
q_∞	dynamic pressure, psf (kPa)
R	local radius of tip section
Rn	Reynolds number based on chord
s	semispan
T_o	total or stagnation temperature, °R (°C)
V_∞	freestream velocity, ft/sec (m/sec)
x	streamwise distance from leading edge
x/c	steamwise fraction of local chord
y	spanwise coordinate normal to freestream
z_u, z_l	airfoil vertical upper and lower ordinate normal to freestream, positive up
α_o	mean angle of attack, degrees
θ	amplitude of pitch oscillations, degrees or radians
η	fraction of span, y/s
γ	ratio of specific heats for test gas

ω frequency, radians/second

Introduction

Steady and unsteady measured pressures for a rectangular supercritical wing (referred to as RSW) undergoing pitching oscillations have been presented in references 1 to 3. From the several hundred compiled data points, 27 static and 36 pitching oscillation cases have been proposed for computational test cases to illustrate the trends with Mach number, reduced frequency, and angle of attack.

The wing was designed to be a simple configuration for Computational Fluid Dynamics (CFD) comparisons. The wing had an unswept rectangular planform plus a tip of revolution, a panel aspect ratio of 2.0, a twelve per cent thick supercritical airfoil section, and no twist. The model was tested over a wide range of Mach numbers, from 0.27 to 0.90, corresponding to low subsonic flows up to strong transonic flows. The higher Mach numbers are well beyond the design Mach number such as might be required for flutter verification beyond cruise conditions. The pitching oscillations covered a broad range of reduced frequencies.

Some early calculations for this wing are given for lifting pressure in references 3 and 4 as calculated from a linear lifting surface program and from a transonic small perturbation program. The unsteady results were given primarily for a mild transonic condition at $M = 0.70$. For these cases the agreement with the data was only fair, possibly resulting from the omission of viscous effects. Supercritical airfoil sections are known to be sensitive to viscous effects (for example, one case cited in ref. 4). Calculations using a higher level code with the full potential equation have been presented in reference 5 for one of the same cases and with the Euler equations in reference 6. The agreement around the leading edge was improved, but overall the agreement was not completely satisfactory. Typically for low-aspect-ratio rectangular wings, transonic shock waves on the wing tend to sweep forward from root to tip such that there are strong three-dimensional effects. It might also be noted that for most of the test, the model was tested with free transition, but a few points were taken with an added transition strip for comparison. Some unpublished results of a rigid wing of the same airfoil and planform that was tested on the pitch and plunge apparatus mount system (PAPA, ref. 7-8) showed effects of the lower surface transition strip on flutter at the lower subsonic Mach numbers. Significant effects of a transition strip were also obtained on a wing with a thicker supercritical section on the PAPA mount system (ref. 9). Both of these flutter tests on the PAPA resulted in very low reduced frequencies that may be a factor in this influence of the transition strip. However, these results indicate that correlation studies for RSW may require some attention to the estimation of transition location to accurately treat viscous effects.

In this report several test cases are selected to illustrate trends for a variety of different conditions with emphasis on transonic flow effects. An overview of the model and tests are given and the standard formulary for these data is listed. All of the data are presented herein both in tabular and in graphical form. Only the static pressures and the real and imaginary parts of the first harmonic of the unsteady pressures are available. All the data for the test are available in electronic file form, and are printed in the tables of reference 1. The test cases are also available as separate electronic files.

This report provides an early release of test cases that have been proposed for a document that supplements the cases presented in AGARD Report 702 (ref. 10-11) and is being generated under the NATO Research and Technology Organization (RTO) Applied Vehicle Technology (AVT) Working Group-003. The overall description of the data set is given in the body of this report by a formulary similar to that used in AGARD Report 702.

Model and Tests

The rectangular supercritical wing model was tested in the NASA Langley Transonic Dynamics Tunnel (TDT). The tunnel has a slotted test section 16-feet (4.064 m) square with cropped corners. At the time of these tests, it could be operated with air or a heavy gas, R-12, as a test medium at pressures from very low to near atmospheric values. Currently the TDT can be operated with air or R-134a as a test medium. An early description of this facility is given in an internal report (NASA LWP-799, Sep. 1969) and the early data system in reference 12. More recent descriptions of the facility are given in references 13 and 14, and of the recent data system are given in references 15 and 16. Based on cone transition results (ref. 17-18), the turbulence level for this tunnel is in the average large transonic tunnel category. Some low speed turbulence measurements in air have also been presented in reference 19.

A photograph of the model and splitter plate as installed in the TDT is shown in figure 1 and the dimensions of the model and splitter plate setup are detailed in the sketch of figure 2. The unswept rectangular planform was 48 inches (1219 mm) in span plus a tip of revolution of maximum radius of 1.434 inches (36.4 mm) such that the maximum spanwise extent was 49.43 inches (1255 mm). The chord was 24 inches (609.6 mm). The model was mounted on a splitter plate offset from the wall. It was oscillated in pitch about 46 percent root chord with a shaft that was directly driven by a rotary hydraulic actuator located behind the tunnel wall. It could be set at various mean angles, and the amplitude and frequency of oscillation could be varied.

The wing was constructed in three sections. The center section was made of aluminum with the upper and lower halves pinned and bonded together. The leading and trailing edge portions were made of balsa and Kevlar sandwich material to minimize the inertia loading. The leading and trailing edge sections were joined at 0.23 and 0.69 of the chord, respectively. Some stiffness measurements are given in reference 3. Unsteady pressures were measured on four chords. There were 14 measurement locations along each chord on both upper and lower surfaces and one location in the nose for a total of 29 points per chord as shown in figure 3 and listed in table 1. The transducers in the center portion of the wing were in-situ measurements. The transducers in the leading and trailing edges were mounted near the joints of the leading or trailing edge sections to the center beam. Equal length tubes were used between the orifices and these transducers. Other transducers were located by the first row of in-situ transducers and had tubes of the same length located in the center beam. These transducers were used to correct for dynamic effects of the tubes of the transducers in the leading and trailing edges. Each transducer was referenced to the tunnel static pressure and was used to measure both static and unsteady pressures. Eight accelerometers were located on the center section for dynamic measurements. Figure 4 (from ref. 1) shows C_L versus Mach number as integrated from the pressure data, and gives an overall indication of the performance of the wing.

The airfoil for the RSW is illustrated in figure 5. This airfoil was derived by ratioing the thickness of an 11 percent airfoil (ref. 20) to 12 percent while keeping the same mean camber line. The trailing edge thickness was increased to 0.7 percent chord by rotating the lower cusp area as described in reference 21. The design Mach number and lift coefficient for the 2-dimensional airfoil is quoted at $M = 0.80$, and $C_L = 0.6$ (ref. 3). The design ordinates and the measured ordinates for five spanwise stations are given in table 2. The design wing tip-shape is also presented in table 2. The quoted accuracy of the measured ordinates is .00040 in. (.0010 mm). The measured airfoil ordinates are compared with the theoretical ordinates in figure 6. The measured ordinates agree very well with the theoretical ones but with some small deviation in the lower surface aft, or cove, region.

By CFD standards, the theoretical and measured ordinates were given on a medium to coarse grid. In order to develop a common set of ordinates for CFD applications, the measured ordinates have been interpolated at each span station. The measured ordinates were fit with a spline using arc-length as the independent parameter and running from upper surface trailing edge around the nose to the lower surface

trailing edge. Three passes of a local 5-point least-squares cubic smoothing patch were made and the resulting curve interpolated for the ordinates. The smoothed ordinates are interpolated for 206 values of x/c at each of the five measurement span stations. These are included as a file for the data set and are listed in table 3. One airfoil section, after smoothing, and the corresponding streamwise slopes are presented in figure 7. For this wing, the measured spanwise sections are nearly identical, except at the lower surface trailing edge where the slope varies by about 8 per cent. It should also be noted that the slope varies quite rapidly near the inflection point in the cove region of the airfoil lower surface (fig. 7).

As can been seen in figure 1, the model was tested with the sidewall slots of the test section open. Some recent unpublished results for a model having about six times the root chord of this model and mounted directly to the wind tunnel wall, have shown an order of ten percent influence of closing the slots on static lift curve slope (similar to those measured in ref. 22). Significantly less influence would be anticipated for this much smaller model mounted on a splitter plate.

Test Cases

The static test cases for the rectangular supercritical wing are given in table 4, and the dynamic test cases are presented in table 5. The point number is used to identify the test conditions and are in the order taken during the test. The test case number is related to the enumeration given in the RTO chapter. The cases are chosen to indicate trends with Mach number at two degrees angle of attack, and also at zero and four degrees angle of attack with a coarse increment. Some cases for high angles of attack at $M=0.40$, some cases for the effect of transition at $M=0.825$, and some cases for air as the test medium are listed. The dynamic cases are chosen to evaluate unsteady effects at these static conditions. The cases illustrate variations with Mach number for nearly constant reduced frequency, and variations with reduced frequency at constant Mach numbers. Some cases are chosen also to indicate the effects of angle of attack, transition strip, and amplitude. The plot of C_L versus Mach number as integrated from the pressure data (fig. 4) was used as a guide in selecting the test cases.

All the data for the static test cases are tabulated and shown in composite plots in figure 8. The data for the dynamic cases are also tabulated and shown in the plots of figure 9 in terms of in-phase and out-of-phase parts (real and imaginary) of the pressure normalized by the amplitude of the pitching oscillation. The phase is referenced to the pitching motion. More digits than are significant are retained in the tables to accurately reproduce the phase angles of the original tabulations.

Note that most of the tests for RSW were conducted with the heavy gas, R-12, as the test medium. The ratio of specific heats, γ , is tabulated for each point in the figures. It varies from about 1.129 to 1.132 and a value of 1.132 is suggested for use in computational comparisons. The corresponding value of Prandtl number is calculated to range from 0.77 to 0.78 for the conditions of this test assuming 0.99 for the fraction of heavy gas in the heavy gas-air mixture.

Formulary for Rectangular Supercritical Wing Data Set

1. General Description of Model

1.1 Designation	Rectangular Supercritical Wing (RSW)
1.2 Type	Semispan wing
1.3 Derivation	None
1.4 Additional remarks	Shown mounted in tunnel in figure 1 and sketch of setup shown in figure 2
1.5 References	References 1-3 are the original source

2. Model Geometry

2.1 Planform	Rectangular plus tip of revolution
2.2 Aspect ratio	2.0 for panel (without tip)
2.3 Leading edge sweep	Unswept
2.4 Trailing edge sweep	Unswept
2.5 Taper ratio	1.0
2.6 Twist	None
2.7 Wing centerline chord	24.0 inches (609.6 mm)
2.8 Semi-span of model	48.0 inches (1219 mm) plus tip
2.9 Area of planform	1152 sq. in (1.786 sq m)
2.10 Location of reference sections and definition of profiles	Reduced frequency based on root semichord, 12.0 inches 304.8 mm)
2.11 Lofting procedure between reference sections	Constant percent thickness airfoil
2.12 Form of wing-body junction	No fairing
2.13 Form of wing tip	Tip of rotation. Each spanwise section formed by half circle with radius half the local thickness and rotated about the mean line
2.14 Control surface details	No control surfaces
2.15 Additional remarks	See figures 1-3 for overview
2.16 References	References 1-3

3. Wind Tunnel

3.1 Designation	NASA LaRC Transonic Dynamics Tunnel (TDT)
3.2 Type of tunnel	Continuous flow, single return
3.3 Test section dimensions	16 ft x 16 ft (4.064 x 4.064 m)
3.4 Type of roof and floor	Three slots each
3.5 Type of side walls	Two sidewall slots
3.6 Ventilation geometry	Constant width slots in test region
3.7 Thickness of side wall boundary layer	Some documentation in internal report LWP-799. Model tested with splitter plate
3.8 Thickness of boundary layers at roof and floor	Not documented
3.9 Method of measuring velocity	Calculated from static pressures measured in plenum and total pressure measured upstream of entrance nozzle of test section
3.10 Flow angularity	Not documented, considered small
3.11 Uniformity of velocity over test section	Not documented, considered nearly uniform
3.12 Sources and levels of noise or turbulence in empty tunnel	Generally unknown. Some low speed measurements are presented in reference 19. Cone transition measurements are presented in references 17 and 18

3.13 Tunnel resonances	Unknown
3.14 Additional remarks	Tests generally performed in heavy gas, R-12. Ratio of specific heats, γ , is 1.129-1.132. For computations, 1.132 is recommended. For the conditions of this test, the Prandtl number is calculated to be 0.77-0.78
3.15 References on tunnel	References 12, 13, and internal report LWP-799

4. Model Motion

4.1 General description	Pitching about 46% of root chord for wing, 11.04 inches (280.4 mm) aft of leading edge
4.2 Reference coordinate and definition of motion	Pitch about axis normal to freestream
4.3 Range of amplitude	Pitch amplitude of 0.50, 1.00, and 1.50 degrees
4.4 Range of frequency	5, 10, 15, and 20 Hz with a few lower frequencies
4.5 Method of applying motion	Pitch oscillations shaft-driven with a rotary hydraulic actuator
4.6 Timewise purity of motion	Not documented
4.7 Natural frequencies and normal modes of model and support system	First natural frequency was 34.8 Hz
4.8 Actual mode of applied	Some accelerometer measurements given in ref. 2
4.9 Additional remarks	None

5. Test Conditions

5.1 Model planform area/tunnel area	.03
5.2 Model span/tunnel height	.25
5.3 Blockage	Model less than 0.4%
5.4 Position of model in tunnel	Mounted from splitter plate on wall and in the center of the tunnel
5.5 Range of Mach number	0.40 to 0.90
5.6 Range of tunnel total pressure	175 to 2025 psf (8.38 to 812 kPa)
5.7 Range of tunnel total temperature	Not documented but generally in the range of 520 to 580 degrees Rankine (16 to 49° C)
5.8 Range of model steady or mean incidence	Generally -1 to 7 degrees, a few points from -4 to 14 degrees
5.9 Definition of model incidence	From chord line of airfoil
5.10 Position of transition, if free	Unknown except for a few points with transition strip. Although the joint was quite smooth, an initial estimate of transition might be considered to be at the joint between the leading edge section and the main spar (23 per cent chord)
5.11 Position and type of trip, if transition fixed	Generally free transition. A few points measured with transition strip of number 60 grit located at 6 percent chord on upper and lower surfaces (number is approximate grains per inch (per 25.4 mm)).

5.12 Flow instabilities during tests	None defined
5.13 Changes to mean shape of model due to steady aerodynamic load	Not measured
5.14 Additional remarks	Generally, a heavy gas, R-12, was used as a test medium for the test cases. The ratio of specific heats, γ , is tabulated for each point and varies from about 1.129 to 1.132. A value of 1.132 is suggested for use in computational comparisons. The corresponding value of Prandtl number is 0.77-0.78. A few points were also measured in air
5.15 References describing tests	References 1- 3

6. Measurements and Observations

6.1 Steady pressures for the mean conditions	yes
6.2 Steady pressures for small changes from the mean conditions	yes
6.3 Quasi-steady pressures	no
6.4 Unsteady pressures	yes
6.5 Steady section forces for the mean conditions by integration of pressures	no
6.6 Steady section forces for small changes from the mean conditions by integration	no
6.7 Quasi-steady section forces by integration	no
6.8 Unsteady section forces by integration	no
6.9 Measurement of actual motion at points of model	no
6.10 Observation or measurement of boundary layer properties	no
6.11 Visualisation of surface flow	no
6.12 Visualisation of shock wave movements	no
6.13 Additional remarks	no

7. Instrumentation

7.1 Steady pressure	
7.1.1 Position of orifices spanwise and chordwise	29 chordwise locations at 4 spanwise stations. See figure 4
7.1.2 Type of measuring system	Kulite

7.2 Unsteady pressure	
7.2.1 Position of orifices spanwise and chordwise	Same transducers measured steady and unsteady pressures
7.2.2 Diameter of orifices	Not documented
7.2.3 Type of measuring system	In situ pressure gages and short tubes to unsteady gages with tube calibrations
7.2.4 Type of transducers	Kulite
7.2.5 Principle and accuracy of calibration	Statically calibrated through reference tubes
7.3 Model motion	
7.3.1 Method of measuring motion reference coordinate	Potentiometer
7.3.2 Method of determining spatial mode of motion	Some verification with accelerometers
7.3.3 Accuracy of measured motion	Undocumented
7.4 Processing of unsteady measurements	
7.4.1 Method of acquiring and processing measurements	Analog signals digitized at about 300 samples/sec for 75-100 cycles depending on frequency
7.4.2 Type of analysis	Fourier analysis
7.4.3 Unsteady pressure quantities obtained and accuracies achieved	Amplitude and phase of each pressure signal. Accuracy not specified
7.4.4 Method of integration to obtain forces	None
7.5 Additional remarks	None
7.6 References on techniques	Data system overview for test given in reference 12

8. Data Presentation

8.1 Test cases for which data could be made available	All data are available
8.2 Test cases for which data are included in this document	All data tabulated and plotted. See figures 8 and 9.
8.3 Steady pressures	Generally available for each test case
8.4 Quasi-steady or steady perturbation pressures	Steady pressures measured for several angles of attack
8.5 Unsteady pressures	Primary data. First harmonic only. No time histories saved. C_n magnitude and phase of reference 2 converted to real and imaginary parts and normalized by amplitude of oscillation (in radians) for this report.
8.6 Steady forces or moments	None
8.7 Quasi-steady or unsteady perturbation forces	None
8.8 Unsteady forces and moments	None

8.9 Other forms in which data could be made available	None
8.10 Reference giving other representations of data	References 1-6

9. Comments on Data

9.1 Accuracy	
9.1.1 Mach number	Not documented
9.1.2 Steady incidence	Not documented
9.1.3 Reduced frequency	Should be accurate
9.1.4 Steady pressure coefficients	Not documented
9.1.5 Steady pressure derivatives	None
9.1.6 Unsteady pressure coefficients	Not documented, but each gage individually calibrated dynamically and monitored statically
9.2 Sensitivity to small changes of parameter	None indicated. Amplitudes of oscillation was varied in test
9.3 Non-linearities	Many flow conditions involve shock waves
9.4 Influence of tunnel total pressure	Some variation during test. Most of the test at constant dynamic pressure
9.5 Effects on data of uncertainty, or variation, in mode of model motion	Unknown, not expected to be appreciable.
9.6 Wall interference corrections	None applied
9.7 Other relevant tests on same model	None
9.8 Relevant tests on other models of nominally the same shapes	None
9.9 Any remarks relevant to comparison between experiment and theory	Generally free transition. R_n from 1×10^6 to 8×10^6 but generally about 4×10^6
9.10 Additional remarks	Upper and lower surface data instrumented symmetrically
9.11 References on discussion of data	References 1-6

10. Personal Contact for Further Information

Head, Aeroelasticity Branch
 Mail Stop 340
 NASA Langley Research Center
 Hampton, VA 23681-2199 USA

Phone: +1-(757)-864-2820
 FAX: +1-(757)-864-8678

Concluding Remarks

Steady and unsteady measured pressures for a rectangular supercritical wing (RSW) undergoing pitching oscillations were reviewed. From the several hundred compiled data points, 27 static cases and 36 pitching oscillation cases have been proposed for computational test cases to illustrate the trends with Mach number, reduced frequency, and angle of attack. An overview of the model and tests are given, and the standard formulary for these data is listed. All of the data are presented in both tabular and graphical form. This report provides an early release of test cases that have been proposed for a document that supplements the cases presented in AGARD Report 702 and is being generated under the NATO Research and Technology Organization (RTO) Applied Vehicle Technology (AVT) Working Group-003.

NASA Langley Research Center
Hampton, VA 23681-2199
March 8, 1999

References

1. Ricketts, Rodney H.; Sandford, Maynard C.; Seidel, David A.; and Watson, Judith J: *Transonic Pressure Distributions on a Rectangular Supercritical Wing Oscillated in Pitch*. Journal of Aircraft, vol. 21, no. 8, August 1984, pp 576-582. (Also AIAA Paper 83-0923, May 1983 which is available as NASA TM 84616, Mar. 1983).
2. Ricketts, Rodney H.; Sandford, Maynard C.; Watson, Judith J.; and Seidel, David A.: *Subsonic and Transonic Unsteady-and Steady-Pressure Measurements on a Rectangular Supercritical Wing Oscillated in Pitch*. NASA TM 85765, August 1984.
3. Ricketts, Rodney H.; Sandford, Maynard C.; Watson, Judith J.; and Seidel, David A.: *Geometric and Structural Properties of a Rectangular Supercritical Wing Oscillated in Pitch for Measurements of Unsteady Transonic Pressure Distributions*. NASA TM 85673, Nov. 1983.
4. Seidel, David A.; Bennett, Robert M.; and Ricketts, Rodney H.: *Some Recent Applications of XTRAN3S*. AIAA Paper 83-1811, July 1983. (Also available as NASA TM 85641, May 1983).
5. Hounjet, M. H. L.: *NLR Inviscid Transonic Unsteady Loads Prediction Methods in Aeroelasticity*. Paper No. 12 in "Transonic Unsteady Aerodynamics and Aeroelasticity," AGARD CP-507, March 1992.
6. Brenneis, A.; and Eberle, A.: *Application of an Implicit Relaxation Method Solving the Euler Equations for Time-Accurate Unsteady Problems*. Journal of Fluids Engineering, Transactions of the ASME, Vol 112, Dec. 1990, pp. 510-520.
7. Farmer, Moses G.: *A Two-Degree-of Freedom Flutter Mount System with Low Damping for Testing Rigid Wings at Different Angles of Attack*. NASA TM 83302, 1982.
8. Farmer, Moses G.: *Model Mount System for Testing Flutter*. U. S. Patent No. 4,475,385, Oct. 9, 1984.
9. Dansberry, B.E.; Durham, M.H.; Bennett, R.M.; Rivera, J.A., Jr.; Silva, W.A.; Wieseman, C.D.; and Turnock, D.L.: *Experimental Unsteady Pressures at Flutter on the Supercritical Wing Benchmark Model*. AIAA Paper No. 93-1592, April 1993.
10. *Compendium of Unsteady Aerodynamic Measurements*. AGARD Report No. 702, Aug. 1982.
11. *Compendium of Unsteady Aerodynamic Measurements, Addendum No. 1*. AGARD Report No. 702, May 1985.

12. Cole, Patricia H.: *Wind Tunnel Real-Time Data Acquisition System*. NASA TM-80081, 1979.
13. Cole, Stanley C., and Rivera, Jose, A., Jr.: *The New Heavy Gas Testing Capability in the NASA Langley Transonic Dynamics Tunnel*. Paper No. 4, presented at the Royal Aeronautical Society Wind Tunnels and Wind Tunnel Test Techniques Forum, Churchill College, Cambridge, UK, Apr. 1997.
14. Corliss, James M.; and Cole, Stanley R.: *Heavy Gas Conversion of the NASA Langley Transonic Dynamics Tunnel*. AIAA Paper 98-2710, June 1998.
15. Wieseman, Carol D.; and Hoadley, Sherwood, T.: *Versatile Software Package for Near Real-Time Analysis of Experimental Data*. AIAA Paper 98-2722, June 1998.
16. Bryant, C.; and Hoadley, S. T.: *Open Architecture Dynamic Data System at Langley's Transonic Dynamics Tunnel*. AAIA Paper 98-0343, Jan. 1998.
17. Dougherty, N. Sam, Jr.: *Influence of Wind Tunnel Noise on the Location of Boundary-Layer Transition on a Slender Cone at Mach Numbers from 0.2 to 5.5*. Volume I. - Experimental Methods and Summary of Results. Volume II. - Tabulated and Plotted Data. AEDC --TR-78-44, March 1980.
18. Dougherty, N. S., Jr.; and Fisher, D. F.: *Boundary-Layer Transition on a 10-Degree Cone: Wind Tunnel/Flight Correlation*. AIAA Paper 80-0154, January 1980.
19. Sleeper, Robert K.; Keller, Donald F.; Perry, Boyd, III; and Sandford, Maynard C.: *Characteristics of Vertical and Lateral Tunnel Turbulence Measured in Air in the Langley Transonic Dynamics Tunnel*. NASA TM 107734, March 1993.
20. Whitcomb, Richard T.: *Review of NASA Supercritical Airfoils*. ICAS Paper No.74-10, presented at the Ninth Congress of the International Council of The Aeronautical Sciences, Aug. 1974, Haifa, Israel.
21. Harris, Charles D.: *Wind-Tunnel Investigation of Effects of Trailing-Edge Geometry on a NASA Supercritical Airfoil Section*. NASA TM X-2336, Sept. 1971.
22. Lambourne, N.; Destuynder, R.; Kienappel, K.; and Roos, R.: *Comparative Measurements in Four European Wind Tunnels of the Unsteady Pressures on an Oscillating Model (The NORA Experiments)*. AGARD Report No. 673, Feb. 1980.

Table 1. Pressure Orifice Locations and Type

x/c	Type
0.000	Tube to Transducer
.003	Tube to Transducer
.050	Tube to Transducer
.100	Tube to Transducer
.200	Tube to Transducer
.260	In Situ
.320	In Situ
.380	In Situ
.440	In Situ
.500	In Situ
.560	In Situ
.620	In Situ
.700	Tube to Transducer
.800	Tube to Transducer
.900	Tube to Transducer

Table 2. Design and Measured Ordinates

x, in	x/c	Design Values		Measured Values					
		z_u , in	z_l , in	$y = 1.000$ in		$y = 14.932$ in		$y = 28.324$ in	
0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
0.1800	0.0075	0.4610	-0.4610	0.4571	-0.4726	0.4535	-0.4701	0.4514	-0.4624
0.3000	0.0125	0.5630	-0.5650	0.5602	-0.5750	0.5557	-0.5717	0.5572	-0.5669
0.6000	0.0250	0.7230	-0.7350	0.7193	-0.7435	0.7156	-0.7376	0.7197	-0.7380
0.9000	0.0375	0.8280	-0.8470	0.8226	-0.8569	0.8234	-0.8498	0.8242	-0.8492
1.2000	0.0500	0.9100	-0.9360	0.9050	-0.9436	0.9050	-0.9383	0.9062	-0.9365
1.8000	0.0750	1.0330	-1.0670	1.0289	-1.0720	1.0290	-1.0693	1.0295	-1.0683
2.4000	0.1000	1.1220	-1.1610	1.1191	-1.1638	1.1176	-1.1620	1.1176	-1.1603
3.0000	0.1250	1.1930	-1.2340	1.1901	-1.2372	1.1895	-1.2345	1.1910	-1.2346
3.6000	0.1500	1.2480	-1.2890	1.2466	-1.2928	1.2459	-1.2902	1.2465	-1.2898
4.2000	0.1750	1.2930	-1.3330	1.2936	-1.3378	1.2916	-1.3345	1.2925	-1.3330
4.8000	0.2000	1.3290	-1.3650	1.3335	-1.3691	1.3287	-1.3670	1.3300	-1.3665
6.0000	0.2500	1.3840	-1.4130	1.3876	-1.4147	1.3846	-1.4122	1.3839	-1.4116
7.2000	0.3000	1.4150	-1.4340	1.4177	-1.4343	1.4147	-1.4320	1.4148	-1.4308
8.4000	0.3500	1.4320	-1.4370	1.4343	-1.4374	1.4331	-1.4343	1.4329	-1.4326
9.6000	0.4000	1.4390	-1.4170	1.4421	-1.4153	1.4396	-1.4127	1.4397	-1.4130
10.8000	0.4500	1.4320	-1.3750	1.4354	-1.3739	1.4341	-1.3717	1.4354	-1.3721
12.0000	0.5000	1.4170	-1.3060	1.4194	-1.3069	1.4177	-1.3036	1.4190	-1.3036
13.2000	0.5500	1.3870	-1.2000	1.3893	-1.2011	1.3892	-1.1971	1.3891	-1.1978
13.8000	0.5750	1.3690	-1.1260	1.3713	-1.1266	1.3702	-1.1224	1.3697	-1.1228
14.4000	0.6000	1.3450	-1.0330	1.3492	-1.0332	1.3487	-1.0284	1.3467	-1.0291
15.0000	0.6250	1.3200	-0.9140	1.3235	-0.9129	1.3225	-0.9084	1.3216	-0.9096
15.6000	0.6500	1.2880	-0.7620	1.2920	-0.7606	1.2912	-0.7569	1.2905	-0.7564
16.2000	0.6750	1.2500	-0.5940	1.2554	-0.5942	1.2543	-0.5896	1.2531	-0.5888
16.8000	0.7000	1.2110	-0.4390	1.2091	-0.4419	1.2169	-0.4370	1.2158	-0.4352
17.4000	0.7250	1.1640	-0.3010	1.1623	-0.3074	1.1737	-0.2994	1.1744	-0.2998
18.0000	0.7500	1.1130	-0.1750	1.1133	-0.1801	1.1232	-0.1697	1.1243	-0.1731
18.6000	0.7750	1.0580	-0.0650	1.0593	-0.0670	1.0675	-0.0608	1.0702	-0.0598
19.2000	0.8000	0.9930	0.0290	0.9948	0.0284	1.0032	0.0354	1.0066	0.0369
19.8000	0.8250	0.9190	0.1080	0.9224	0.1088	0.9285	0.1237	0.9327	0.1169
20.4000	0.8500	0.8330	0.1650	0.8387	0.1685	0.8446	0.1772	0.8472	0.1755
21.0000	0.8750	0.7380	0.2030	0.7440	0.2064	0.7494	0.2154	0.7518	0.2150
21.6000	0.9000	0.6250	0.2110	0.6317	0.2147	0.6371	0.2211	0.6412	0.2231
22.2000	0.9250	0.4980	0.1870	0.5046	0.1920	0.5076	0.2004	0.5140	0.1988
22.8000	0.9500	0.3500	0.1190	0.3574	0.1255	0.3580	0.1314	0.3632	0.1333
23.4000	0.9750	0.1790	-0.0010	0.1864	0.0053	0.1829	0.0104	0.1895	0.0128
24.0000	1.0000	-0.0190	-0.1870	-0.0077	-0.1765	-0.0217	-0.1796	-0.0184	-0.1734

Table 2. Concluded

x, in	x/c	Measured Values				Design Values Wing Tip Radius	
		y = 38.932 in		y = 45.948 in			
		z _u , in	z _p , in	z _u , in	z _p , in		
0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.000	
0.1800	0.0075	0.4580	-0.4583	0.4648	-0.4585	0.461	
0.3000	0.0125	0.5625	-0.5640	0.5681	-0.5613	0.564	
0.6000	0.0250	0.7248	-0.7321	0.7250	-0.7271	0.729	
0.9000	0.0375	0.8299	-0.8446	0.8316	-0.8402	0.837	
1.2000	0.0500	0.9103	-0.9320	0.9109	-0.9273	0.923	
1.8000	0.0750	1.0330	-1.0639	1.0301	-1.0552	1.050	
2.4000	0.1000	1.1199	-1.1560	1.1161	-1.1480	1.141	
3.0000	0.1250	1.1900	-1.2284	1.1842	-1.2206	1.214	
3.6000	0.1500	1.2454	-1.2836	1.2417	-1.2780	1.268	
4.2000	0.1750	1.2929	-1.3283	1.2887	-1.3270	1.313	
4.8000	0.2000	1.3324	-1.3631	1.3308	-1.3633	1.347	
6.0000	0.2500	1.3833	-1.4117	1.3877	-1.4143	1.398	
7.2000	0.3000	1.4138	-1.4310	1.4174	-1.4363	1.424	
8.4000	0.3500	1.4310	-1.4283	1.4336	-1.4394	1.434	
9.6000	0.4000	1.4369	-1.4073	1.4397	-1.4176	1.428	
10.8000	0.4500	1.4329	-1.3670	1.4362	-1.3743	1.403	
12.0000	0.5000	1.4168	-1.3004	1.4208	-1.3049	1.361	
13.2000	0.5500	1.3876	-1.1963	1.3909	-1.1989	1.293	
13.8000	0.5750	1.3689	-1.1224	1.3708	-1.1250	1.248	
14.4000	0.6000	1.3461	-1.0287	1.3476	-1.0315	1.189	
15.0000	0.6250	1.3204	-0.9091	1.3215	-0.9128	1.117	
15.6000	0.6500	1.2891	-0.7564	1.2893	-0.7598	1.025	
16.2000	0.6750	1.2520	-0.5891	1.2509	-0.5927	0.922	
16.8000	0.7000	1.2128	-0.4338	1.2144	-0.4376	0.825	
17.4000	0.7250	1.1698	-0.2965	1.1687	-0.3019	0.732	
18.0000	0.7500	1.1225	-0.1706	1.1209	-0.1761	0.644	
18.6000	0.7750	1.0688	-0.0577	1.0665	-0.0598	0.561	
19.2000	0.8000	1.0052	0.0397	1.0004	0.0357	0.482	
19.8000	0.8250	0.9320	0.1198	0.9280	0.1171	0.405	
20.4000	0.8500	0.8493	0.1811	0.8447	0.1753	0.334	
21.0000	0.8750	0.7546	0.2194	0.7506	0.2131	0.267	
21.6000	0.9000	0.6446	0.2282	0.6387	0.2184	0.207	
22.2000	0.9250	0.5153	0.2058	0.5083	0.1999	0.155	
22.8000	0.9500	0.3661	0.1395	0.3586	0.1306	0.115	
23.4000	0.9750	0.1892	0.0174	0.1809	0.0091	0.090	
24.0000	1.0000	-0.0061	-0.1671	-0.0139	-0.1757	0.084	

Table 3. Airfoil Ordinates Interpolated from Smoothed Measured Ordinates

	y = 1.000 in.		y = 14.932 in.		y = 28.324 in.		y = 38.932 in.		y = 45.948 in.	
x/c	z _u /c	z _r /c								
.0000	.000016	-.000523	.000007	-.000582	.000013	-.000369	.000038	.000015	.000258	.000020
.0001	.001999	-.002516	.001949	-.002534	.001994	-.002358	.002204	-.002152	.002361	-.002079
.0002	.002926	-.003448	.002866	-.003457	.002894	-.003263	.003114	-.003061	.003285	-.003001
.0005	.004776	-.005307	.004699	-.005300	.004693	-.005071	.004927	-.004875	.005127	-.004839
.0010	.006864	-.007406	.006769	-.007382	.006730	-.007117	.006977	-.006926	.007205	-.006914
.0020	.009797	-.010356	.009680	-.010309	.009605	-.010005	.009867	-.009820	.010126	-.009832
.0050	.015407	-.016000	.015257	-.015913	.015168	-.015589	.015439	-.015417	.015722	-.015433
.0100	.021038	-.021671	.020865	-.021541	.020866	-.021302	.021111	-.021149	.021349	-.021089
.0150	.024819	-.025538	.024646	-.025369	.024729	-.025227	.024951	-.025069	.025123	-.024939
.0200	.027728	-.028587	.027574	-.028379	.027692	-.028307	.027909	-.028121	.028019	-.027954
.0250	.030075	-.031088	.029952	-.030850	.030078	-.030821	.030296	-.030611	.030361	-.030425
.0300	.032039	-.033198	.031953	-.032941	.032071	-.032930	.032287	-.032714	.032331	-.032518
.0350	.033726	-.035019	.033677	-.034753	.033777	-.034743	.033990	-.034533	.034025	-.034331
.0400	.035217	-.036630	.035199	-.036366	.035279	-.036348	.035487	-.036145	.035515	-.035938
.0450	.036567	-.038083	.036570	-.037829	.036631	-.037801	.036832	-.037603	.036851	-.037389
.0500	.037807	-.039410	.037823	-.039172	.037869	-.039132	.038062	-.038939	.038068	-.038716
.0550	.038964	-.040636	.038987	-.040417	.039020	-.040368	.039204	-.040179	.039195	-.039942
.0600	.040047	-.041773	.040071	-.041575	.040095	-.041518	.040268	-.041333	.040242	-.041080
.0650	.041062	-.042829	.041083	-.042653	.041100	-.042591	.041263	-.042410	.041217	-.042138
.0700	.042015	-.043814	.042030	-.043659	.042042	-.043594	.042194	-.043414	.042129	-.043124
.0750	.042911	-.044736	.042919	-.044599	.042929	-.044533	.043068	-.044354	.042982	-.044047
.0800	.043755	-.045601	.043756	-.045480	.043766	-.045416	.043891	-.045235	.043784	-.044912
.0850	.044552	-.046416	.044544	-.046307	.044556	-.046246	.044666	-.046061	.044540	-.045727
.0900	.045304	-.047183	.045290	-.047085	.045304	-.047028	.045398	-.046838	.045254	-.046494
.0950	.046016	-.047909	.045995	-.047817	.046013	-.047766	.046090	-.047569	.045930	-.047220
.1000	.046691	-.048596	.046665	-.048508	.046686	-.048463	.046747	-.048258	.046573	-.047907
.1050	.047332	-.049249	.047303	-.049162	.047327	-.049123	.047371	-.048911	.047186	-.048560
.1100	.047942	-.049869	.047911	-.049783	.047938	-.049748	.047966	-.049528	.047772	-.049182
.1150	.048523	-.050460	.048491	-.050371	.048520	-.050342	.048534	-.050114	.048333	-.049775
.1200	.049078	-.051023	.049045	-.050931	.049077	-.050905	.049078	-.050671	.048872	-.050342

Table 3. Continued

	y = 1.000 in.		y = 14.932 in.		y = 28.324 in.		y = 38.932 in.		y = 45.948 in.	
x/c	z _u /c	z _r /c								
.1250	.049609	-.051559	.049576	-.051463	.049610	-.051441	.049600	-.051200	.049391	-.050885
.1300	.050118	-.052071	.050084	-.051971	.050120	-.051950	.050101	-.051705	.049893	-.051407
.1350	.050608	-.052560	.050572	-.052456	.050609	-.052435	.050584	-.052187	.050377	-.051908
.1400	.051078	-.053026	.051041	-.052917	.051078	-.052897	.051050	-.052648	.050846	-.052389
.1450	.051531	-.053470	.051490	-.053358	.051528	-.053336	.051499	-.053088	.051299	-.052852
.1500	.051967	-.053893	.051921	-.053777	.051960	-.053754	.051932	-.053508	.051739	-.053296
.1550	.052388	-.054295	.052334	-.054177	.052374	-.054152	.052350	-.053911	.052165	-.053722
.1600	.052793	-.054677	.052731	-.054558	.052772	-.054530	.052754	-.054296	.052577	-.054132
.1650	.053185	-.055039	.053113	-.054920	.053153	-.054891	.053143	-.054664	.052977	-.054524
.1700	.053561	-.055384	.053479	-.055264	.053519	-.055233	.053518	-.055017	.053363	-.054900
.1750	.053924	-.055711	.053830	-.055592	.053870	-.055559	.053878	-.055353	.053736	-.055260
.1800	.054273	-.056021	.054167	-.055903	.054207	-.055868	.054225	-.055675	.054097	-.055605
.1850	.054608	-.056315	.054491	-.056199	.054530	-.056163	.054557	-.055983	.054444	-.055933
.1900	.054929	-.056593	.054802	-.056479	.054839	-.056442	.054875	-.056276	.054778	-.056247
.1950	.055237	-.056857	.055100	-.056745	.055136	-.056707	.055179	-.056556	.055098	-.056545
.2000	.055531	-.057108	.055386	-.056997	.055420	-.056959	.055469	-.056822	.055406	-.056829
.2050	.055813	-.057344	.055661	-.057236	.055692	-.057198	.055745	-.057075	.055700	-.057098
.2100	.056082	-.057569	.055924	-.057462	.055953	-.057424	.056008	-.057315	.055981	-.057354
.2150	.056338	-.057780	.056175	-.057676	.056202	-.057638	.056258	-.057543	.056250	-.057595
.2200	.056583	-.057980	.056416	-.057877	.056440	-.057840	.056495	-.057758	.056505	-.057823
.2250	.056815	-.058168	.056646	-.058067	.056667	-.058030	.056720	-.057960	.056749	-.058038
.2300	.057036	-.058346	.056866	-.058246	.056884	-.058209	.056934	-.058151	.056980	-.058241
.2350	.057247	-.058512	.057076	-.058414	.057091	-.058377	.057137	-.058329	.057200	-.058431
.2400	.057446	-.058668	.057276	-.058571	.057288	-.058535	.057329	-.058496	.057408	-.058609
.2450	.057635	-.058815	.057467	-.058718	.057476	-.058682	.057511	-.058651	.057605	-.058776
.2500	.057814	-.058952	.057648	-.058855	.057654	-.058819	.057684	-.058794	.057791	-.058932
.2550	.057984	-.059080	.057821	-.058983	.057824	-.058947	.057847	-.058927	.057966	-.059077
.2600	.058144	-.059199	.057985	-.059102	.057986	-.059065	.058002	-.059048	.058131	-.059211
.2650	.058295	-.059309	.058141	-.059212	.058139	-.059174	.058148	-.059158	.058286	-.059335
.2700	.058438	-.059410	.058288	-.059312	.058285	-.059274	.058287	-.059258	.058431	-.059448

Table 3. Continued

y = 1.000 in.			y = 14.932 in.			y = 28.324 in.			y = 38.932 in.			y = 45.948 in.		
x/c	z _u /c	z _r /c												
.2750	.058573	-.059502	.058428	-.059404	.058423	-.059364	.058417	-.059348	.058567	-.059551				
.2800	.058699	-.059586	.058560	-.059486	.058553	-.059446	.058540	-.059427	.058695	-.059644				
.2850	.058819	-.059660	.058685	-.059560	.058676	-.059518	.058656	-.059496	.058814	-.059728				
.2900	.058931	-.059726	.058803	-.059624	.058793	-.059582	.058766	-.059555	.058926	-.059801				
.2950	.059036	-.059784	.058914	-.059681	.058903	-.059638	.058869	-.059604	.059030	-.059865				
.3000	.059136	-.059832	.059018	-.059728	.059006	-.059684	.058966	-.059644	.059128	-.059919				
.3050	.059229	-.059872	.059116	-.059767	.059104	-.059723	.059057	-.059675	.059219	-.059964				
.3100	.059316	-.059904	.059208	-.059798	.059195	-.059753	.059143	-.059697	.059303	-.060000				
.3150	.059398	-.059927	.059294	-.059820	.059281	-.059775	.059223	-.059710	.059382	-.060026				
.3200	.059474	-.059941	.059374	-.059833	.059362	-.059789	.059298	-.059714	.059455	-.060044				
.3250	.059545	-.059947	.059448	-.059839	.059436	-.059794	.059369	-.059709	.059522	-.060052				
.3300	.059611	-.059945	.059517	-.059836	.059506	-.059792	.059434	-.059696	.059584	-.060051				
.3350	.059671	-.059934	.059581	-.059824	.059571	-.059781	.059494	-.059675	.059642	-.060041				
.3400	.059727	-.059915	.059639	-.059805	.059631	-.059763	.059550	-.059646	.059694	-.060022				
.3450	.059779	-.059888	.059693	-.059777	.059686	-.059736	.059602	-.059609	.059742	-.059995				
.3500	.059826	-.059852	.059742	-.059741	.059736	-.059702	.059649	-.059564	.059786	-.059959				
.3550	.059868	-.059808	.059786	-.059697	.059782	-.059660	.059692	-.059511	.059826	-.059914				
.3600	.059907	-.059756	.059826	-.059645	.059824	-.059610	.059731	-.059451	.059863	-.059860				
.3650	.059940	-.059696	.059861	-.059585	.059861	-.059552	.059766	-.059384	.059895	-.059797				
.3700	.059970	-.059627	.059891	-.059516	.059894	-.059486	.059796	-.059308	.059923	-.059726				
.3750	.059995	-.059550	.059917	-.059440	.059923	-.059412	.059823	-.059225	.059948	-.059646				
.3800	.060016	-.059464	.059939	-.059354	.059947	-.059329	.059845	-.059135	.059968	-.059557				
.3850	.060032	-.059370	.059956	-.059261	.059966	-.059238	.059863	-.059037	.059985	-.059459				
.3900	.060044	-.059268	.059968	-.059158	.059982	-.059139	.059877	-.058931	.059998	-.059352				
.3950	.060052	-.059157	.059976	-.059048	.059992	-.059031	.059886	-.058818	.060008	-.059236				
.4000	.060055	-.059037	.059980	-.058928	.059999	-.058914	.059891	-.058697	.060013	-.059111				
.4050	.060054	-.058908	.059979	-.058800	.060001	-.058789	.059892	-.058568	.060015	-.058977				
.4100	.060048	-.058771	.059973	-.058663	.059998	-.058655	.059889	-.058431	.060013	-.058834				
.4150	.060037	-.058625	.059963	-.058517	.059991	-.058512	.059881	-.058286	.060007	-.058681				
.4200	.060022	-.058469	.059948	-.058361	.059979	-.058359	.059869	-.058133	.059996	-.058519				

Table 3. Continued

y = 1.000 in.			y = 14.932 in.			y = 28.324 in.			y = 38.932 in.			y = 45.948 in.		
x/c	z_u/c	z_l/c	z_u/c	z_l/c	z_u/c	z_l/c	z_u/c	z_l/c	z_u/c	z_l/c	z_u/c	z_l/c	z_u/c	z_l/c
.4250	.060002	-.058304	.059929	-.058196	.059962	-.058196	.059852	-.057970	.059982	-.058348				
.4300	.059978	-.058129	.059905	-.058021	.059941	-.058023	.059831	-.057799	.059963	-.058166				
.4350	.059948	-.057945	.059876	-.057836	.059915	-.057841	.059804	-.057618	.059940	-.057974				
.4400	.059914	-.057750	.059843	-.057641	.059884	-.057647	.059774	-.057427	.059912	-.057772				
.4450	.059875	-.057545	.059805	-.057435	.059848	-.057443	.059738	-.057227	.059879	-.057559				
.4500	.059831	-.057329	.059762	-.057219	.059807	-.057228	.059698	-.057016	.059842	-.057336				
.4550	.059781	-.057103	.059714	-.056991	.059761	-.057002	.059653	-.056795	.059800	-.057101				
.4600	.059727	-.056865	.059662	-.056752	.059710	-.056764	.059603	-.056563	.059753	-.056856				
.4650	.059668	-.056616	.059605	-.056502	.059654	-.056514	.059548	-.056319	.059700	-.056599				
.4700	.059603	-.056355	.059543	-.056239	.059593	-.056251	.059488	-.056064	.059642	-.056330				
.4750	.059534	-.056081	.059476	-.055963	.059526	-.055976	.059423	-.055796	.059579	-.056048				
.4800	.059460	-.055794	.059404	-.055674	.059454	-.055687	.059353	-.055515	.059511	-.055754				
.4850	.059380	-.055494	.059327	-.055371	.059377	-.055385	.059278	-.055221	.059437	-.055447				
.4900	.059296	-.055180	.059245	-.055054	.059294	-.055068	.059198	-.054913	.059357	-.055126				
.4950	.059207	-.054851	.059159	-.054723	.059206	-.054737	.059112	-.054590	.059271	-.054791				
.5000	.059114	-.054508	.059067	-.054376	.059112	-.054391	.059021	-.054253	.059180	-.054442				
.5050	.059015	-.054149	.058971	-.054015	.059013	-.054029	.058925	-.053900	.059083	-.054078				
.5100	.058912	-.053774	.058869	-.053636	.058908	-.053651	.058824	-.053531	.058979	-.053699				
.5150	.058803	-.053382	.058763	-.053241	.058798	-.053256	.058718	-.053145	.058870	-.053303				
.5200	.058690	-.052972	.058652	-.052827	.058683	-.052842	.058606	-.052740	.058755	-.052890				
.5250	.058573	-.052543	.058536	-.052395	.058562	-.052410	.058489	-.052317	.058635	-.052458				
.5300	.058450	-.052094	.058415	-.051942	.058436	-.051958	.058367	-.051873	.058509	-.052007				
.5350	.058323	-.051624	.058289	-.051468	.058304	-.051485	.058240	-.051408	.058377	-.051536				
.5400	.058191	-.051132	.058159	-.050973	.058168	-.050990	.058107	-.050922	.058240	-.051044				
.5450	.058054	-.050618	.058024	-.050455	.058027	-.050473	.057970	-.050412	.058097	-.050529				
.5500	.057913	-.050080	.057884	-.049914	.057880	-.049932	.057827	-.049878	.057949	-.049992				
.5550	.057767	-.049517	.057739	-.049347	.057728	-.049367	.057679	-.049319	.057796	-.049430				
.5600	.057616	-.048928	.057590	-.048754	.057572	-.048775	.057526	-.048733	.057637	-.048843				
.5650	.057461	-.048309	.057435	-.048132	.057411	-.048155	.057368	-.048118	.057473	-.048227				
.5700	.057300	-.047660	.057276	-.047480	.057244	-.047504	.057204	-.047472	.057304	-.047580				

Table 3. Continued

y = 1.000 in.			y = 14.932 in.			y = 28.324 in.			y = 38.932 in.			y = 45.948 in.		
x/c	z_u/c	z_r/c	z_u/c	z_r/c	z_u/c	z_r/c	z_u/c	z_r/c	z_u/c	z_r/c	z_u/c	z_r/c	z_u/c	z_r/c
.5750	.057135	-.046977	.057110	-.046795	.057073	-.046821	.057035	-.046792	.057129	-.046902				
.5800	.056965	-.046260	.056939	-.046075	.056897	-.046103	.056860	-.046077	.056948	-.046188				
.5850	.056789	-.045504	.056762	-.045317	.056715	-.045347	.056680	-.045325	.056762	-.045438				
.5900	.056607	-.044709	.056578	-.044520	.056528	-.044551	.056494	-.044532	.056569	-.044647				
.5950	.056420	-.043870	.056387	-.043681	.056335	-.043713	.056301	-.043696	.056370	-.043815				
.6000	.056225	-.042987	.056190	-.042797	.056136	-.042831	.056102	-.042815	.056165	-.042937				
.6050	.056024	-.042055	.055985	-.041866	.055931	-.041900	.055897	-.041886	.055953	-.042012				
.6100	.055816	-.041077	.055772	-.040888	.055718	-.040922	.055684	-.040910	.055734	-.041040				
.6150	.055600	-.040050	.055552	-.039863	.055499	-.039896	.055463	-.039885	.055507	-.040018				
.6200	.055375	-.038975	.055324	-.038791	.055271	-.038821	.055235	-.038813	.055273	-.038949				
.6250	.055143	-.037853	.055087	-.037672	.055036	-.037698	.054998	-.037691	.055031	-.037830				
.6300	.054901	-.036684	.054842	-.036506	.054793	-.036527	.054754	-.036522	.054780	-.036662				
.6350	.054649	-.035472	.054589	-.035298	.054542	-.035312	.054500	-.035309	.054521	-.035451				
.6400	.054388	-.034223	.054328	-.034052	.054282	-.034058	.054239	-.034058	.054254	-.034200				
.6450	.054115	-.032942	.054060	-.032774	.054015	-.032772	.053969	-.032773	.053980	-.032915				
.6500	.053832	-.031635	.053785	-.031469	.053741	-.031458	.053692	-.031459	.053699	-.031603				
.6550	.053536	-.030307	.053503	-.030142	.053460	-.030122	.053406	-.030123	.053411	-.030268				
.6600	.053230	-.028966	.053215	-.028799	.053172	-.028771	.053113	-.028772	.053116	-.028918				
.6650	.052912	-.027619	.052921	-.027449	.052878	-.027414	.052813	-.027412	.052815	-.027560				
.6700	.052584	-.026273	.052620	-.026098	.052577	-.026057	.052506	-.026051	.052508	-.026201				
.6750	.052246	-.024935	.052314	-.024754	.052272	-.024709	.052193	-.024697	.052195	-.024850				
.6800	.051898	-.023612	.052003	-.023422	.051962	-.023375	.051873	-.023355	.051876	-.023513				
.6850	.051542	-.022308	.051685	-.022105	.051646	-.022060	.051549	-.022031	.051552	-.022193				
.6900	.051178	-.021023	.051361	-.020808	.051325	-.020766	.051218	-.020727	.051222	-.020894				
.6950	.050806	-.019762	.051030	-.019532	.050998	-.019495	.050883	-.019445	.050886	-.019619				
.7000	.050429	-.018525	.050692	-.018279	.050665	-.018250	.050542	-.018189	.050545	-.018369				
.7050	.050046	-.017315	.050347	-.017053	.050326	-.017033	.050196	-.016961	.050197	-.017148				
.7100	.049658	-.016131	.049994	-.015853	.049979	-.015843	.049845	-.015761	.049843	-.015954				
.7150	.049265	-.014972	.049633	-.014679	.049625	-.014679	.049488	-.014588	.049482	-.014787				
.7200	.048868	-.013837	.049263	-.013530	.049262	-.013541	.049124	-.013442	.049113	-.013645				

Table 3. Continued

y = 1.000 in.			y = 14.932 in.		y = 28.324 in.		y = 38.932 in.		y = 45.948 in.	
x/c	z_u/c	z_r/c	z_u/c	z_r/c	z_u/c	z_r/c	z_u/c	z_r/c	z_u/c	z_r/c
.7250	.048468	-.012726	.048883	-.012406	.048891	-.012426	.048754	-.012321	.048736	-.012527
.7300	.048064	-.011636	.048493	-.011306	.048511	-.011335	.048376	-.011225	.048351	-.011432
.7350	.047655	-.010568	.048092	-.010231	.048120	-.010266	.047990	-.010154	.047956	-.010359
.7400	.047241	-.009522	.047681	-.009180	.047719	-.009219	.047595	-.009107	.047551	-.009308
.7450	.046820	-.008498	.047259	-.008154	.047308	-.008194	.047190	-.008082	.047135	-.008278
.7500	.046391	-.007496	.046825	-.007152	.046885	-.007190	.046774	-.007080	.046709	-.007270
.7550	.045954	-.006515	.046380	-.006173	.046450	-.006208	.046347	-.006100	.046270	-.006282
.7600	.045506	-.005557	.045922	-.005219	.046002	-.005248	.045907	-.005142	.045820	-.005316
.7650	.045048	-.004622	.045452	-.004287	.045543	-.004311	.045455	-.004207	.045356	-.004372
.7700	.044578	-.003711	.044969	-.003377	.045070	-.003397	.044989	-.003295	.044879	-.003451
.7750	.044095	-.002824	.044473	-.002490	.044583	-.002508	.044509	-.002407	.044388	-.002554
.7800	.043599	-.001963	.043964	-.001624	.044083	-.001643	.044014	-.001543	.043883	-.001683
.7850	.043088	-.001128	.043440	-.000780	.043567	-.000805	.043504	-.000704	.043363	-.000837
.7900	.042563	-.000319	.042903	-.000039	.043037	-.000006	.042979	-.000110	.042829	-.000019
.7950	.042022	.000462	.042350	.000833	.042491	.000790	.042437	.000896	.042280	.000771
.8000	.041466	.001215	.041783	.001600	.041928	.001545	.041881	.001656	.041716	.001531
.8050	.040893	.001940	.041200	.002340	.041349	.002270	.041308	.002387	.041138	.002261
.8100	.040304	.002634	.040602	.003049	.040752	.002966	.040719	.003090	.040545	.002959
.8150	.039698	.003299	.039988	.003727	.040137	.003630	.040114	.003762	.039937	.003626
.8200	.039076	.003933	.039358	.004373	.039505	.004264	.039492	.004404	.039313	.004260
.8250	.038436	.004536	.038711	.004984	.038856	.004866	.038854	.005014	.038674	.004860
.8300	.037779	.005106	.038047	.005559	.038188	.005436	.038199	.005592	.038018	.005427
.8350	.037104	.005643	.037366	.006098	.037503	.005973	.037526	.006136	.037346	.005960
.8400	.036410	.006145	.036667	.006598	.036799	.006475	.036836	.006646	.036655	.006456
.8450	.035697	.006612	.035949	.007059	.036076	.006942	.036127	.007120	.035946	.006916
.8500	.034963	.007042	.035211	.007479	.035335	.007372	.035399	.007556	.035218	.007337
.8550	.034209	.007434	.034453	.007858	.034574	.007765	.034651	.007955	.034469	.007720
.8600	.033433	.007787	.033674	.008196	.033793	.008119	.033882	.008313	.033699	.008062
.8650	.032635	.008099	.032872	.008491	.032991	.008431	.033092	.008631	.032906	.008364
.8700	.031813	.008368	.032047	.008744	.032168	.008701	.032278	.008906	.032089	.008625

Table 3. Concluded

y = 1.000 in.			y = 14.932 in.			y = 28.324 in.			y = 38.932 in.			y = 45.948 in.		
x/c	z _u /c	z _r /c												
.8750	.030967	.008594	.031198	.008954	.031323	.008927	.031441	.009137	.031246	.008844				
.8800	.030096	.008774	.030323	.009121	.030454	.009107	.030578	.009322	.030377	.009019				
.8850	.029200	.008906	.029422	.009243	.029561	.009239	.029688	.009459	.029481	.009149				
.8900	.028277	.008989	.028494	.009317	.028643	.009322	.028771	.009547	.028555	.009230				
.8950	.027327	.009020	.027539	.009341	.027698	.009352	.027825	.009583	.027600	.009262				
.9000	.026350	.008998	.026554	.009314	.026726	.009328	.026849	.009564	.026614	.009240				
.9050	.025344	.008919	.025540	.009231	.025724	.009248	.025841	.009490	.025596	.009163				
.9100	.024309	.008781	.024495	.009091	.024692	.009109	.024800	.009356	.024545	.009027				
.9150	.023244	.008581	.023418	.008890	.023628	.008908	.023726	.009158	.023460	.008829				
.9200	.022147	.008315	.022309	.008623	.022530	.008641	.022616	.008895	.022340	.008564				
.9250	.021018	.007980	.021165	.008287	.021397	.008306	.021471	.008561	.021185	.008229				
.9300	.019856	.007573	.019986	.007879	.020227	.007899	.020288	.008154	.019994	.007821				
.9350	.018660	.007092	.018772	.007397	.019020	.007420	.019068	.007672	.018766	.007338				
.9400	.017429	.006536	.017522	.006839	.017775	.006866	.017811	.007114	.017502	.006778				
.9450	.016165	.005904	.016235	.006202	.016493	.006236	.016516	.006479	.016201	.006140				
.9500	.014867	.005195	.014912	.005487	.015172	.005529	.015185	.005765	.014863	.005422				
.9550	.013533	.004407	.013550	.004688	.013813	.004741	.013815	.004969	.013488	.004622				
.9600	.012162	.003529	.012146	.003796	.012409	.003863	.012407	.004083	.012075	.003731				
.9650	.010749	.002550	.010694	.002797	.010955	.002881	.010958	.003094	.010622	.002736				
.9700	.009291	.001459	.009189	.001678	.009444	.001781	.009466	.001989	.009127	.001628				
.9750	.007784	.000243	.007625	.000425	.007870	.000549	.007929	.000756	.007589	.000392				
.9800	.006226	-.001106	.005998	-.000970	.006230	-.000823	.006347	-.000613	.006008	-.000978				
.9850	.004626	-.002568	.004319	-.002488	.004532	-.002316	.004727	-.002098	.004390	-.002462				
.9900	.002994	-.004116	.002600	-.004100	.002792	-.003902	.003079	-.003672	.002745	-.004033				
.9950	.001340	-.005723	.000854	-.005775	.001023	-.005550	.001412	-.005306	.001081	-.005664				
1.000	-.000325	-.007359	-.000905	-.007481	-.000761	-.007229	-.000265	-.006971	-.000592	-.007324				

Table 4. Static Test Cases for the Rectangular Supercritical Wing

Test Case No.	Point	M	α_o , deg.	Comments
6E1	212	.404	2.22	vs M, $\alpha_o = 2^\circ$
6E2	394	.604	2.00	
6E3	364	.701	2.00	
6E4	331	.753	2.05	
6E5	152	.802	2.00	
6E6	462	.828	2.00	
6E7	276	.850	2.01	
6E8	423	.876	2.00	
6E9	251	.907	2.00	
6E10	489	.803	1.99	Repeat of 152
6E11	214	.403	.21	vs M, $\alpha_o = 0^\circ$
6E12	154	.801	.03	
6E13	464	.821	-.01	
6E14	253	.901	.00	
6E15	210	.403	4.20	vs M, $\alpha_o = 4^\circ$
6E16	150	.803	3.99	
6E17	460	.828	4.00	
6E18	249	.903	4.00	
6E19	604	.400	7.01	vs α_o , M=.4
6E20	607	.400	9.97	
6E21	609	.401	12.00	
6E22	628	.826	.00	With transition
6E23	626	.825	2.00	strip
6E24	624	.826	4.00	
6E25	52	.802	-.05	Air
6E26	53	.802	2.01	
6E27	54	.801	4.01	

Table 5. Dynamic Test Cases for the Rectangular Supercritical Wing

Test Case No.	Point	M	q psf	α_{\circ} deg.	θ deg.	f Hz	k	Comments
6E28	514	.402	54.8	1.97	1.003	10.00	.309	vs M, $\alpha_{\circ} = 2^{\circ}$
6E29	344	.750	100.8	2.05	1.052	14.99	.249	
6E30	316	.802	107.6	2.08	1.035	15.03	.233	
6E31	475	.826	108.1	1.97	1.023	15.01	.228	
6E32	289	.854	113.7	1.99	1.006	14.96	.219	
6E33	435	.875	115.2	1.96	.987	14.99	.215	
6E34	264	.894	116.8	2.01	1.032	14.99	.210	
6E35	513	.403	54.7	1.97	1.008	5.02	.155	vs k, $\alpha_{\circ} = 2^{\circ}$
6E36	515	.402	54.7	1.98	1.020	15.06	.466	M = .40
6E37	516	.402	54.8	1.98	1.060	19.97	.617	
6E38	494	.803	106.1	2.19	1.069	1.98	.031	vs k, $\alpha_{\circ} = 2^{\circ}$
6E39	493	.802	105.8	1.89	1.025	3.00	.047	M = .80
6E40	495	.803	106.1	1.84	1.080	3.95	.062	
6E41	314	.803	107.7	2.10	1.080	4.95	.077	
6E42	315	.804	107.9	2.08	1.057	9.96	.154	
6E43	317	.802	107.5	2.07	1.039	20.01	.311	
6E44	473	.825	107.8	1.98	1.070	4.97	.076	vs k, $\alpha_{\circ} = 2^{\circ}$
6E45	474	.825	107.8	1.97	1.038	9.96	.152	M = .825
6E46	476	.825	108.0	1.97	1.035	20.07	.305	
6E47	262	.896	117.1	2.00	1.022	4.96	.069	vs k, $\alpha_{\circ} = 2^{\circ}$
6E48	263	.896	117.1	2.00	.989	9.95	.139	M = .90
6E49	265	.902	118.3	2.01	1.055	19.99	.278	
6E50	481	.823	107.6	-.03	1.023	15.01	.229	vs α_{\circ} , M = .825
6E51	469	.822	107.2	3.99	1.018	15.04	.230	
6E52	269	.901	118.2	-.03	1.065	14.98	.208	vs α_{\circ} , M = .90
6E53	258	.900	117.9	4.03	1.024	14.95	.208	
6E54	632	.825	108.7	1.98	1.014	10.03	.152	With Transition
6E55	633	.826	108.9	1.98	.984	15.03	.228	Strip, M = .825
6E56	634	.826	108.9	1.98	1.005	20.09	.305	
6E57	180	.802	108.0	3.30	.500	15.12	.234	vs θ , $\alpha_{\circ} = 3.3^{\circ}$
6E58	184	.801	107.8	3.30	.983	15.03	.233	M = .80
6E59	189	.802	108.2	3.29	1.513	14.99	.232	
6E60	613	.402	54.4	11.99	1.004	5.00	.155	vs k, $\alpha_{\circ} = 12^{\circ}$
6E61	614	.401	54.2	12.00	.998	10.02	.312	M = .40
6E62	615	.401	54.2	12.01	1.012	14.99	.466	
6E63	616	.401	54.3	12.02	1.087	19.99	.621	



Figure 1. Rectangular supercritical wing installed in wind tunnel.




Figure 2. Diagram of wing and splitter plate in wind tunnel. Dimensions in inches (mm).




Figure 3. Instrumentation layout for the RSW model.




Figure 4. Lift coefficient vs. Mach number.




Figure 5. Airfoil for rectangular supercritical wing.







Figure 6. Comparison of the design and measured coordinates.




(b) Span station 14.932 in.



(c) Span station 28.324 in.



(d) Span station 38.932 in.



(e) Span station 45.948 in.

Figure 6. Concluded.





Figure 7. Plot of interpolated ordinates and slopes of smoothed measured airfoil, $y = 28.324$ in.

Point Number = 212 Mach Number = 0.404 Alphao = 2.22, deg.

q	H	V	Rn	gamma	Cp*			
111.6	1322.4	203.9	.804E+07	1.135	-3.961			
x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	0.988		0.956		0.984		1.011	
.025	-1.055	-0.001	-1.135	-0.060	-1.004	-0.055	-0.814	-0.119
.050	-0.867	-0.148	-0.838	-0.057	-0.751	-0.202	-0.706	-0.235
.100	-0.718	-0.188	-0.628	-0.201	-0.613	-0.245	-0.489	-0.243
.200	-0.496	-0.218	-0.458	-0.259	-0.479	-0.238	-0.336	-0.244
.260	-0.409	-0.147	-0.357	-0.127	-0.270	-0.141	-0.203	-0.133
.320	-0.353	-0.106	-0.376	-0.150	-0.279	-0.123	-0.153	-0.093
.380	-0.307	-0.082	-0.323	-0.146	-0.218	-0.124	-0.177	-0.111
.440	-0.414	-0.127	-0.297	-0.029	-0.202	0.000	-0.178	-0.187
.500	-0.323	-0.124	-0.291	-0.149	-0.235	-0.166	-0.141	-0.158
.560	-0.325	-0.122	-0.250	-0.124	-0.266	-0.362	-0.151	-0.166
.620	-0.347	-0.054	-0.308	-0.009	-0.254	-0.105	-0.120	-0.116
.700	-0.387	0.218	-0.390	0.197	-0.320	0.209	-0.223	0.081
.800	-0.419	0.367	-0.349	0.361	-0.346	0.340	-0.259	0.294
.900	-0.337	0.438	-0.323	0.489	-0.305	0.424	-0.289	0.344




(a) Test case 6E1 (point 212).

Figure 8. Static test cases.

Point Number = 394 Mach Number = 0.604 Alphao = 2.00, deg.


η	H	V	Rn	gamma	C_p^*			
81.3	482.6	303.9	.403E+07	1.131	-1.410			
x/c	$y/s = 0.309$		$y/s = 0.588$		$y/s = 0.809$		$y/s = 0.951$	
	C_{pu}	C_{pl}	C_{pu}	C_{pl}	C_{pu}	C_{pl}	C_{pu}	C_{pl}
.000	1.104		1.035		1.056		1.069	
.025	-1.065	-0.043	-1.212	-0.118	-1.106	-0.093	-0.870	-0.146
.050	-0.933	-0.229	-0.901	-0.045	-0.808	-0.265	-0.773	-0.300
.100	-0.779	-0.279	-0.689	-0.247	-0.691	-0.316	-0.539	-0.294
.200	-0.504	-0.067	-0.465	-0.136	-0.925	-0.135	-0.370	-0.146
.260	-0.463	-0.218	-0.418	-0.185	-0.331	-0.197	-0.249	-0.237
.320	-0.405	-0.135	-0.427	-0.183	-0.307	-0.172	-0.197	-0.152
.380	-0.350	-0.121	-0.369	-0.201	-0.260	-0.168	-0.199	-0.152
.440	-0.353	-0.179	-0.348	-0.073	-0.243	0.000	-0.216	-0.209
.500	-0.381	-0.194	-0.338	-0.205	-0.285	-0.241	-0.178	-0.197
.560	-0.383	-0.176	-0.302	-0.247	-0.294	-0.221	-0.169	-0.218
.620	-0.421	-0.018	-0.372	-0.067	-0.327	-0.129	-0.177	-0.164
.700	-0.436	0.248	-0.422	0.210	-0.346	0.244	-0.252	0.054
.800	-0.471	0.411	-0.381	0.398	-0.388	0.359	-0.282	0.347
.900	-0.360	0.491	-0.351	0.581	-0.325	0.455	-0.333	0.378



(b) Test case 6E2 (point 394).
Figure 8. Continued.

Point Number = 364 Mach Number = 0.701 Alphao = 2.00, deg.


q	H	V	Rn	gamma	Cp*			
92.7	438.2	351.1	.402E+07	1.131	-0.863			
x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	1.151		1.085		1.106		1.111	
.025	-1.019	-0.070	-1.252	-0.140	-1.197	-0.106	-0.920	-0.158
.050	-1.036	-0.267	-1.015	-0.093	-0.882	-0.304	-0.851	-0.340
.100	-0.845	-0.325	-0.786	-0.296	-0.786	-0.366	-0.615	-0.334
.200	-0.544	-0.234	-0.509	-0.280	-0.942	-0.246	-0.399	-0.248
.260	-0.518	-0.271	-0.469	-0.261	-0.375	-0.261	-0.285	-0.283
.320	-0.454	-0.192	-0.462	-0.242	-0.354	-0.228	-0.229	-0.222
.380	-0.403	-0.185	-0.413	-0.258	-0.315	-0.225	-0.230	-0.190
.440	-0.429	-0.229	-0.400	-0.146	-0.293	0.000	-0.241	-0.244
.500	-0.427	-0.250	-0.405	-0.263	-0.317	-0.288	-0.202	-0.244
.560	-0.426	-0.228	-0.353	-0.308	-0.341	-0.252	-0.196	-0.261
.620	-0.468	-0.119	-0.418	-0.098	-0.356	-0.124	-0.203	-0.186
.700	-0.439	0.253	-0.460	0.231	-0.369	0.253	-0.263	0.062
.800	-0.503	0.424	-0.424	0.424	-0.420	0.367	-0.294	0.360
.900	-0.360	0.505	-0.361	0.581	-0.339	0.471	-0.362	0.392



(c) Test case 6E3 (point 364).
Figure 8. Continued.

Point Number = 331 Mach Number = 0.753 Alphao = 2.05, deg.


q	H	V	Rn	gamma	Cp*			
101.3	432.8	380.5	.400E+07	1.131	-0.648			
x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	1.177		1.129		1.140		1.133	
.025	-0.849	-0.078	-1.051	-0.156	-1.033	-0.111	-0.869	-0.150
.050	-1.082	-0.288	-1.003	-0.138	-1.042	-0.302	-0.954	-0.360
.100	-1.027	-0.356	-1.003	-0.324	-0.912	-0.406	-0.663	-0.352
.200	-0.459	-0.292	-0.473	-0.339	-0.219	-0.330	-0.405	-0.321
.260	-0.549	-0.283	-0.498	-0.263	-0.377	-0.236	-0.283	-0.288
.320	-0.458	-0.218	-0.493	-0.239	-0.336	-0.205	-0.221	-0.218
.380	-0.407	-0.193	-0.409	-0.261	-0.313	-0.230	-0.213	-0.204
.440	-0.363	-0.253	-0.337	-0.176	-0.290	-0.001	-0.234	-0.260
.500	-0.440	-0.271	-0.473	-0.278	-0.312	-0.304	-0.225	-0.253
.560	-0.460	-0.233	-0.358	-0.364	-0.329	-0.294	-0.200	-0.268
.620	-0.474	0.167	-0.412	-0.106	-0.330	-0.209	-0.218	-0.166
.700	-0.506	0.267	-0.478	0.240	-0.385	0.262	-0.259	0.096
.800	-0.526	0.422	-0.458	0.415	-0.433	0.383	-0.301	0.365
.900	-0.342	0.517	-0.348	0.563	-0.334	0.510	-0.389	0.408



(d) Test case 6E4 (point 331).
Figure 8. Continued.

Point Number = 152 Mach Number = 0.802 Alphao = 2.00, deg.


q	H	V	Rn	gamma	Cp*			
106.1	415.9	403.5	.401E+07	1.133	-0.479			
x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	1.187		1.164		1.166		1.159	
.025	-0.666	-0.092	-0.826	-0.151	-0.845	-0.117	-0.739	-0.156
.050	-0.906	-0.310	-0.857	-0.201	-0.944	-0.307	-0.995	-0.398
.100	-0.930	-0.399	-0.904	-0.381	-0.961	-0.460	-0.824	-0.416
.200	-0.907	-0.350	-0.897	-0.414	-0.874	-0.362	-0.429	-0.370
.260	-0.936	-0.378	-0.945	-0.399	-0.362	-0.324	-0.340	-0.345
.320	-0.849	-0.296	-0.841	-0.314	-0.336	-0.283	-0.265	-0.274
.380	-0.471	-0.289	-0.230	-0.359	-0.323	-0.292	-0.263	-0.247
.440	-0.183	-0.329	-0.318	-0.269	-0.310	0.000	-0.275	-0.313
.500	-0.404	-0.344	-0.391	-0.366	-0.342	-0.366	-0.249	-0.303
.560	-0.444	-0.291	-0.374	-0.398	-0.358	-0.331	-0.230	-0.335
.620	-0.511	-0.013	-0.451	-0.093	-0.373	-0.113	-0.226	-0.193
.700	-0.550	0.260	-0.522	0.258	-0.402	0.204	-0.258	0.130
.800	-0.608	0.392	-0.553	0.440	-0.478	0.335	-0.313	0.314
.900	-0.319	0.499	-0.353	0.602	-0.338	0.478	-0.396	0.393



(e) Test case 6E5 (point 152).
Figure 8. Continued.

Point Number = 462 Mach Number = 0.828 Alphao = 2.00, deg.


q	H	V	Rn	gamma	Cp*			
108.0	406.5	414.0	.400E+07	1.132	-0.400			
x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	1.217		1.172		1.183		1.175	
.025	-0.571	-0.098	-0.755	-0.174	-0.751	-0.124	-0.664	-0.164
.050	-0.798	-0.333	-0.764	-0.190	-0.835	-0.349	-0.929	-0.429
.100	-0.842	-0.434	-0.815	-0.402	-0.892	-0.498	-0.848	-0.458
.200	-0.839	-0.415	-0.825	-0.455	-1.004	-0.400	-0.438	-0.379
.260	-0.883	-0.447	-0.873	-0.459	-0.754	-0.420	-0.501	-0.375
.320	-0.821	-0.325	-0.898	-0.365	-0.536	-0.317	-0.300	-0.297
.380	-0.745	-0.345	-0.839	-0.398	-0.321	-0.323	-0.290	-0.279
.440	-0.696	-0.371	-0.605	-0.309	-0.320	-0.001	-0.293	-0.336
.500	-0.790	-0.406	-0.315	-0.416	-0.345	-0.416	-0.263	-0.337
.560	-0.740	-0.296	-0.294	-0.393	-0.342	-0.345	-0.246	-0.363
.620	-0.328	0.133	-0.397	-0.073	-0.372	-0.103	-0.243	-0.191
.700	-0.410	0.226	-0.484	0.244	-0.397	0.186	-0.253	0.136
.800	-0.606	0.357	-0.569	0.423	-0.507	0.312	-0.314	0.307
.900	-0.300	0.498	-0.318	0.579	-0.323	0.469	-0.426	0.400



(f) Test case 6E6 (point 462).
Figure 8. Continued.

Point Number = 276 Mach Number = 0.850 Alphao = 2.01, deg.


q	H	V	Rn	gamma	Cp*			
112.6	410.3	427.6	.400E+07	1.131	-0.338			
x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	1.232		1.186		1.196		1.188	
.025	-0.476	-0.092	-0.659	-0.167	-0.667	-0.108	-0.585	-0.145
.050	-0.711	-0.328	-0.669	-0.167	-0.734	-0.332	-0.848	-0.419
.100	-0.762	-0.440	-0.747	-0.394	-0.821	-0.510	-0.853	-0.490
.200	-0.753	-0.412	-0.764	-0.490	-0.834	-0.480	-0.538	-0.435
.260	-0.846	-0.458	-0.858	-0.455	-0.783	-0.412	-0.453	-0.438
.320	-0.808	-0.425	-0.869	-0.456	-0.704	-0.434	-0.396	-0.347
.380	-0.764	-0.420	-0.841	-0.474	-0.535	-0.360	-0.332	-0.303
.440	-0.754	-0.417	-0.779	-0.363	-0.402	0.000	-0.330	-0.358
.500	-0.757	-0.430	-0.885	-0.449	-0.429	-0.457	-0.309	-0.426
.560	-0.789	-0.367	-0.687	-0.463	-0.407	-0.338	-0.273	-0.388
.620	-0.829	0.186	-0.305	-0.037	-0.372	-0.042	-0.252	-0.155
.700	-0.910	0.228	-0.427	0.247	-0.378	0.185	-0.265	0.109
.800	-0.315	0.420	-0.509	0.458	-0.510	0.296	-0.309	0.330
.900	-0.268	0.540	-0.304	0.607	-0.296	0.483	-0.443	0.406



(g) Test case 6E7 (point 276).
Figure 8. Continued.

Point Number = 423 Mach Number = 0.876 Alphao = 2.00, deg.
 q H V Rn gamma Cp*
 115.0 404.0 438.6 .401E+07 1.132 -0.269


x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	1.246		1.203		1.209		1.197	
.025	-0.409	-0.066	-0.593	-0.144	-0.587	-0.096	-0.527	-0.125
.050	-0.638	-0.305	-0.602	-0.151	-0.689	-0.306	-0.771	-0.403
.100	-0.695	-0.414	-0.681	-0.374	-0.750	-0.479	-0.807	-0.481
.200	-0.714	-0.496	-0.706	-0.535	-1.082	-0.544	-0.640	-0.483
.260	-0.784	-0.484	-0.779	-0.501	-0.764	-0.459	-0.456	-0.439
.320	-0.758	-0.421	-0.814	-0.462	-0.758	-0.455	-0.458	-0.415
.380	-0.709	-0.454	-0.774	-0.545	-0.556	-0.458	-0.382	-0.401
.440	-0.691	-0.562	-0.743	-0.494	-0.545	-0.001	-0.404	-0.429
.500	-0.747	-0.680	-0.856	-0.660	-0.516	-0.595	-0.394	-0.440
.560	-0.768	-0.456	-0.780	-0.615	-0.512	-0.198	-0.363	-0.521
.620	-0.824	0.068	-0.814	-0.049	-0.536	-0.026	-0.323	-0.157
.700	-0.921	0.093	-0.715	0.147	-0.469	0.079	-0.279	0.111
.800	-0.371	0.381	-0.352	0.424	-0.460	0.207	-0.302	0.290
.900	-0.177	0.488	-0.209	0.574	-0.227	0.420	-0.401	0.419



(h) Test case 6E8 (point 423).
Figure 8. Continued.

Point Number = 251 Mach Number = 0.907 Alphao = 2.00, deg.

q	H	V	Rn	gamma	Cp*			
117.7	397.5	452.3	.401E+07	1.133	-0.194			
x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	1.274		1.223		1.226		1.218	
.025	-0.315	-0.025	-0.485	-0.095	-0.512	-0.027	-0.430	-0.078
.050	-0.535	-0.250	-0.499	-0.067	-0.487	-0.267	-0.693	-0.341
.100	-0.606	-0.364	-0.585	-0.329	-0.687	-0.415	-0.756	-0.472
.200	-0.614	-0.417	-0.614	-0.468	-0.807	-0.495	-0.626	-0.443
.260	-0.719	-0.484	-0.726	-0.527	-0.702	-0.512	-0.448	-0.517
.320	-0.708	-0.430	-0.733	-0.528	-0.741	-0.503	-0.457	-0.474
.380	-0.676	-0.474	-0.754	-0.560	-0.664	-0.526	-0.440	-0.459
.440	-0.640	-0.540	-0.789	-0.520	-0.568	0.002	-0.435	-0.518
.500	-0.695	-0.645	-0.846	-0.669	-0.573	-0.632	-0.417	-0.538
.560	-0.725	-0.768	-0.795	-0.741	-0.597	-0.204	-0.436	-0.637
.620	-0.761	-0.459	-0.830	-0.302	-0.595	-0.005	-0.471	-0.206
.700	-0.777	-0.285	-0.803	-0.242	-0.673	-0.116	-0.447	-0.261
.800	-0.275	-0.069	-0.383	0.039	-0.399	-0.145	-0.286	0.202
.900	-0.230	0.157	-0.099	0.337	-0.042	0.100	-0.267	0.358




(i) Test case 6E9 (point 251).

Figure 8. Continued.

Point Number = 489 Mach Number = 0.803 Alphao = 1.99, deg.


q	H	V	Rn	gamma	Cp*			
105.8	414.7	402.7	.400E+07	1.132	-0.476			
x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	1.193		1.157		1.168		1.163	
.025	-0.665	-0.099	-0.852	-0.174	-0.828	-0.134	-0.731	-0.168
.050	-0.897	-0.327	-0.852	-0.196	-0.959	-0.336	-0.979	-0.416
.100	-0.924	-0.413	-0.894	-0.388	-0.945	-0.474	-0.806	-0.424
.200	-0.896	-0.378	-0.879	-0.424	-0.992	-0.379	-0.429	-0.355
.260	-0.899	-0.361	-0.901	-0.344	-0.411	-0.314	-0.351	-0.306
.320	-0.786	-0.284	-0.740	-0.320	-0.335	-0.277	-0.262	-0.270
.380	-0.526	-0.277	-0.290	-0.343	-0.280	-0.276	-0.252	-0.249
.440	-0.357	-0.324	-0.294	-0.261	-0.299	-0.001	-0.270	-0.304
.500	-0.405	-0.349	-0.395	-0.366	-0.344	-0.380	-0.255	-0.285
.560	-0.436	-0.290	-0.371	-0.373	-0.336	-0.333	-0.239	-0.335
.620	-0.514	0.167	-0.450	-0.108	-0.371	-0.217	-0.241	-0.198
.700	-0.580	0.254	-0.515	0.246	-0.406	0.193	-0.248	0.164
.800	-0.607	0.394	-0.554	0.422	-0.481	0.342	-0.313	0.297
.900	-0.324	0.515	-0.345	0.571	-0.340	0.475	-0.407	0.400



(j) Test case 6E10 (point 489).
Figure 8. Continued.

Point Number = 214 Mach Number = 0.403 Alphao = 0.21, deg.

q	H	V	Rn	gamma	Cp*			
111.1	1322.8	203.4	.802E+07	1.135	-3.983			
x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	1.060		1.039		1.046		1.044	
.025	-0.593	-0.348	-0.683	-0.411	-0.637	-0.370	-0.537	-0.355
.050	-0.553	-0.407	-0.547	-0.303	-0.511	-0.429	-0.524	-0.402
.100	-0.515	-0.368	-0.444	-0.370	-0.455	-0.394	-0.382	-0.345
.200	-0.373	-0.338	-0.346	-0.382	-0.389	-0.329	-0.278	-0.311
.260	-0.306	-0.236	-0.265	-0.208	-0.200	-0.206	-0.157	-0.174
.320	-0.268	-0.180	-0.301	-0.215	-0.221	-0.175	-0.115	-0.122
.380	-0.236	-0.145	-0.259	-0.202	-0.179	-0.166	-0.145	-0.136
.440	-0.348	-0.180	-0.238	-0.076	-0.165	0.000	-0.153	-0.200
.500	-0.268	-0.170	-0.243	-0.190	-0.204	-0.192	-0.123	-0.164
.560	-0.277	-0.160	-0.209	-0.214	-0.237	-0.369	-0.141	-0.168
.620	-0.305	-0.070	-0.272	-0.034	-0.230	-0.115	-0.110	-0.101
.700	-0.358	0.198	-0.362	0.179	-0.299	0.207	-0.211	0.090
.800	-0.396	0.348	-0.330	0.340	-0.333	0.327	-0.235	0.299
.900	-0.324	0.418	-0.313	0.470	-0.295	0.410	-0.229	0.339




(k) Test case 6E11 (point 214).

Figure 8. Continued.

Point Number = 154 Mach Number = 0.801 Alphao = 0.03, deg.

	q	H	V	Rn	gamma	Cp*				
	106.0	416.2	403.1	.401E+07	1.133	-0.482				
x/c	y/s = 0.309	y/s = 0.588	y/s = 0.809	y/s = 0.951	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	1.197	1.174	1.180	1.165						
.025	-0.405	-0.381	-0.586	-0.525	-0.381	-0.381	-0.586	-0.525	-0.384	-0.384
.050	-0.589	-0.595	-0.641	-0.691	-0.595	-0.595	-0.641	-0.691	-0.624	-0.624
.100	-0.653	-0.657	-0.714	-0.550	-0.657	-0.657	-0.714	-0.550	-0.550	-0.550
.200	-0.526	-0.562	-0.542	-0.431	-0.562	-0.562	-0.542	-0.431	-0.348	-0.431
.260	-0.575	-0.487	-0.453	-0.314	-0.487	-0.487	-0.453	-0.314	-0.278	-0.314
.320	-0.388	-0.384	-0.375	-0.220	-0.384	-0.384	-0.375	-0.220	-0.263	-0.263
.380	-0.356	-0.373	-0.316	-0.228	-0.373	-0.373	-0.316	-0.228	-0.277	-0.277
.440	-0.270	-0.393	-0.293	-0.254	-0.393	-0.393	-0.293	0.000	-0.254	-0.328
.500	-0.451	-0.384	-0.331	-0.240	-0.384	-0.384	-0.331	-0.381	-0.240	-0.305
.560	-0.444	-0.292	-0.345	-0.228	-0.292	-0.292	-0.345	-0.314	-0.228	-0.315
.620	-0.497	0.040	-0.362	-0.229	0.040	0.040	-0.362	-0.090	-0.229	-0.144
.700	-0.527	0.206	-0.393	0.124	0.206	0.206	-0.393	0.176	-0.257	0.124
.800	-0.566	0.295	-0.445	0.265	0.295	0.295	-0.445	0.278	-0.281	0.265
.900	-0.284	0.399	-0.301	-0.263	0.399	0.399	-0.301	0.393	-0.263	0.342




(I) Test case 6E12 (point 154).

Figure 8. Continued.

Point Number = 464 Mach Number = 0.821 Alphao = -0.01, deg.

q	H	V	Rn	gamma	Cp*			
106.8	406.3	410.6	.398E+07	1.132	-0.420			
x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	1.213		1.179		1.190		1.177	
.025	-0.365	-0.360	-0.546	-0.450	-0.555	-0.377	-0.492	-0.373
.050	-0.543	-0.577	-0.549	-0.408	-0.578	-0.557	-0.703	-0.620
.100	-0.647	-0.695	-0.647	-0.661	-0.730	-0.719	-0.630	-0.598
.200	-0.603	-0.709	-0.594	-0.747	-0.621	-0.614	-0.346	-0.456
.260	-0.527	-0.625	-0.595	-0.634	-0.408	-0.475	-0.313	-0.333
.320	-0.539	-0.431	-0.421	-0.458	-0.324	-0.344	-0.235	-0.295
.380	-0.349	-0.357	-0.357	-0.375	-0.284	-0.346	-0.245	-0.304
.440	-0.350	-0.398	-0.357	-0.332	-0.301	-0.001	-0.266	-0.343
.500	-0.473	-0.442	-0.437	-0.438	-0.351	-0.420	-0.254	-0.332
.560	-0.500	-0.309	-0.393	-0.401	-0.354	-0.312	-0.250	-0.325
.620	-0.500	0.099	-0.462	-0.052	-0.387	-0.096	-0.255	-0.132
.700	-0.589	0.208	-0.538	0.210	-0.406	0.169	-0.263	0.130
.800	-0.581	0.321	-0.550	0.337	-0.480	0.269	-0.287	0.250
.900	-0.266	0.436	-0.276	0.494	-0.286	0.397	-0.276	0.336



(m) Test case 6E13 (point 464).


Figure 8. Continued.

Point Number = 253 Mach Number = 0.901 Alphao = 0.00, deg.

q	H	V	Rn
116.9	397.5	449.9	.400E+07

gamma	Cp*	
1.133	-0.208	

x/c	$\eta/s = 0.309$		$\eta/s = 0.588$		$\eta/s = 0.809$		$\eta/s = 0.951$	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	1.276		1.227		1.227		1.218	
.025	-0.171	-0.210	-0.347	-0.299	-0.388	-0.216	-0.308	-0.234
.050	-0.343	-0.406	-0.342	-0.207	-0.296	-0.399	-0.554	-0.454
.100	-0.483	-0.561	-0.474	-0.511	-0.586	-0.588	-0.637	-0.626
.200	-0.480	-0.568	-0.490	-0.614	-0.648	-0.636	-0.534	-0.535
.260	-0.576	-0.649	-0.561	-0.662	-0.588	-0.653	-0.490	-0.585
.320	-0.556	-0.576	-0.605	-0.654	-0.577	-0.632	-0.399	-0.467
.380	-0.551	-0.575	-0.602	-0.691	-0.527	-0.630	-0.365	-0.500
.440	-0.592	-0.636	-0.626	-0.654	-0.474	0.001	-0.370	-0.548
.500	-0.628	-0.742	-0.677	-0.774	-0.493	-0.698	-0.355	-0.582
.560	-0.660	-0.597	-0.614	-0.420	-0.517	-0.521	-0.378	-0.546
.620	-0.695	-0.408	-0.623	-0.263	-0.513	-0.114	-0.424	-0.121
.700	-0.693	-0.284	-0.665	-0.229	-0.592	-0.078	-0.434	-0.215
.800	-0.507	-0.100	-0.588	-0.011	-0.565	0.069	-0.301	0.160
.900	-0.179	0.105	-0.063	0.265	-0.094	0.320	-0.193	0.275




(n) Test case 6E14 (point 253).

Figure 8. Continued.

Point Number = 210 Mach Number = 0.403 Alphao = 4.20, deg.

q	H	V	Rn	gamma	Cp*			
111.0	1321.4	203.3	.803E+07	1.135	-3.983			
x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	0.778		0.761		0.827		0.916	
.025	-1.576	0.296	-1.634	0.239	-1.409	0.216	-1.101	0.097
.050	-1.202	0.090	-1.147	0.168	-1.003	0.004	-0.886	-0.078
.100	-0.931	-0.018	-0.818	-0.038	-0.772	-0.103	-0.593	-0.143
.200	-0.616	-0.108	-0.567	-0.153	-0.564	-0.146	-0.392	-0.186
.260	-0.507	-0.056	-0.447	-0.046	-0.343	-0.072	-0.218	-0.044
.320	-0.437	-0.030	-0.449	-0.079	-0.329	-0.065	-0.151	-0.030
.380	-0.376	-0.018	-0.385	-0.088	-0.269	-0.075	-0.192	-0.074
.440	-0.481	-0.070	-0.353	0.019	-0.240	0.000	-0.179	-0.140
.500	-0.372	-0.074	-0.336	-0.106	-0.261	-0.135	-0.139	-0.096
.560	-0.369	-0.081	-0.289	-0.015	-0.289	-0.337	-0.149	-0.138
.620	-0.382	-0.036	-0.340	0.019	-0.275	-0.085	-0.127	-0.121
.700	-0.409	0.238	-0.413	0.213	-0.343	0.214	-0.245	0.067
.800	-0.435	0.382	-0.363	0.377	-0.362	0.348	-0.301	0.287
.900	-0.341	0.453	-0.327	0.500	-0.317	0.434	-0.369	0.339




(o) Test case 6E15 (point 210).

Figure 8. Continued.

Point Number = 150 Mach Number = 0.803 Alphao = 3.99, deg.


Q	H	V	Rn	gamma	Cp*			
106.2	415.5	403.7	.401E+07	1.133	-0.476			
x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	1.147		1.119		1.131		1.125	
.025	-0.920	0.152	-1.028	0.099	-1.019	0.115	-0.990	0.041
.050	-1.105	-0.070	-1.103	0.024	-1.160	-0.094	-1.176	-0.206
.100	-1.167	-0.189	-1.136	-0.185	-1.186	-0.270	-1.128	-0.288
.200	-1.141	-0.233	-1.107	-0.298	-1.187	-0.275	-0.547	-0.323
.260	-1.182	-0.245	-1.177	-0.273	-1.004	-0.242	-0.491	-0.298
.320	-1.154	-0.197	-1.155	-0.223	-0.458	-0.222	-0.330	-0.202
.380	-1.109	-0.204	-1.073	-0.281	-0.352	-0.243	-0.295	-0.224
.440	-0.882	-0.254	-0.522	-0.203	-0.321	0.000	-0.295	-0.297
.500	-0.527	-0.282	-0.215	-0.314	-0.328	-0.344	-0.260	-0.295
.560	-0.235	-0.256	-0.243	-0.429	-0.340	-0.340	-0.237	-0.343
.620	-0.323	-0.029	-0.347	-0.099	-0.349	-0.151	-0.230	-0.222
.700	-0.431	0.289	-0.465	0.280	-0.389	0.232	-0.269	0.119
.800	-0.546	0.437	-0.509	0.473	-0.511	0.384	-0.366	0.322
.900	-0.345	0.533	-0.373	0.620	-0.367	0.518	-0.594	0.396



(p) Test case 6E16 (point 150).
Figure 8. Continued.

Point Number = 460 Mach Number = 0.828 Alphao = 4.00, deg.


Q	H	V	Rn	gamma	Cp*			
107.9	406.3	413.7	.401E+07	1.132	-0.400			
x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	1.186		1.140		1.151		1.152	
.025	-0.806	0.137	-0.938	0.069	-0.917	0.099	-0.883	0.027
.050	-0.988	-0.098	-0.990	0.029	-1.029	-0.136	-1.098	-0.235
.100	-1.060	-0.221	-1.028	-0.207	-1.099	-0.292	-1.083	-0.323
.200	-1.038	-0.259	-1.002	-0.315	-1.001	-0.291	-0.618	-0.315
.260	-1.100	-0.274	-1.100	-0.302	-1.006	-0.284	-0.553	-0.324
.320	-1.083	-0.218	-1.093	-0.277	-0.931	-0.255	-0.437	-0.242
.380	-1.058	-0.242	-1.069	-0.320	-0.561	-0.272	-0.390	-0.263
.440	-1.034	-0.297	-1.054	-0.249	-0.407	0.000	-0.358	-0.326
.500	-0.866	-0.345	-1.068	-0.372	-0.387	-0.394	-0.301	-0.338
.560	-0.925	-0.295	-0.439	-0.439	-0.352	-0.370	-0.269	-0.389
.620	-0.914	0.040	-0.217	-0.101	-0.353	-0.149	-0.252	-0.230
.700	-0.226	0.276	-0.351	0.277	-0.373	0.214	-0.267	0.120
.800	-0.414	0.434	-0.460	0.481	-0.497	0.369	-0.363	0.332
.900	-0.325	0.558	-0.354	0.625	-0.352	0.521	-0.659	0.417



(q) Test case 6E17 (point 460).
Figure 8. Continued.

Point Number = 249 Mach Number = 0.903 Alphao = 4.00, deg.

q	H	V	Rn	gamma	Cp*			
116.9	396.6	450.3	.400E+07	1.133	-0.203			
x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	1.260		1.204		1.206		1.204	
.025	-0.501	0.145	-0.629	0.084	-0.651	0.138	-0.609	0.065
.050	-0.679	-0.085	-0.680	0.084	-0.651	-0.119	-0.825	-0.207
.100	-0.778	-0.221	-0.746	-0.184	-0.846	-0.283	-0.899	-0.338
.200	-0.761	-0.238	-0.750	-0.308	-0.921	-0.340	-0.754	-0.358
.260	-0.869	-0.342	-0.858	-0.385	-0.832	-0.376	-0.534	-0.454
.320	-0.869	-0.320	-0.863	-0.388	-0.877	-0.386	-0.527	-0.350
.380	-0.858	-0.390	-0.881	-0.449	-0.841	-0.445	-0.487	-0.422
.440	-0.788	-0.458	-0.924	-0.414	-0.664	0.002	-0.493	-0.498
.500	-0.803	-0.548	-0.989	-0.577	-0.650	-0.568	-0.474	-0.494
.560	-0.782	-0.685	-0.926	-0.700	-0.663	-0.427	-0.487	-0.616
.620	-0.845	-0.311	-0.940	-0.290	-0.658	0.007	-0.510	-0.328
.700	-0.799	-0.230	-0.892	-0.166	-0.727	-0.099	-0.418	-0.242
.800	-0.323	-0.059	-0.402	0.167	-0.363	-0.042	-0.379	0.302
.900	-0.308	0.199	-0.147	0.432	-0.084	0.231	-0.403	0.416




(r) Test case 6E18 (point 249).
Figure 8. Continued.

Point Number = 604 Mach Number = 0.400 Alphao = 7.01, deg.

q	H	V	Rn	gamma	Cp*
54.1	652.8	201.8	.400E+07	1.132	-4.058


x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	0.328		0.291		0.446		0.678	
.025	-2.396	0.610	-2.393	0.544	-2.081	0.532	-1.536	0.361
.050	-1.659	0.350	-1.560	0.558	-1.268	0.240	-1.094	0.121
.100	-1.218	0.177	-1.059	0.184	-1.021	0.078	-0.756	-0.011
.200	-0.755	0.076	-0.665	-0.040	-0.766	0.011	-0.484	-0.086
.260	-0.653	0.050	-0.544	0.057	-0.426	-0.055	-0.295	-0.153
.320	-0.538	0.074	-0.523	-0.038	-0.337	-0.048	-0.247	0.022
.380	-0.452	0.129	-0.476	-0.009	-0.381	-0.080	-0.246	-0.032
.440	-0.957	0.028	-0.485	0.174	-0.242	0.002	-0.256	-0.129
.500	-0.421	0.009	-0.315	-0.030	-0.299	-0.090	-0.202	-0.162
.560	-0.435	0.010	-0.319	0.125	-0.324	-0.106	-0.162	-0.141
.620	-0.417	-0.136	-0.378	0.096	-0.331	-0.006	-0.150	-0.117
.700	-0.400	0.281	-0.432	0.221	-0.369	0.301	-0.333	-0.083
.800	-0.456	0.420	-0.339	0.410	-0.394	0.344	-0.396	0.373
.900	-0.343	0.476	-0.315	0.627	-0.322	0.462	-0.554	0.330



(s) Test case 6E19 (point 604).
Figure 8. Continued.

Point Number = 607 Mach Number = 0.400 Alphao = 9.97, deg.

	54.1	652.8	q	H	V	Rn	gamma	C_p^*
x/c								
			$y/s = 0.309$	$y/s = 0.588$	$y/s = 0.809$	$y/s = 0.951$		
			C_{pu}	C_{pl}	C_{pu}	C_{pl}	C_{pu}	C_{pl}
.000			-0.372		-0.358		-0.104	0.329
.025			-3.734	0.826	-3.490	0.772	-2.929	0.774
.050			-2.195	0.583	-2.059	0.779	-1.678	0.463
.100			-1.516	0.373	-1.337	0.373	-1.254	0.257
.200			-0.922	0.217	-0.813	0.096	-0.908	0.129
.260			-0.790	0.167	-0.668	0.162	-0.518	0.040
.320			-0.650	0.172	-0.614	0.057	-0.420	0.038
.380			-0.549	0.215	-0.556	0.074	-0.444	-0.010
.440			-1.281	0.106	-0.543	0.248	-0.293	0.002
.500			-0.482	0.077	-0.376	0.041	-0.346	-0.043
.560			-0.484	0.070	-0.366	0.171	-0.373	-0.075
.620			-0.455	-0.100	-0.413	0.131	-0.370	0.030
.700			-0.410	0.310	-0.454	0.246	-0.397	0.344
.800			-0.458	0.437	-0.351	0.427	-0.423	0.343
.900			-0.324	0.488	-0.303	0.629	-0.335	0.472




(t) Test case 6E20 (point 607).

Figure 8. Continued.

Point Number = 609 Mach Number = 0.401 Alphao = 12.00, deg.

q	H	V	Rn	gamma	Cp*			
54.2	652.8	202.0	.401E+07	1.132	-4.034			
x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	-0.903		-0.869		-0.563		0.027	
.025	-4.813	0.922	-3.814	0.879	-3.708	0.892	-2.514	0.700
.050	-2.490	0.705	-2.358	0.905	-1.941	0.589	-1.377	0.431
.100	-1.707	0.487	-1.514	0.487	-1.402	0.366	-1.007	0.207
.200	-1.030	0.304	-0.910	0.183	-0.990	0.206	-0.622	0.044
.260	-0.885	0.241	-0.750	0.214	-0.580	0.105	-0.416	-0.054
.320	-0.725	0.232	-0.674	0.119	-0.471	0.095	-0.368	0.095
.380	-0.614	0.267	-0.608	0.130	-0.491	0.044	-0.349	0.031
.440	-0.816	0.156	-0.597	0.300	-0.328	0.002	-0.323	-0.091
.500	-0.523	0.122	-0.417	0.082	-0.374	-0.009	-0.245	-0.125
.560	-0.515	0.109	-0.396	0.245	-0.398	-0.041	-0.220	-0.126
.620	-0.475	-0.074	-0.432	0.157	-0.395	0.059	-0.245	-0.121
.700	-0.406	0.327	-0.461	0.263	-0.418	0.373	-0.485	-0.187
.800	-0.442	0.447	-0.348	0.439	-0.442	0.341	-0.622	0.388
.900	-0.290	0.494	-0.284	0.630	-0.343	0.475	-0.884	0.298




(u) Test case 6E21 (point 609).

Figure 8. Continued.

Point Number = 628 Mach Number = 0.826 Alphao = 0.00, deg.

q	H	V	Rn	gamma	Cp*			
108.6	410.3	413.8	.401E+07	1.132	-0.406			
x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	1.189		1.182		1.193		1.178	
.025	-0.380	-0.346	-0.535	-0.427	-0.545	-0.379	-0.487	-0.368
.050	-0.496	-0.492	-0.506	-0.391	-0.563	-0.530	-0.650	-0.609
.100	-0.722	-0.690	-0.703	-0.717	-0.764	-0.731	-0.740	-0.609
.200	-0.614	-0.705	-0.594	-0.711	-0.468	-0.621	-0.376	-0.426
.260	-0.514	-0.630	-0.586	-0.644	-0.463	-0.503	-0.336	-0.390
.320	-0.025	-0.551	-0.019	-0.578	-0.016	-0.403	-0.011	-0.313
.380	-0.427	-0.413	-0.397	-0.421	-0.298	-0.367	-0.244	-0.313
.440	-0.228	-0.415	-0.368	-0.358	-0.310	-0.001	-0.264	-0.349
.500	-0.457	-0.416	-0.439	-0.401	-0.349	-0.412	-0.253	-0.338
.560	-0.470	-0.259	-0.391	-0.221	-0.347	-0.002	-0.249	-0.327
.620	-0.496	0.117	-0.451	-0.023	-0.377	-0.127	-0.250	-0.108
.700	-0.556	0.130	-0.502	0.132	-0.391	0.133	-0.259	0.134
.800	-0.493	0.188	-0.462	0.196	-0.427	0.205	-0.276	0.192
.900	-0.180	0.287	-0.199	0.331	-0.228	0.314	-0.251	0.288




(v) Test case 6E22 (point 628).

Figure 8. Continued.

Point Number = 626 Mach Number = 0.825 Alphao = 2.00, deg.

q	H	V	Rn	gamma	Cp*			
108.5	410.1	413.4	.401E+07	1.132	-0.409			
x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	1.184		1.171		1.180		1.173	
.025	-0.616	-0.092	-0.768	-0.160	-0.761	-0.136	-0.675	-0.165
.050	-0.834	-0.295	-0.793	-0.213	-0.883	-0.333	-0.928	-0.419
.100	-0.849	-0.424	-0.814	-0.424	-0.877	-0.494	-0.862	-0.468
.200	-0.875	-0.409	-0.868	-0.420	-0.908	-0.389	-0.456	-0.370
.260	-0.841	-0.438	-0.873	-0.429	-0.649	-0.407	-0.479	-0.321
.320	-0.036	-0.365	-0.040	-0.391	-0.020	-0.329	-0.014	-0.287
.380	-0.703	-0.344	-0.817	-0.413	-0.325	-0.331	-0.278	-0.289
.440	-0.460	-0.384	-0.336	-0.327	-0.314	-0.001	-0.283	-0.337
.500	-0.659	-0.393	-0.353	-0.381	-0.335	-0.398	-0.258	-0.338
.560	-0.347	-0.265	-0.333	-0.236	-0.332	-0.302	-0.244	-0.352
.620	-0.393	0.103	-0.409	-0.009	-0.358	-0.134	-0.238	-0.153
.700	-0.476	0.164	-0.466	0.153	-0.382	0.144	-0.244	0.138
.800	-0.483	0.231	-0.456	0.218	-0.428	0.225	-0.288	0.204
.900	-0.201	0.342	-0.220	0.349	-0.248	0.339	-0.361	0.322




(w) Test case 6E23 (point 628).

Figure 8. Continued.

Point Number = 624 Mach Number = 0.826 Alphao = 4.01, deg.

q	H	V	Rn	gamma	Cp*			
108.5	409.8	413.7	.401E+07	1.132	-0.406			
x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	1.164		1.139		1.146		1.150	
.025	-0.841	0.144	-0.956	0.088	-0.934	0.092	-0.904	0.028
.050	-1.024	-0.073	-1.028	-0.005	-1.108	-0.115	-1.108	-0.227
.100	-1.072	-0.213	-1.057	-0.223	-1.096	-0.290	-1.115	-0.327
.200	-1.078	-0.274	-1.046	-0.289	-1.065	-0.290	-0.620	-0.312
.260	-1.054	-0.277	-1.060	-0.260	-1.019	-0.277	-0.568	-0.272
.320	-0.048	-0.268	-0.048	-0.293	-0.034	-0.262	-0.020	-0.260
.380	-1.005	-0.250	-1.044	-0.320	-0.463	-0.274	-0.356	-0.266
.440	-1.045	-0.323	-1.021	-0.256	-0.368	-0.001	-0.333	-0.326
.500	-0.925	-0.354	-0.590	-0.342	-0.343	-0.374	-0.286	-0.335
.560	-0.950	-0.263	-0.331	-0.201	-0.323	-0.318	-0.258	-0.369
.620	-0.442	0.101	-0.308	-0.013	-0.336	-0.157	-0.241	-0.189
.700	-0.317	0.200	-0.358	0.191	-0.365	0.156	-0.251	0.138
.800	-0.351	0.284	-0.384	0.268	-0.428	0.260	-0.337	0.205
.900	-0.199	0.400	-0.233	0.393	-0.277	0.379	-0.528	0.334




(x) Test case 6E24 (point 624).

Figure 8. Continued.

Point Number = 52 Mach Number = 0.802 Alphao = -0.05, deg.


q	H	V	Rn	gamma	Cp*			
93.2	315.9	878.4	.117E+07	1.400	-0.429			
x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	1.211		1.178		1.179		1.172	
.025	-0.339	-0.316	-0.458	-0.359	-0.482	-0.315	-0.462	-0.324
.050	-0.520	-0.523	-0.521	-0.399	-0.601	-0.479	-0.619	-0.544
.100	-0.632	-0.650	-0.645	-0.620	-0.691	-0.655	-0.586	-0.576
.200	-0.612	-0.654	-0.615	-0.711	-0.584	-0.571	-0.416	-0.453
.260	-0.615	-0.541	-0.598	-0.538	-0.490	-0.448	-0.409	-0.305
.320	-0.541	-0.522	-0.544	-0.506	-0.427	-0.431	-0.305	-0.377
.380	-0.499	-0.460	-0.457	-0.441	-0.305	-0.360	-0.226	-0.307
.440	-0.451	-0.462	-0.271	-0.415	-0.288	-0.003	-0.263	-0.316
.500	-0.487	-0.462	-0.418	-0.431	-0.347	-0.448	-0.290	-0.343
.560	-0.461	-0.393	-0.398	-0.318	-0.310	-0.395	-0.293	-0.376
.620	-0.509	0.138	-0.455	-0.166	-0.374	-0.490	-0.312	-0.217
.700	-0.567	0.258	-0.493	0.254	-0.394	0.224	-0.239	0.250
.800	-0.573	0.416	-0.557	0.393	-0.455	0.419	-0.281	0.219
.900	-0.384	0.504	-0.298	0.455	-0.344	0.507	-0.275	0.387



(y) Test case 6E25 (point 52).
Figure 8. Continued.

Point Number = 53 Mach Number = 0.802 Alphao = 2.01, deg.


q	H	V	Rn	gamma	Cp*			
93.2	315.9	878.4	.117E+07	1.400	-0.429			
x/c	y/s = 0.309		y/s = 0.588		y/s = 0.809		y/s = 0.951	
	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl	Cpu	Cpl
.000	1.193		1.159		1.165		1.157	
.025	-0.597	-0.059	-0.727	-0.097	-0.733	-0.077	-0.691	-0.117
.050	-0.811	-0.274	-0.782	-0.182	-0.919	-0.260	-0.865	-0.344
.100	-0.864	-0.378	-0.855	-0.360	-0.883	-0.413	-0.777	-0.401
.200	-0.869	-0.386	-0.859	-0.429	-0.791	-0.394	-0.516	-0.366
.260	-0.913	-0.353	-0.908	-0.330	-0.766	-0.313	-0.453	-0.210
.320	-0.839	-0.367	-0.838	-0.334	-0.690	-0.329	-0.312	-0.313
.380	-0.792	-0.340	-0.780	-0.338	-0.179	-0.271	-0.262	-0.277
.440	-0.710	-0.371	-0.442	-0.381	-0.288	-0.004	-0.286	-0.281
.500	-0.652	-0.369	-0.277	-0.350	-0.351	-0.369	-0.299	-0.313
.560	-0.281	-0.319	-0.311	-0.278	-0.285	-0.298	-0.290	-0.355
.620	-0.386	0.096	-0.399	-0.360	-0.355	-0.629	-0.299	-0.319
.700	-0.527	0.253	-0.465	0.252	-0.391	0.167	-0.218	0.265
.800	-0.562	0.441	-0.532	0.444	-0.449	0.427	-0.306	0.206
.900	-0.393	0.528	-0.324	0.494	-0.353	0.504	-0.393	0.413



(z) Test case 6E26 (point 53).
Figure 8. Continued.

Point Number = 54 Mach Number = 0.801 Alphao = 4.01, deg.

	Q	H	V	Rn	gamma	Cp*
	93.4	317.4	879.8	.117E+07	1.400	-0.432
x/c		y/s = 0.309	y/s = 0.588	y/s = 0.809	y/s = 0.951	
		Cpu	Cpl	Cpu	Cpl	Cpu
						Cpl
.000		1.149		1.116		1.130
.025	-0.840	0.172	-0.927	0.136	-0.912	0.136
.050	-1.012	-0.048	-1.016	0.022	-1.167	-0.054
.100	-1.086	-0.173	-1.071	-0.166	-1.084	-0.235
.200	-1.077	-0.230	-1.057	-0.276	-1.078	-0.274
.260	-1.114	-0.214	-1.116	-0.191	-0.975	-0.202
.320	-1.071	-0.248	-1.055	-0.216	-0.950	-0.243
.380	-1.021	-0.231	-0.971	-0.241	-0.447	-0.197
.440	-0.994	-0.276	-0.840	-0.298	-0.270	-0.004
.500	-0.989	-0.287	-0.762	-0.272	-0.336	-0.319
.560	-0.626	-0.240	-0.322	-0.180	-0.265	-0.231
.620	-0.270	0.182	-0.277	-0.281	-0.329	-0.604
.700	-0.394	0.191	-0.357	0.154	-0.373	0.051
.800	-0.415	0.429	-0.419	0.408	-0.431	0.401
.900	-0.364	0.521	-0.288	0.483	-0.361	0.483




(aa) Test case 6E27 (point 54).

Figure 8. Continued.

Point Number = 514		Mach Number = 0.402		Alphao = 1.97, deg.				
q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg	
54.8	655.0	203.1	.403E+07	1.132	10.00	0.309	1.003	
y/s = 0.309				y/s = 0.588				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t
.000	-3.584	1.171			-3.489	1.093		
.025	-12.245	3.908	8.456	-2.425	-11.537	3.682	8.324	-2.262
.050	-8.347	2.174	6.599	-1.633	-7.610	1.827	6.241	-1.407
.100	-5.382	0.699	4.702	-0.611	-4.541	0.517	4.365	-0.544
.200	-3.196	-0.134	3.022	0.180	-2.907	-0.193	2.845	0.249
.260	-2.592	-0.434	2.335	0.552	-2.345	-0.507	2.083	0.609
.320	-2.078	-0.627	1.961	0.618	-1.884	-0.671	1.805	0.718
.380	-1.734	-0.740	1.671	0.741	-1.527	-0.778	1.500	0.828
.440	-1.436	-0.826	1.500	0.828	-1.341	-0.871	1.270	0.876
.500	-1.260	-0.889	1.221	0.846	-1.083	-0.840	1.075	0.941
.560	-0.996	-0.857	1.043	0.976	-0.943	-0.831	0.876	0.901
.620	-0.812	-0.883	0.765	1.068	-0.763	-0.850	0.594	0.976
.700	-0.504	-0.762	0.665	0.929	-0.461	-0.789	0.500	0.898
.800	-0.194	-0.537	0.578	0.708	-0.214	-0.530	0.538	0.667
.900	0.144	-0.093	0.399	0.486	0.104	-0.137	0.397	0.411
y/s = 0.809				y/s = 0.951				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t
.000	-2.848	0.844			-1.592	0.459		
.025	-10.232	3.070	6.003	-2.124	-7.402	2.164	5.976	-1.748
.050	-6.788	1.580	4.345	-1.316	-4.892	1.156	4.331	-1.048
.100	-4.042	0.339	2.667	-0.453	-2.736	0.186	2.670	-0.285
.200	-2.384	-0.272	1.481	0.193	-1.578	-0.258	1.466	0.240
.260	-2.069	-0.432	2.060	0.559	-1.117	-0.438	-1.214	1.800
.320	-1.461	-0.651	1.107	0.639	-0.898	-0.500	-0.132	1.192
.380	-1.305	-0.709	0.833	0.763	-0.699	-0.589	0.846	0.477
.440	-1.001	-0.760	-0.612	0.000	-0.632	-0.579	0.488	0.560
.500	-0.765	-0.770	0.499	0.889	-0.526	-0.524	0.278	0.689
.560	-0.607	-0.830	0.359	0.876	-0.342	-0.527	0.079	0.681
.620	-0.467	-0.786	0.213	0.875	-0.450	-0.438	-0.353	0.653
.700	-0.330	-0.665	0.198	0.820	-0.309	-0.411	-0.182	0.661
.800	-0.148	-0.492	0.164	0.704	-0.789	-0.129	-0.036	0.513
.900	0.000	-0.171	0.140	0.574	-1.523	0.244	-0.106	0.326

(a-1) Tabulated data for test case 6E28 (point 514)

Figure 9. Dynamic test cases.



(a-2) Plot of data for test case 6E28 (point 514)
Figure 9. Continued.

Point Number = 344 Mach Number = 0.750 Alphao = 2.05, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
100.8	432.8	378.9	.400E+07	1.131	14.99	0.249	1.052


y/s = 0.309					y/s = 0.588				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	

.000	-0.817	0.720			-1.153	0.822		
.025	-7.352	6.235	7.115	-4.124	-6.050	5.076	7.278	-4.168
.050	-8.681	7.362	6.623	-3.778	-8.846	7.163	6.257	-3.313
.100	-10.716	8.223	5.683	-2.216	-10.544	7.633	5.151	-2.081
.200	-12.333	7.178	3.853	-0.728	-5.649	1.190	3.726	-0.491
.260	-1.576	-5.723	3.319	0.145	-1.320	-3.285	2.787	0.752
.320	-1.857	-2.950	2.621	0.500	-1.703	-2.125	2.557	0.544
.380	-1.937	-2.426	2.217	0.755	-1.573	-1.950	2.055	0.873
.440	-1.587	-2.009	1.907	0.934	-1.179	-1.767	1.722	1.047
.500	-1.328	-2.060	1.474	1.028	-1.014	-1.742	1.235	1.230
.560	-0.904	-1.922	0.994	1.227	-0.796	-1.611	0.762	1.321
.620	-0.532	-1.774	0.387	1.531	-0.481	-1.447	0.069	1.414
.700	-0.059	-1.306	0.799	0.819	-0.081	-1.032	0.628	0.890
.800	0.491	-0.510	0.749	0.326	0.567	-0.424	0.925	0.326
.900	0.551	0.527	0.583	0.296	0.473	0.270	0.596	0.057

y/s = 0.809					y/s = 0.951				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	

.000	-0.854	0.585			-0.639	0.416		
.025	-5.976	4.736	5.637	-3.607	-7.109	4.849	5.678	-2.893
.050	-10.187	8.103	5.039	-2.866	-9.932	7.084	5.051	-2.313
.100	-11.262	6.847	3.195	-1.676	-2.933	-0.221	3.260	-0.880
.200	-2.283	-1.031	1.843	-0.287	-2.014	0.060	1.851	0.036
.260	-2.176	-1.128	1.238	0.362	-1.654	-0.337	1.095	0.609
.320	-1.628	-1.187	1.187	0.646	-1.341	-0.456	-0.044	1.252
.380	-1.258	-1.284	0.930	0.740	-1.011	-0.644	0.806	0.648
.440	-1.048	-1.253	-0.159	0.000	-0.780	-0.680	0.489	0.722
.500	-0.822	-1.285	0.475	1.096	-0.603	-0.703	0.285	0.823
.560	-0.543	-1.129	0.180	1.172	-0.371	-0.666	-0.052	0.870
.620	-0.390	-1.133	-0.342	1.143	-0.205	-0.563	-0.643	0.946
.700	-0.215	-0.901	0.333	0.865	-0.167	-0.402	-0.049	0.706
.800	0.060	-0.432	0.439	0.365	-0.867	0.085	0.259	0.416
.900	0.109	0.189	0.419	0.151	-2.530	1.007	0.010	0.436

(b-1) Tabulated data for test case 6E29 (point 344)
Figure 9. Continued.



(b-2) Plot of data for test case 6E29 (point 344)

Figure 9. Continued.

Point Number = 316 Mach Number = 0.802 Alphao = 2.08, deg.

q,psf 107.6	H,psf 422.0	V,fps 404.9	Rn .401E+07	gamma 1.131	freq,Hz 15.03	k 0.233	theta,deg 1.035
----------------	----------------	----------------	----------------	----------------	------------------	------------	--------------------


y/s = 0.309				y/s = 0.588				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.282	0.476			-0.397	0.600		
.025	-4.813	3.996	5.969	-3.391	-3.796	3.312	6.105	-3.596
.050	-4.595	3.911	5.896	-3.515	-5.988	5.007	5.455	-3.061
.100	-4.272	3.942	5.648	-2.421	-4.149	3.581	5.126	-2.368
.200	-3.898	4.678	4.361	-0.769	-4.031	4.638	4.044	-0.655
.260	-4.813	7.763	3.759	0.197	-10.280	13.741	3.459	0.767
.320	-9.489	18.152	3.084	0.667	-14.445	15.063	2.679	0.698
.380	-11.881	13.288	2.517	1.012	-7.603	0.745	2.132	1.177
.440	-9.965	-1.489	1.846	1.222	-1.657	-7.797	1.691	1.251
.500	-4.391	-9.679	1.218	1.209	-1.826	-6.961	0.932	1.307
.560	-3.405	-9.306	0.388	1.558	-0.891	-5.688	0.177	1.484
.620	0.070	-6.643	-0.737	1.911	-0.196	-4.868	-0.309	1.406
.700	1.809	-4.997	1.189	0.454	1.141	-2.942	0.789	0.696
.800	3.179	0.452	1.415	-0.482	2.375	0.166	1.196	-0.435
.900	0.706	2.040	0.958	-0.751	0.737	1.970	0.712	-0.615

y/s = 0.809				y/s = 0.951				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.362	0.419			-0.283	0.341		
.025	-3.634	2.901	4.928	-3.001	-5.221	3.738	4.946	-2.487
.050	-5.929	4.818	4.947	-2.693	-4.265	3.442	4.967	-2.316
.100	-3.700	3.083	3.368	-2.026	-5.540	4.765	3.487	-0.889
.200	-7.198	11.430	2.042	-0.241	-1.952	1.159	2.037	0.218
.260	-6.005	4.541	1.466	0.553	-2.803	1.190	1.239	0.836
.320	-2.975	-1.208	1.490	0.805	-2.048	-0.050	0.148	1.599
.380	-2.755	-1.755	0.945	1.096	-1.820	-0.481	0.776	0.865
.440	-2.100	-2.049	-0.367	0.000	-1.422	-0.858	0.454	0.887
.500	-1.531	-2.568	0.329	1.234	-1.069	-1.122	0.111	0.879
.560	-0.969	-2.593	-0.301	1.372	-0.646	-1.161	-0.421	0.903
.620	-0.381	-2.462	-0.782	1.228	-0.307	-1.121	-0.772	0.869
.700	0.117	-1.768	0.375	0.692	-0.136	-0.819	0.036	0.552
.800	0.718	-0.293	0.386	0.103	-0.664	-0.015	0.339	0.187
.900	0.230	1.252	0.250	-0.426	-2.607	1.346	0.105	0.256

(c-1) Tabulated of data for test case 6E30 (point 316)
Figure 9. Continued.



(c-3) Plot of data for test case 6E30 (point 316)
Figure 9. Continued.


Point Number = 475 Mach Number = 0.826 Alphao = 1.97, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
108.1	408.1	413.8	.400E+07	1.132	15.01	0.228	1.023

y/s = 0.309					y/s = 0.588				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	
.000	-0.056	0.274			-0.187	0.208			
.025	-4.081	3.053	5.528	-3.414	-3.324	2.380	5.753	-3.581	
.050	-4.417	3.163	5.420	-3.683	-5.466	3.715	5.065	-3.202	
.100	-3.967	2.925	5.432	-3.023	-3.630	2.430	4.801	-2.885	
.200	-3.376	2.773	5.321	-1.749	-3.104	2.206	5.564	-2.373	
.260	-4.747	2.524	5.424	-0.840	-4.255	2.487	5.308	0.371	
.320	-5.623	3.365	4.865	0.272	-3.159	2.415	5.255	0.312	
.380	-5.735	2.541	4.055	1.771	-3.511	5.797	3.370	2.413	
.440	-1.101	1.414	2.012	2.106	-6.626	17.912	2.060	2.655	
.500	-3.356	13.363	1.066	1.907	-2.543	1.033	0.828	2.675	
.560	-8.472	15.603	-0.904	2.050	-3.103	-3.684	0.030	2.464	
.620	-8.364	-0.791	-2.732	2.051	-3.113	-4.176	0.034	1.512	
.700	-4.826	-10.541	2.128	0.700	-3.749	-5.237	0.177	0.878	
.800	2.084	-8.485	2.362	-0.704	1.679	-4.033	-0.068	-0.612	
.900	1.389	2.750	1.209	-1.471	1.016	2.428	-0.040	-0.503	

y/s = 0.809					y/s = 0.951				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	
.000	-0.193	0.203			-0.106	0.130			
.025	-3.235	2.215	4.698	-2.945	-4.527	2.796	4.715	-2.465	
.050	-5.231	3.462	4.985	-2.832	-3.495	2.227	4.985	-2.673	
.100	-3.245	2.099	4.055	-2.866	-3.332	2.737	4.293	-1.631	
.200	-3.158	2.228	2.741	-0.802	-1.778	2.983	2.799	-0.078	
.260	-4.904	5.681	2.852	-0.288	-0.715	1.072	2.774	0.681	
.320	-0.343	5.310	2.034	1.222	-1.275	1.774	0.729	2.118	
.380	-2.116	2.001	1.334	1.757	-1.300	1.150	1.067	1.370	
.440	-2.293	0.903	-0.598	0.000	-1.369	0.641	0.692	1.407	
.500	-2.498	-0.333	0.409	2.049	-1.282	0.130	0.226	1.495	
.560	-2.047	-1.269	-0.751	1.869	-1.021	-0.299	-0.755	1.374	
.620	-1.699	-1.861	-1.198	1.121	-0.799	-0.615	-1.053	1.162	
.700	-1.034	-1.987	0.357	1.044	-0.597	-0.668	-0.014	0.672	
.800	0.494	-1.606	0.389	0.138	-1.008	0.019	0.392	-0.008	
.900	0.482	1.255	0.133	-0.948	-2.787	1.775	0.200	-0.101	

(d-1) Tabulated of data for test case 6E31 (point 475)
Figure 9. Continued.



(d-2) Plot of data for test case 6E31 (point 475)

Figure 9. Continued.

Point Number = 289 Mach Number = 0.854 Alphao = 1.99, deg.

q,psf 113.7	H,psf 412.1	V,fps 430.0	Rn .401E+07	gamma 1.131	freq,Hz 14.96	k 0.219	theta,deg 1.006
----------------	----------------	----------------	----------------	----------------	------------------	------------	--------------------


y/s = 0.309				y/s = 0.588				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	0.000	0.000			-0.164	0.047		
.025	-3.803	2.404	4.601	-2.954	-2.914	1.892	4.553	-3.129
.050	-4.086	2.378	4.259	-3.244	-4.873	2.836	3.718	-2.731
.100	-3.677	2.174	4.004	-2.721	-3.183	1.657	3.684	-2.776
.200	-3.315	1.891	5.371	-5.097	-2.979	1.427	4.411	-5.220
.260	-3.222	1.579	3.390	-3.129	-4.742	2.092	3.846	-3.475
.320	-3.633	2.022	5.111	-3.319	-3.265	1.488	5.199	-4.347
.380	-3.248	1.655	6.370	-2.916	-4.216	2.139	6.342	-3.107
.440	-1.932	0.489	9.116	-2.038	-4.166	2.234	8.489	-1.375
.500	-1.163	-0.467	9.328	4.389	-3.653	2.723	8.619	5.118
.560	-1.897	0.613	-6.697	9.424	-5.249	8.806	-2.928	8.750
.620	-2.028	1.038	-4.022	1.260	0.429	6.136	-1.634	-0.670
.700	-2.770	3.970	4.327	2.529	-3.404	-4.279	1.696	3.671
.800	-2.113	-3.109	2.560	0.783	-2.491	-3.258	-0.004	2.164
.900	1.792	-2.569	1.553	0.562	1.367	1.451	0.300	1.450

y/s = 0.809				y/s = 0.951				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.170	0.013			-0.112	-0.018		
.025	-3.033	1.808	3.809	-2.568	-4.383	2.185	3.775	-2.232
.050	-4.732	2.623	3.616	-2.398	-3.247	1.528	3.486	-2.369
.100	-2.984	1.417	2.880	-2.325	-3.973	1.719	2.835	-2.008
.200	-2.841	1.319	2.674	-5.340	0.365	-1.317	2.819	-2.899
.260	-3.243	1.245	1.377	-1.552	-1.128	0.160	1.543	-0.402
.320	-4.131	2.178	2.900	-1.873	-0.159	-0.236	2.902	-1.323
.380	-0.947	0.201	2.999	-2.376	-0.390	0.629	3.240	-0.198
.440	-0.127	1.247	-2.743	0.000	0.042	0.166	2.657	1.025
.500	0.131	1.132	2.253	4.268	0.189	0.833	2.235	2.509
.560	-0.064	2.619	-2.210	5.465	0.092	0.735	-0.851	3.133
.620	-1.467	1.743	-0.873	1.432	-0.267	0.629	-0.824	0.610
.700	-2.443	-0.559	0.686	1.905	-0.664	0.162	0.464	0.914
.800	-1.637	-1.744	1.285	0.737	-1.285	0.257	0.796	1.111
.900	0.164	0.233	1.068	-0.596	-3.418	1.565	0.297	1.100

(e-1) Tabulated data for test case 6E32 (point 289)
Figure 9. Continued.



(e-2) Plot of data for test case 6E32 (point 289)

Figure 9. Continued.

Point Number = 435 Mach Number = 0.876 Alphao = 1.96, deg.


q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
115.2	405.3	438.8	.401E+07	1.132	14.99	0.215	0.987

y/s = 0.309					y/s = 0.588				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	
.000	-0.174	0.014			-0.290	-0.010			
.025	-3.683	1.717	4.279	-1.950	-3.073	1.375	4.501	-2.023	
.050	-4.093	1.797	3.895	-2.071	-4.977	2.092	3.516	-1.662	
.100	-3.668	1.610	3.933	-1.727	-3.310	1.257	4.042	-2.042	
.200	-3.417	1.458	4.005	-1.851	-3.013	1.055	3.214	-1.745	
.260	-3.878	1.003	2.957	-2.787	-4.862	1.367	2.970	-1.586	
.320	-4.609	1.192	2.748	-1.737	-3.400	0.988	2.965	-2.333	
.380	-5.097	0.844	2.148	-1.025	-4.311	1.384	2.553	-2.283	
.440	-2.955	0.181	1.766	-0.577	-4.456	1.500	2.318	-1.747	
.500	-1.899	-0.537	1.749	-1.144	-4.545	1.600	1.656	-0.964	
.560	-1.436	-0.464	-11.356	8.071	-4.410	1.791	-2.266	-7.016	
.620	-1.961	0.220	3.347	-0.364	-4.485	2.445	3.646	-0.970	
.700	-2.149	0.711	8.863	-1.167	-4.212	2.091	3.678	4.187	
.800	0.538	-2.079	6.661	-2.570	3.599	-0.924	4.842	2.875	
.900	-2.140	0.534	3.484	-1.729	-2.269	1.294	3.144	0.554	

y/s = 0.809					y/s = 0.951				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	
.000	-0.287	0.045			-0.232	-0.011			
.025	-3.107	1.442	3.585	-1.800	-4.387	1.693	3.580	-1.520	
.050	-4.695	2.012	2.988	-1.532	-3.206	1.205	2.934	-1.400	
.100	-3.166	1.146	3.397	-1.317	-3.945	1.381	3.325	-1.658	
.200	-3.025	0.822	1.124	-2.070	-2.828	0.653	1.228	-0.524	
.260	-3.171	0.715	1.893	-1.580	-1.736	0.137	1.543	-1.576	
.320	-4.395	1.310	0.726	-1.650	-1.445	-0.134	0.621	-0.767	
.380	-3.624	0.817	0.883	-1.395	-1.265	-0.428	0.433	-1.077	
.440	-1.737	-0.131	-0.246	0.000	-0.842	-0.221	1.352	-1.743	
.500	-1.347	-0.681	1.042	-2.456	0.044	-0.462	1.867	-1.175	
.560	-0.557	-0.509	-1.379	8.421	0.970	-0.180	4.618	3.889	
.620	0.578	-0.572	1.266	0.663	1.256	0.452	-1.191	0.604	
.700	2.676	1.846	1.369	-0.674	0.190	0.968	1.288	0.531	
.800	-1.524	1.903	1.402	-1.528	-1.161	1.137	1.623	0.096	
.900	-0.465	0.871	0.405	-2.333	-3.639	2.283	0.612	0.181	

(f-1) Tabulated data for test case 6E33 (point 435)

Figure 9. Continued.



(f-2) Plot of data for test case 6E33 (point 435)
Figure 9. Continued.


Point Number = 264 Mach Number = 0.894 Alphao = 2.01, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
116.8	401.3	448.2	.398E+07	1.132	14.99	0.210	1.032

y/s = 0.309					y/s = 0.588				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	
.000	-0.186	0.121			-0.290	0.165			
.025	-3.783	1.740	4.253	-1.624	-3.160	1.500	4.597	-1.811	
.050	-3.932	1.677	3.849	-1.730	-4.950	2.122	3.562	-1.410	
.100	-3.759	1.658	4.215	-1.568	-3.503	1.408	4.453	-1.872	
.200	-3.516	1.521	3.543	-0.936	-3.164	1.208	3.208	-1.086	
.260	-3.391	1.234	3.337	-1.514	-4.682	1.396	3.094	-0.893	
.320	-3.755	1.525	2.665	-0.547	-3.445	1.073	2.938	-0.831	
.380	-3.701	1.510	2.393	-0.718	-4.330	1.407	2.738	-0.916	
.440	-2.487	0.579	1.952	-0.429	-4.315	1.452	2.696	-1.178	
.500	-1.770	-0.155	1.822	-0.188	-4.603	1.639	2.096	-0.734	
.560	-1.288	-0.768	-0.886	2.097	-4.442	1.750	-1.427	0.746	
.620	-1.937	-0.152	0.990	0.502	-3.966	1.595	0.924	0.508	
.700	-2.113	0.683	2.068	-0.810	-2.765	1.421	1.818	-0.226	
.800	-0.597	-1.001	2.789	-1.610	1.816	-0.245	2.548	-0.779	
.900	-1.578	-1.401	2.853	-1.089	-0.613	0.260	2.636	-0.872	

y/s = 0.809					y/s = 0.951				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	
.000	-0.249	0.123			-0.273	0.052			
.025	-3.238	1.462	3.736	-1.470	-4.601	1.803	3.683	-1.406	
.050	-4.746	2.034	2.952	-1.168	-3.374	1.281	2.872	-1.190	
.100	-3.259	1.271	3.894	-1.133	-3.980	1.402	3.798	-1.566	
.200	-3.074	1.131	1.566	-1.134	-3.409	1.003	1.626	-0.360	
.260	-3.262	0.911	1.075	-0.787	-0.622	-0.239	1.105	0.114	
.320	-3.606	1.116	1.032	-0.550	-1.720	-0.051	0.981	-0.387	
.380	-3.306	0.960	0.499	-0.048	-1.775	-0.068	0.310	-0.392	
.440	-2.125	0.417	-0.113	0.000	-1.755	-0.275	-0.141	-0.089	
.500	-1.998	0.035	0.641	-0.270	-1.304	-0.475	0.500	-0.441	
.560	-1.888	-0.010	0.472	0.309	-0.936	-0.785	0.386	-0.674	
.620	-1.871	-0.253	0.975	0.134	1.536	-2.178	-0.243	0.969	
.700	-1.514	-0.693	1.914	-0.134	1.828	-0.128	1.673	-0.989	
.800	6.909	1.406	1.428	-0.932	0.084	1.663	1.771	-0.926	
.900	-0.241	1.027	0.543	-1.362	-2.518	2.662	0.888	0.017	

(g-1) Tabulated data for test case 6E34 (point 264)
Figure 9. Continued.



(g-2) Plot of data for test case 6E34 (point 264)
Figure 9. Continued.

Point Number = 513 Mach Number = 0.402 Alphao = 1.97, deg.

q,psf 54.7	H,psf 654.9	V,fps 202.9	Rn .402E+07	gamma 1.132	freq,Hz 5.02	k 0.155	theta,deg 1.008
---------------	----------------	----------------	----------------	----------------	-----------------	------------	--------------------


y/s = 0.309				y/s = 0.588				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-3.864	0.674			-3.757	0.622		
.025	-13.066	2.163	8.889	-1.281	-12.393	2.052	8.727	-1.211
.050	-8.893	1.250	6.933	-0.900	-8.062	1.033	6.492	-0.763
.100	-5.662	0.495	4.873	-0.392	-4.821	0.320	4.480	-0.305
.200	-3.353	0.047	3.069	0.027	-3.069	-0.037	2.841	0.079
.260	-2.782	-0.131	2.372	0.274	-2.493	-0.196	2.142	0.278
.320	-2.262	-0.230	2.017	0.345	-2.022	-0.313	1.900	0.352
.380	-1.916	-0.249	1.661	0.386	-1.670	-0.343	1.542	0.396
.440	-1.610	-0.354	1.530	0.439	-1.434	-0.358	1.297	0.424
.500	-1.374	-0.363	1.288	0.449	-1.258	-0.356	1.154	0.483
.560	-1.138	-0.361	1.104	0.453	-1.142	-0.349	0.901	0.596
.620	-0.958	-0.358	0.786	0.563	-0.911	-0.323	0.676	0.520
.700	-0.736	-0.303	0.648	0.462	-0.612	-0.301	0.561	0.481
.800	-0.415	-0.186	0.708	0.363	-0.370	-0.145	0.661	0.331
.900	-0.032	0.047	0.630	0.261	-0.103	0.048	0.575	0.246

y/s = 0.809				y/s = 0.951				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-2.973	0.487			-1.684	0.270		
.025	-10.779	1.707	6.242	-1.187	-7.585	1.161	6.248	-0.878
.050	-7.048	0.903	4.511	-0.755	-4.960	0.644	4.519	-0.507
.100	-4.198	0.264	2.778	-0.284	-2.724	0.152	2.783	-0.117
.200	-2.609	-0.178	1.534	0.070	-1.533	-0.075	1.527	0.150
.260	-2.157	-0.121	1.520	0.237	-1.125	-0.160	-1.309	0.802
.320	-1.509	-0.277	0.722	0.327	-0.891	-0.184	-0.323	0.665
.380	-1.334	-0.284	0.877	0.375	-0.709	-0.209	0.864	0.283
.440	-1.154	-0.307	-0.606	0.000	-0.698	-0.243	0.508	0.365
.500	-0.845	-0.336	0.398	0.438	-0.580	-0.234	0.284	0.355
.560	-0.708	-0.363	0.307	0.471	-0.457	-0.229	0.070	0.392
.620	-0.601	-0.323	0.263	0.487	-0.605	-0.159	-0.353	0.370
.700	-0.434	-0.270	0.230	0.441	-0.431	-0.145	-0.235	0.389
.800	-0.307	-0.150	0.175	0.358	-0.966	0.022	-0.044	0.281
.900	-0.170	0.018	0.134	0.281	-1.803	0.237	0.039	0.166

(h-1) Tabulated data for test case 6E35 (point 513)
Figure 9. Continued.



(h-2) Plot of data for test case 6E35 (point 513)

Figure 9. Continued.


Point Number = 515 Mach Number = 0.402 Alphao = 1.98, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
54.7	654.9	202.9	.402E+07	1.132	15.06	0.466	1.020

x/c	y/s = 0.309				y/s = 0.588			
	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t
.000	-3.492	1.548			-3.481	1.572		
.025	-11.884	5.069	8.319	-3.094	-11.203	5.082	8.250	-3.117
.050	-8.073	2.780	6.532	-2.072	-7.607	2.399	6.181	-1.878
.100	-5.454	0.747	4.727	-0.673	-4.684	0.567	4.447	-0.649
.200	-3.287	-0.421	3.112	0.460	-3.050	-0.494	2.940	0.466
.260	-2.656	-0.914	2.453	0.976	-2.396	-0.968	2.131	1.012
.320	-2.180	-1.164	1.990	1.158	-1.934	-1.251	1.895	1.207
.380	-1.781	-1.275	1.707	1.282	-1.585	-1.344	1.606	1.406
.440	-1.425	-1.435	1.450	1.410	-1.318	-1.459	1.326	1.452
.500	-1.178	-1.503	1.199	1.486	-1.064	-1.449	1.082	1.505
.560	-0.939	-1.533	0.960	1.586	-0.845	-1.458	0.844	1.650
.620	-0.673	-1.484	0.661	1.732	-0.609	-1.450	0.568	1.587
.700	-0.441	-1.333	0.559	1.470	-0.290	-1.374	0.444	1.391
.800	-0.042	-1.010	0.347	1.186	0.021	-1.011	0.355	1.125
.900	0.387	-0.325	0.186	0.994	0.337	-0.377	0.127	0.776

x/c	y/s = 0.809				y/s = 0.951			
	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t
.000	-2.850	1.192			-1.598	0.692		
.025	-10.127	4.174	5.986	-2.912	-7.255	2.887	5.990	-2.264
.050	-6.833	2.050	4.456	-1.767	-4.872	1.546	4.473	-1.316
.100	-4.201	0.316	2.782	-0.540	-2.747	0.173	2.796	-0.264
.200	-2.533	-0.511	1.664	0.404	-1.617	-0.473	1.608	0.504
.260	-2.157	-0.807	2.430	0.949	-1.232	-0.674	-0.905	2.599
.320	-1.541	-1.128	1.628	1.039	-0.960	-0.778	0.041	1.966
.380	-1.292	-1.167	0.853	1.242	-0.738	-0.921	0.833	0.836
.440	-1.076	-1.297	-0.249	0.000	-0.640	-0.924	0.390	1.054
.500	-0.750	-1.382	0.527	1.389	-0.513	-0.871	0.349	1.068
.560	-0.580	-1.401	0.342	1.383	-0.276	-0.914	0.020	1.067
.620	-0.407	-1.402	0.162	1.390	-0.360	-0.762	-0.404	1.048
.700	-0.236	-1.213	0.186	1.270	-0.233	-0.692	-0.229	0.985
.800	-0.011	-0.899	0.127	1.111	-0.600	-0.307	-0.139	0.831
.900	0.180	-0.350	0.100	0.944	-1.282	0.157	-0.191	0.646

(i-1) Tabulated data for test case 6E36 (point 515)
Figure 9. Continued.



(i-2) Plot of data for test case 6E36 (point 515)

Figure 9. Continued.


Point Number = 516 Mach Number = 0.402 Alphao = 1.98, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
54.8	654.9	203.2	.403E+07	1.132	19.97	0.617	1.060

y/s = 0.309					y/s = 0.588				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	
.000	-3.313	1.936			-3.427	1.955			
.025	-11.488	6.368	8.127	-4.052	-10.957	6.532	8.202	-4.143	
.050	-7.832	3.405	6.492	-2.689	-7.705	3.004	6.273	-2.509	
.100	-5.612	0.849	4.792	-0.836	-4.934	0.623	4.686	-0.818	
.200	-3.484	-0.766	3.290	0.639	-3.358	-0.831	3.176	0.658	
.260	-2.796	-1.418	2.630	1.387	-2.627	-1.391	2.432	1.410	
.320	-2.306	-1.789	2.129	1.575	-2.137	-1.825	2.121	1.675	
.380	-1.864	-1.957	1.818	1.774	-1.719	-1.943	1.726	1.864	
.440	-1.457	-2.081	1.565	1.932	-1.455	-2.148	1.481	1.930	
.500	-1.168	-2.134	1.289	2.063	-1.076	-2.121	1.186	2.062	
.560	-0.878	-2.152	0.967	2.173	-0.784	-2.131	0.967	2.054	
.620	-0.577	-2.140	0.703	2.329	-0.497	-2.104	0.641	2.178	
.700	-0.392	-2.016	0.514	1.933	-0.265	-1.982	0.405	1.903	
.800	0.093	-1.565	0.190	1.719	0.173	-1.449	0.139	1.561	
.900	0.543	-0.673	-0.013	1.459	0.544	-0.741	-0.020	1.297	

y/s = 0.809					y/s = 0.951				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	
.000	-2.814	1.612			-1.587	0.927			
.025	-10.021	5.669	5.977	-3.983	-7.329	3.946	5.966	-3.172	
.050	-6.896	2.843	4.491	-2.410	-4.983	2.095	4.494	-1.862	
.100	-4.410	0.440	2.930	-0.699	-3.020	0.206	2.947	-0.393	
.200	-2.787	-0.868	1.850	0.601	-1.871	-0.707	1.779	0.644	
.260	-2.279	-1.122	2.878	1.290	-1.410	-1.002	-0.205	3.453	
.320	-1.731	-1.631	1.817	1.465	-1.120	-1.172	0.388	2.346	
.380	-1.483	-1.719	0.969	1.617	-0.886	-1.293	0.950	1.108	
.440	-1.299	-1.862	1.273	0.000	-0.669	-1.297	0.456	1.500	
.500	-0.830	-1.938	0.526	1.878	-0.492	-1.316	0.381	1.240	
.560	-0.570	-1.973	0.368	1.826	-0.253	-1.327	0.039	1.405	
.620	-0.388	-1.962	0.173	1.879	-0.339	-1.196	-0.378	1.410	
.700	-0.196	-1.773	0.163	1.770	-0.132	-1.073	-0.210	1.280	
.800	0.111	-1.347	0.040	1.566	-0.442	-0.680	-0.273	1.046	
.900	0.344	-0.674	0.007	1.243	-1.077	-0.096	-0.374	0.898	

(j-1) Tabulated data for test case 6E37 (point 516)
Figure 9. Continued.



(j-2) Plot of data for test case 6E37 (point 516)

Figure 9. Continued.

Point Number = 494 Mach Number = 0.803 Alphao = 2.19, deg.

q,psf 106.1	H,psf 415.4	V,fps 403.2	Rn .401E+07	gamma 1.132	freq,Hz 1.98	k 0.031	theta,deg 1.069
----------------	----------------	----------------	----------------	----------------	-----------------	------------	--------------------

		y/s = 0.309			y/s = 0.588			
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t


.000	-0.687	0.116			-0.802	0.057		
.025	-7.365	0.683	7.805	-0.559	-5.924	0.550	8.123	-0.625
.050	-8.598	0.737	7.749	-0.596	-8.970	0.785	7.107	-0.547
.100	-7.097	0.671	6.905	-0.350	-6.463	0.543	6.362	-0.456
.200	-7.725	0.853	4.822	-0.143	-7.204	0.681	4.285	-0.150
.260	-12.010	1.093	3.752	-0.020	-13.617	1.167	3.804	-0.093
.320	-18.225	1.370	3.484	-0.030	-20.473	1.503	2.571	0.094
.380	-17.642	1.265	2.674	0.173	-6.324	0.099	1.979	0.125
.440	-1.069	-0.976	2.086	0.128	4.993	-1.245	1.767	0.086
.500	5.978	-1.502	1.588	0.252	3.429	-0.868	1.383	0.175
.560	3.397	-0.772	0.147	0.156	2.231	-0.577	0.293	0.132
.620	1.942	-0.402	-2.060	0.352	1.269	-0.430	-0.922	0.285
.700	0.842	-0.164	2.090	0.036	0.104	-0.025	1.233	0.011
.800	-0.388	0.370	3.482	-0.128	-0.408	-0.133	2.604	-0.338
.900	-1.239	0.346	2.772	-0.286	-1.362	0.294	2.073	-0.269

		y/s = 0.809			y/s = 0.951			
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.745	0.089			-0.533	0.056		
.025	-5.495	0.529	6.097	-0.490	-7.000	0.551	6.095	-0.426
.050	-9.446	0.876	6.098	-0.438	-6.624	0.545	6.097	-0.405
.100	-5.872	0.524	3.694	-0.292	-8.069	0.621	3.693	-0.187
.200	-14.341	1.482	1.929	0.044	-2.144	-0.019	1.929	0.007
.260	-8.565	0.419	1.072	0.000	-2.733	0.033	1.071	0.043
.320	-0.482	-0.425	0.107	0.075	-1.230	-0.075	-0.082	0.069
.380	-0.372	-0.386	0.697	-0.024	-0.841	-0.170	0.692	0.081
.440	-0.184	-0.387	-0.696	0.000	-0.488	-0.222	0.696	0.039
.500	0.297	-0.380	0.320	0.047	-0.131	-0.234	0.289	0.140
.560	0.308	-0.371	-0.411	0.061	0.049	-0.153	-0.416	0.103
.620	0.399	-0.270	-1.060	0.206	0.066	-0.147	-1.061	0.153
.700	0.105	-0.020	0.161	0.018	-0.093	-0.054	0.137	0.085
.800	-0.601	0.228	0.803	-0.059	-1.393	0.051	0.803	-0.045
.900	-1.100	0.238	0.534	-0.151	-4.598	0.330	0.535	0.031

(k-1) Tabulated data for test case 6E38 (point 494)

Figure 9. Continued.



(k-2) Plot of data for test case 6E38 (point 494)

Figure 9. Continued.

Point Number = 493 Mach Number = 0.802 Alphao = 1.89, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
105.8	415.2	402.4	.400E+07	1.132	3.00	0.047	1.025


x/c	y/s = 0.309				y/s = 0.588			
	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.690	0.227			-0.830	0.120		
.025	-7.517	1.137	7.991	-0.967	-6.081	0.909	8.374	-1.058
.050	-8.735	1.305	7.988	-0.995	-9.237	1.348	7.322	-0.912
.100	-7.290	1.142	7.121	-0.698	-6.693	0.976	6.608	-0.765
.200	-7.877	1.361	4.971	-0.208	-7.288	1.154	4.469	-0.148
.260	-12.126	1.683	3.800	0.086	-13.181	1.806	3.857	0.027
.320	-18.424	2.230	3.240	0.107	-21.281	2.802	2.739	0.043
.380	-18.227	1.980	2.678	0.159	-8.089	0.509	2.066	0.087
.440	-1.884	-1.493	2.235	0.070	4.833	-1.914	1.675	0.085
.500	5.986	-2.492	1.788	0.059	3.524	-1.569	1.228	0.380
.560	3.429	-1.505	0.205	0.266	2.108	-1.033	0.480	0.286
.620	2.132	-0.840	-2.229	0.531	1.479	-0.790	-0.856	0.529
.700	1.265	-0.716	2.124	-0.037	0.373	-0.118	1.286	-0.002
.800	-0.292	0.604	3.336	-0.351	-0.843	0.647	2.649	-0.424
.900	-1.450	0.589	2.992	-0.399	-1.355	0.343	2.009	-0.490

x/c	y/s = 0.809				y/s = 0.951			
	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.706	0.172			-0.547	0.116		
.025	-5.699	0.821	6.389	-0.840	-7.317	0.950	6.394	-0.661
.050	-9.800	1.360	6.392	-0.772	-6.924	0.936	6.398	-0.627
.100	-6.093	0.824	4.008	-0.603	-8.537	1.109	4.021	-0.169
.200	-14.991	2.536	2.123	-0.099	-2.287	0.148	2.124	0.037
.260	-8.667	0.957	1.118	0.050	-2.571	0.040	1.109	0.140
.320	-0.481	-0.687	0.277	0.234	-1.325	-0.208	-0.123	0.251
.380	-0.260	-0.738	0.705	0.365	-0.975	-0.247	0.724	0.062
.440	-0.015	-0.727	-0.615	0.000	-0.539	-0.295	0.598	0.145
.500	0.166	-0.707	0.265	0.251	-0.198	-0.271	0.257	0.110
.560	0.263	-0.429	-0.286	0.262	0.108	-0.258	-0.234	0.240
.620	0.293	-0.259	-0.985	0.297	0.141	-0.241	-0.993	0.164
.700	-0.046	-0.032	0.165	0.133	-0.037	-0.106	0.133	0.102
.800	-0.938	0.499	0.783	-0.019	-1.275	0.166	0.782	-0.036
.900	-1.019	0.300	0.556	-0.182	-4.660	0.572	0.552	-0.086

(l-1) Tabulated data for test case 6E39 (point 493)
Figure 9. Continued.



(l-2) Plot of data for test case 6E39 (point 493)

Figure 9. Continued.

Point Number = 495 Mach Number = 0.803 Alphao = 1.84, deg.

q,psf 106.1	H,psf 415.6	V,fps 403.2	Rn .401E+07	gamma 1.132	freq,Hz 3.95	k 0.062	theta,deg 1.080
----------------	----------------	----------------	----------------	----------------	-----------------	------------	--------------------

y/s = 0.309				y/s = 0.588				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t


.000	-0.615	0.164			-0.723	0.170		
.025	-7.078	1.401	7.600	-1.190	-5.777	1.144	7.925	-1.170
.050	-8.275	1.638	7.589	-1.256	-8.703	1.660	6.933	-0.987
.100	-6.862	1.396	6.896	-0.859	-6.251	1.204	6.216	-0.741
.200	-7.291	1.670	4.863	-0.417	-6.951	1.490	4.242	-0.148
.260	-11.156	2.108	3.394	-0.089	-13.653	2.605	3.978	0.069
.320	-17.382	2.846	3.129	0.076	-19.958	3.519	2.653	0.009
.380	-17.607	3.105	2.544	0.120	-8.296	1.196	2.069	0.025
.440	-5.175	-1.166	2.106	0.259	5.096	-2.619	1.568	0.274
.500	5.587	-3.371	1.603	0.367	3.390	-1.981	1.033	0.417
.560	3.698	-2.083	0.123	0.461	2.111	-1.424	0.306	0.558
.620	2.227	-1.235	-2.160	0.735	1.281	-0.944	-0.836	0.653
.700	1.209	-0.546	2.069	0.007	0.354	-0.321	1.159	0.134
.800	-0.198	0.880	3.142	-0.509	-0.515	0.459	2.442	-0.506
.900	-1.289	0.626	2.708	-0.526	-1.259	0.885	1.973	-0.416

y/s = 0.809				y/s = 0.951				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.665	0.183			-0.513	0.136		
.025	-5.312	1.033	6.040	-1.024	-6.842	1.219	6.035	-0.891
.050	-9.172	1.750	5.990	-0.948	-6.466	1.210	5.988	-0.852
.100	-5.684	1.064	3.687	-0.746	-7.884	1.419	3.698	-0.337
.200	-13.207	2.928	1.745	-0.247	-2.168	0.174	1.750	0.027
.260	-9.520	1.610	1.008	-0.005	-3.020	0.153	0.966	0.286
.320	-0.822	-0.584	0.423	0.152	-1.367	-0.182	-0.161	0.393
.380	-0.588	-0.752	0.722	0.312	-0.974	-0.259	0.720	0.183
.440	-0.227	-0.818	-0.354	0.000	-0.550	-0.320	0.365	0.217
.500	0.285	-0.856	0.253	0.484	-0.193	-0.378	0.265	0.177
.560	0.297	-0.738	-0.279	0.419	0.039	-0.316	-0.254	0.271
.620	0.223	-0.652	-0.970	0.373	-0.023	-0.211	-0.964	0.293
.700	-0.023	-0.317	0.208	0.154	-0.202	-0.064	0.128	0.169
.800	-0.554	0.410	0.742	-0.083	-1.359	0.237	0.743	-0.016
.900	-1.039	0.639	0.474	-0.207	-4.327	0.818	0.473	-0.066

(m-1) Tabulated data for test case 6E40 (point 495)

Figure 9. Continued.



(m-2) Plot of data for test case 6E40 (point 495)

Figure 9. Continued.

Point Number = 314 Mach Number = 0.803 Alphao = 2.10, deg.

q,psf 107.7	H,psf 422.0	V,fps 405.1	Rn .401E+07	gamma 1.131	freq,Hz 4.95	k 0.077	theta,deg 1.080
----------------	----------------	----------------	----------------	----------------	-----------------	------------	--------------------

	y/s = 0.309				y/s = 0.588			
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t


.000	-0.599	0.216			-0.762	0.230		
.025	-7.136	1.859	7.431	-1.525	-5.817	1.450	7.757	-1.522
.050	-7.718	1.939	7.421	-1.577	-8.618	2.053	6.824	-1.314
.100	-6.728	1.740	6.697	-1.121	-6.293	1.511	6.113	-1.078
.200	-7.198	2.037	4.699	-0.461	-6.716	1.787	4.210	-0.539
.260	-8.975	2.574	3.760	-0.230	-12.205	3.020	3.340	0.111
.320	-16.627	4.145	3.130	-0.022	-20.244	4.525	2.668	0.451
.380	-19.192	5.035	2.595	0.154	-10.979	2.676	2.036	0.599
.440	-4.739	-0.582	1.926	0.378	4.867	-3.408	1.818	0.380
.500	5.319	-4.307	1.564	0.293	3.444	-2.829	1.477	0.158
.560	3.373	-2.830	0.378	0.372	2.289	-1.976	0.279	0.245
.620	2.160	-1.800	-1.330	0.774	1.447	-1.326	-0.641	0.472
.700	1.449	-0.884	1.751	-0.006	0.513	-0.609	1.104	0.151
.800	0.004	0.584	2.546	-0.527	0.132	0.459	2.084	-0.401
.900	-0.835	0.961	2.253	-0.612	-1.012	0.937	1.660	-0.356

	y/s = 0.809				y/s = 0.951			
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.667	0.175			-0.510	0.144		
.025	-5.363	1.297	5.958	-1.240	-7.044	1.562	5.956	-1.050
.050	-8.873	2.130	5.913	-1.121	-6.255	1.444	5.911	-1.000
.100	-5.679	1.342	3.725	-0.917	-7.860	1.800	3.752	-0.328
.200	-13.528	3.828	1.953	-0.306	-2.157	0.276	1.961	0.089
.260	-8.556	1.850	1.166	0.109	-2.748	0.240	1.156	0.160
.320	-0.673	-1.143	0.576	0.302	-1.355	-0.258	-0.183	0.554
.380	-0.623	-0.924	0.731	0.268	-0.897	-0.327	0.723	0.168
.440	-0.177	-0.938	-0.581	0.000	-0.541	-0.427	0.567	0.136
.500	0.131	-0.839	0.197	0.292	-0.244	-0.410	0.205	0.053
.560	0.279	-0.745	-0.149	0.328	-0.050	-0.368	-0.225	0.225
.620	0.245	-0.588	-1.010	0.440	0.001	-0.371	-0.962	0.447
.700	-0.004	-0.159	0.208	0.174	-0.115	-0.239	0.047	0.207
.800	-0.447	0.168	0.583	-0.086	-1.252	0.234	0.581	0.055
.900	-0.782	0.548	0.311	-0.314	-4.225	1.038	0.316	0.040

(n-1) Tabulated data for test case 6E41 (point 314)

Figure 9. Continued.



(n-2) Plot of data for test case 6E41 (point 314)
Figure 9. Continued.


Point Number = 315 Mach Number = 0.804 Alphao = 2.08, deg.

q,psf 107.9	H,psf 422.2	V,fps 405.5	Rn .401E+07	gamma 1.131	freq,Hz 9.96	k 0.154	theta,deg 1.057
----------------	----------------	----------------	----------------	----------------	-----------------	------------	--------------------

y/s = 0.309					y/s = 0.588				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	
.000	-0.492	0.426			-0.569	0.415			
.025	-6.080	3.343	6.761	-2.800	-4.855	2.758	6.959	-3.026	
.050	-6.356	3.626	6.721	-2.895	-7.377	4.022	6.142	-2.594	
.100	-5.686	3.270	6.260	-2.131	-5.373	2.942	5.600	-2.049	
.200	-5.786	3.830	4.620	-0.948	-5.532	3.524	4.146	-0.828	
.260	-7.307	5.251	3.740	-0.059	-11.959	7.560	3.402	0.292	
.320	-14.397	10.888	3.183	0.312	-18.215	9.849	2.634	0.342	
.380	-16.559	10.428	2.602	0.534	-10.416	5.917	2.142	0.594	
.440	-9.467	0.596	2.046	0.533	2.422	-6.618	1.822	0.699	
.500	1.327	-8.571	1.499	0.630	1.672	-5.610	1.001	0.831	
.560	2.087	-7.183	0.430	1.170	1.173	-4.231	0.249	1.055	
.620	1.942	-3.998	-1.187	1.616	1.015	-3.033	-0.489	1.147	
.700	2.124	-2.604	1.623	0.105	0.793	-1.294	0.972	0.340	
.800	1.269	1.183	2.228	-0.851	0.773	0.595	1.582	-0.711	
.900	-0.369	1.750	1.710	-1.048	-0.332	1.647	1.330	-0.838	

y/s = 0.809					y/s = 0.951				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	
.000	-0.550	0.348			-0.465	0.279			
.025	-4.582	2.467	5.469	-2.514	-6.241	3.031	5.484	-2.050	
.050	-7.607	4.165	5.454	-2.269	-5.423	2.847	5.467	-1.936	
.100	-4.777	2.562	3.519	-1.822	-7.007	3.679	3.604	-0.773	
.200	-10.130	7.360	1.776	-0.372	-2.313	0.581	1.789	0.009	
.260	-9.064	4.539	1.191	0.152	-2.847	0.678	1.096	0.470	
.320	-1.827	-1.448	0.958	0.345	-1.662	-0.245	-0.027	0.975	
.380	-1.387	-1.737	0.698	0.638	-1.358	-0.546	0.625	0.430	
.440	-0.870	-1.807	-0.554	0.000	-0.988	-0.761	0.356	0.478	
.500	-0.319	-2.035	0.463	0.647	-0.569	-0.792	0.063	0.647	
.560	0.012	-1.735	-0.063	0.971	-0.210	-0.785	-0.219	0.612	
.620	0.195	-1.505	-0.750	1.078	0.012	-0.705	-0.828	0.613	
.700	0.253	-0.942	0.292	0.380	-0.033	-0.487	0.061	0.319	
.800	0.050	0.649	0.538	-0.168	-0.990	0.286	0.542	0.012	
.900	-0.179	0.904	0.249	-0.536	-3.406	1.545	0.257	0.085	

(o-1) Tabulated data for test case 6E42 (point 315)
Figure 9. Continued.



(o-2) Plot of data for test case 6E42 (point 315)

Figure 9. Continued.


Point Number = 317 Mach Number = 0.802 Alphao = 2.07, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
107.5	422.1	404.5	.401E+07	1.131	20.01	0.311	1.039

y/s = 0.309					y/s = 0.588				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	
.000	-0.026	0.385			-0.167	0.408			
.025	-3.733	4.059	5.438	-4.054	-3.006	3.304	5.725	-4.314	
.050	-3.473	3.622	5.387	-4.300	-4.776	4.894	5.213	-3.801	
.100	-3.148	3.765	5.593	-3.216	-3.171	3.377	5.258	-3.134	
.200	-2.390	3.839	4.798	-1.268	-2.430	3.549	4.687	-1.022	
.260	-1.774	5.627	4.631	0.105	-3.220	9.680	4.675	0.799	
.320	1.035	17.947	3.736	0.973	-3.721	20.678	3.571	1.314	
.380	-1.358	16.875	3.159	1.694	-4.331	5.644	2.832	2.013	
.440	-8.778	5.921	2.376	2.058	-5.692	-5.216	2.185	2.410	
.500	-10.672	-4.774	1.373	2.198	-5.853	-5.034	1.108	2.525	
.560	-10.286	-6.328	0.395	2.338	-4.692	-5.050	0.087	2.480	
.620	-6.634	-7.605	-0.566	2.473	-3.446	-5.389	-0.407	2.112	
.700	-2.308	-9.541	1.075	0.948	-0.509	-5.380	0.732	1.233	
.800	6.054	-3.058	0.879	-0.327	4.063	-2.224	0.587	-0.152	
.900	2.038	2.017	0.225	-0.379	1.792	1.948	0.043	-0.328	

y/s = 0.809					y/s = 0.951				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	
.000	-0.148	0.356			-0.076	0.265			
.025	-2.944	3.060	4.815	-3.654	-4.364	3.971	4.895	-2.988	
.050	-4.630	4.728	5.010	-3.351	-3.351	3.434	5.098	-2.861	
.100	-2.793	2.975	3.720	-2.746	-3.840	4.625	3.997	-1.063	
.200	-2.050	8.411	2.639	-0.296	-1.034	1.630	2.616	0.405	
.260	-1.767	5.572	2.250	0.862	-1.749	1.761	1.947	1.255	
.320	-2.897	0.387	2.109	1.361	-1.645	0.778	0.630	2.286	
.380	-3.031	-0.122	1.270	1.882	-1.794	0.307	0.868	1.473	
.440	-3.060	-0.930	0.495	0.000	-1.702	-0.161	0.681	1.628	
.500	-2.871	-1.753	0.350	2.202	-1.603	-0.593	0.073	1.542	
.560	-2.306	-2.136	-0.313	2.217	-1.186	-0.900	-0.438	1.538	
.620	-1.730	-2.624	-1.026	1.523	-0.847	-0.944	-0.947	1.289	
.700	-0.804	-2.348	0.374	1.229	-0.561	-0.885	-0.104	0.821	
.800	0.931	-1.162	0.446	0.458	-0.859	-0.201	0.228	0.441	
.900	0.703	0.989	0.339	-0.237	-2.248	1.175	-0.083	0.377	

(p-1) Tabulated data for test case 6E43 (point 317)
Figure 9. Continued.



(p-2) Plot of data for test case 6E43 (point 317)

Figure 9. Continued.

Point Number = 473 Mach Number = 0.825 Alphao = 1.98, deg.

q,psf 107.8	H,psf 407.9	V,fps 413.0	Rn .399E+07	gamma 1.132	freq,Hz 4.97	k 0.076	theta,deg 1.070
----------------	----------------	----------------	----------------	----------------	-----------------	------------	--------------------

	y/s = 0.309				y/s = 0.588			
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t


.000	-0.445	0.185			-0.555	0.198		
.025	-6.180	1.552	6.974	-1.444	-4.990	1.235	7.233	-1.511
.050	-7.173	1.775	7.003	-1.565	-7.716	1.810	6.240	-1.292
.100	-5.923	1.477	6.417	-1.224	-5.472	1.293	5.727	-1.124
.200	-5.630	1.540	5.626	-0.751	-5.243	1.327	5.735	-0.745
.260	-7.246	1.448	4.810	-0.303	-6.964	1.493	3.636	0.191
.320	-8.855	1.866	3.906	0.157	-6.218	1.620	3.231	0.477
.380	-8.503	1.423	3.027	0.388	-13.605	4.394	2.005	0.754
.440	-4.962	1.536	1.789	0.338	-19.420	5.313	1.436	0.431
.500	-12.919	3.510	1.600	0.444	-4.872	0.094	0.962	0.061
.560	-16.779	3.201	-0.697	0.666	4.282	-3.644	-0.332	0.731
.620	-0.119	-4.014	-2.766	0.634	3.346	-3.164	-0.888	0.929
.700	7.474	-4.910	1.962	0.276	3.145	-2.667	1.121	-0.086
.800	3.186	-0.414	3.078	-0.411	1.392	-0.005	2.474	-1.025
.900	-1.202	1.145	2.896	-0.963	-1.399	1.165	1.942	-0.769

	y/s = 0.809				y/s = 0.951			
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.454	0.162			-0.409	0.127		
.025	-4.688	1.117	5.581	-1.239	-6.169	1.368	5.579	-1.044
.050	-7.820	1.834	5.793	-1.150	-5.401	1.118	5.792	-1.073
.100	-4.902	1.141	4.109	-1.111	-6.112	1.603	4.143	-0.531
.200	-5.490	1.440	2.029	-0.261	-5.101	1.628	2.035	-0.007
.260	-10.986	3.443	1.445	0.118	-2.986	0.635	1.428	0.229
.320	-7.550	2.409	0.572	0.440	-2.733	0.531	-0.175	0.562
.380	-3.266	0.029	0.832	0.345	-1.713	0.036	0.761	0.393
.440	-1.687	-0.685	-0.584	0.000	-1.206	-0.252	0.528	0.262
.500	-0.675	-1.218	0.316	0.230	-0.665	-0.540	0.154	0.342
.560	0.013	-1.232	-0.683	0.647	-0.097	-0.635	-0.633	0.495
.620	0.647	-1.233	-1.047	0.586	0.159	-0.511	-1.089	0.280
.700	0.613	-0.878	0.210	0.141	0.176	-0.391	0.174	0.124
.800	0.232	0.223	0.901	-0.258	-1.154	0.237	0.901	-0.128
.900	-0.891	0.686	0.620	-0.608	-4.466	1.122	0.627	-0.141

(q-1) Tabulated data for test case 6E44 (point 473)

Figure 9. Continued.



(q-2) Plot of data for test case 6E44 (point 473)

Figure 9. Continued.


Point Number = 474 Mach Number = 0.825 Alphao = 1.97, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
107.8	408.0	413.0	.399E+07	1.132	9.96	0.152	1.038

x/c	y/s = 0.309				y/s = 0.588			
	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t
.000	-0.291	0.332			-0.428	0.348		
.025	-5.011	2.801	6.051	-2.694	-4.108	2.267	6.414	-2.829
.050	-5.734	3.205	6.028	-2.875	-6.616	3.547	5.564	-2.431
.100	-4.963	2.774	5.748	-2.276	-4.581	2.436	5.173	-2.079
.200	-4.592	2.859	4.888	-1.156	-4.233	2.493	5.263	-1.470
.260	-6.162	2.979	4.823	-0.575	-5.665	2.739	3.998	0.505
.320	-7.462	3.835	3.629	0.324	-4.874	3.034	3.531	0.635
.380	-7.367	3.127	2.993	0.774	-10.715	9.957	2.018	1.351
.440	-6.495	6.773	1.675	0.963	-15.847	13.487	1.218	1.201
.500	-12.504	10.344	1.125	0.799	-6.558	1.263	0.676	1.009
.560	-15.533	7.177	-0.817	1.042	0.069	-5.685	-0.250	1.693
.620	-5.216	-6.216	-2.513	1.387	0.020	-5.741	-0.379	1.498
.700	3.039	-10.957	1.913	0.272	0.101	-6.402	0.659	0.063
.800	5.061	-4.011	2.494	-0.893	2.438	-2.075	1.234	-1.414
.900	-0.566	2.532	2.110	-1.413	-0.437	2.333	0.963	-1.278

x/c	y/s = 0.809				y/s = 0.951			
	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t
.000	-0.381	0.319			-0.375	0.233		
.025	-4.000	2.118	5.091	-2.346	-5.448	2.681	5.052	-2.082
.050	-6.531	3.472	5.308	-2.196	-4.496	2.361	5.253	-2.176
.100	-4.113	2.141	3.828	-2.097	-5.063	3.042	3.922	-1.140
.200	-4.400	2.750	2.025	-0.447	-3.996	3.044	2.042	-0.021
.260	-8.659	6.937	1.766	0.076	-2.933	1.868	1.691	0.511
.320	-5.915	5.555	1.065	0.721	-2.632	1.145	-0.197	1.142
.380	-3.830	1.252	0.685	1.044	-2.189	0.292	0.543	0.697
.440	-2.949	-0.430	-0.580	0.000	-1.734	-0.334	0.424	0.509
.500	-2.258	-1.587	0.147	0.937	-1.235	-0.731	0.041	0.440
.560	-1.375	-2.134	-0.740	0.995	-0.746	-1.027	-0.714	0.691
.620	-0.737	-2.487	-1.054	0.862	-0.343	-1.049	-1.042	0.725
.700	-0.223	-2.086	0.201	0.454	-0.134	-0.873	0.078	0.265
.800	0.863	-0.932	0.694	-0.310	-0.932	-0.106	0.681	-0.227
.900	-0.232	1.304	0.446	-1.106	-3.525	1.712	0.513	-0.205

(r-1) Tabulated data for test case 6E45 (point 474)
Figure 9. Continued.



(r-2) Plot of data for test case 6E45 (point 474)

Figure 9. Continued.

Point Number = 476 Mach Number = 0.825 Alphao = 1.97, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
108.0	408.2	413.4	.399E+07	1.132	20.07	0.305	1.035

y/s = 0.309				y/s = 0.588				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t


.000	0.047	0.159			-0.122	0.185		
.025	-3.526	3.441	5.116	-4.323	-2.862	2.774	5.184	-4.667
.050	-3.920	3.505	4.906	-4.721	-4.843	4.300	4.534	-4.228
.100	-3.349	3.145	5.219	-4.019	-3.162	2.691	4.519	-3.998
.200	-2.653	2.748	5.906	-2.919	-2.738	2.249	5.870	-3.768
.260	-4.046	2.402	6.185	-1.727	-3.895	2.539	6.519	-0.422
.320	-4.679	3.062	6.617	-0.591	-2.624	2.125	7.066	-0.531
.380	-4.848	2.038	6.354	2.288	-1.974	3.590	5.815	2.976
.440	-0.609	-0.003	3.843	3.750	1.581	16.421	4.183	4.501
.500	2.930	10.217	1.546	4.620	-1.361	0.742	1.400	5.299
.560	0.406	16.603	-1.370	3.743	-3.536	-1.717	-0.506	3.953
.620	-7.436	1.178	-2.966	3.214	-3.951	-1.876	-0.174	1.484
.700	-9.675	-5.496	2.278	1.473	-5.717	-2.801	0.062	2.213
.800	-3.197	-9.555	1.771	-0.022	-0.971	-5.619	-0.987	0.889
.900	2.630	1.842	0.239	-0.437	2.072	1.918	-0.774	0.712

y/s = 0.809				y/s = 0.951				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.126	0.109			-0.102	0.044		
.025	-2.921	2.630	4.489	-3.862	-4.266	3.261	4.412	-3.435
.050	-4.820	4.073	4.762	-3.749	-3.356	2.538	4.587	-3.835
.100	-2.970	2.312	4.002	-3.900	-3.166	2.421	4.230	-2.736
.200	-2.883	2.244	3.202	-1.440	-1.061	1.621	3.277	-0.817
.260	-4.374	4.926	3.718	-0.918	0.036	0.162	3.763	0.085
.320	2.498	2.354	3.109	1.422	-0.273	0.958	2.240	2.453
.380	-0.886	1.534	2.238	2.314	-0.332	0.761	2.041	1.787
.440	-1.444	1.026	-0.027	0.000	-0.526	0.713	1.485	2.136
.500	-2.147	0.226	0.602	3.433	-0.735	0.387	0.741	2.320
.560	-2.204	-0.541	-1.165	2.985	-0.720	0.013	-0.620	2.584
.620	-2.238	-1.215	-1.624	1.379	-0.678	-0.240	-0.969	1.741
.700	-1.880	-1.717	0.551	1.657	-0.684	-0.365	0.018	1.162
.800	-0.418	-2.231	0.432	0.662	-0.933	0.126	0.187	0.462
.900	0.832	0.889	0.249	-0.366	-2.515	1.511	-0.227	0.242

(s-1) Tabulated data for test case 6E46 (point 476)

Figure 9. Continued.




(s-2) Plot of data for test case 6E46 (point 476)

Figure 9. Continued.

Point Number = 262			Mach Number = 0.896			Alphao = 2.00, deg.		
q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg	
117.1	401.1	449.2	.398E+07	1.132	4.96	0.069	1.022	
y/s = 0.309					y/s = 0.588			
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t
.000	-0.210	0.078			-0.275	0.053		
.025	-4.462	0.843	4.920	-0.832	-3.678	0.762	5.295	-0.962
.050	-4.580	0.824	4.569	-0.880	-5.615	1.081	4.136	-0.759
.100	-4.352	0.822	4.972	-0.859	-3.916	0.712	5.288	-0.999
.200	-4.130	0.788	4.264	-0.675	-3.589	0.633	3.978	-0.687
.260	-3.921	0.684	4.462	-0.843	-5.104	0.745	3.877	-0.607
.320	-4.516	0.861	3.603	-0.545	-3.876	0.614	3.925	-0.664
.380	-4.511	0.885	3.265	-0.529	-4.877	0.746	4.067	-0.820
.440	-2.993	0.453	2.616	-0.317	-4.877	0.746	3.961	-0.777
.500	-2.009	0.190	2.567	-0.252	-5.314	0.851	3.203	-0.559
.560	-1.289	-0.045	-1.558	1.613	-5.287	1.008	-2.780	1.459
.620	-2.176	0.213	1.193	0.838	-4.898	0.952	0.752	0.673
.700	-2.958	0.645	2.295	0.136	-4.016	1.039	2.460	1.090
.800	0.010	-0.561	3.958	0.423	0.741	-2.470	3.067	1.080
.900	-1.105	-0.768	3.126	0.290	-0.730	-0.288	2.794	0.609
y/s = 0.809					y/s = 0.951			
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t
.000	-0.276	0.046			-0.205	0.092		
.025	-3.633	0.700	4.099	-0.763	-4.966	0.894	4.092	-0.685
.050	-5.235	0.980	3.323	-0.624	-3.531	0.635	3.313	-0.584
.100	-3.535	0.617	4.534	-0.666	-4.142	0.723	4.526	-0.806
.200	-3.374	0.559	2.425	-0.736	-3.427	0.580	2.443	-0.339
.260	-3.433	0.544	1.606	-0.607	0.224	-0.002	1.625	-0.065
.320	-3.869	0.654	2.049	-0.561	-1.669	0.205	2.049	-0.321
.380	-3.425	0.592	1.553	-0.397	-1.606	0.254	1.558	-0.194
.440	-2.208	0.389	-1.112	0.000	-1.430	0.281	1.119	0.065
.500	-1.995	0.305	1.336	-0.235	-1.372	0.287	1.345	0.019
.560	-1.812	0.375	-0.708	1.501	-1.311	0.303	0.951	0.065
.620	-1.761	0.342	0.745	0.586	-0.529	0.416	-1.413	0.542
.700	-1.674	0.467	0.784	0.605	-0.084	0.074	0.172	0.937
.800	0.694	-1.345	1.680	0.117	-1.682	-0.032	1.614	0.472
.900	-0.273	0.062	1.323	-0.760	-3.469	0.212	1.321	0.468

(t-1) Tabulated data for test case 6E47 (point 262)
Figure 9. Continued.



(t-2) Plot of data for test case 6E47 (point 262)

Figure 9. Continued.

Point Number = 263 Mach Number = 0.896 Alphao = 2.00, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
117.1	401.2	449.2	.398E+07	1.132	9.95	0.139	0.989


x/c	y/s = 0.309				y/s = 0.588			
	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.150	0.088			-0.271	0.102		
.025	-3.837	1.314	4.365	-1.376	-3.133	1.215	4.648	-1.628
.050	-3.910	1.278	3.964	-1.474	-4.909	1.758	3.654	-1.308
.100	-3.782	1.295	4.387	-1.494	-3.357	1.104	4.642	-1.810
.200	-3.620	1.232	3.609	-1.076	-3.039	0.958	3.380	-1.217
.260	-3.390	0.998	3.690	-1.536	-4.593	1.213	3.337	-1.162
.320	-3.812	1.202	2.928	-0.923	-3.353	0.917	3.295	-1.278
.380	-3.810	1.209	2.760	-1.054	-4.284	1.245	3.205	-1.488
.440	-2.439	0.505	2.253	-0.754	-4.324	1.314	3.266	-1.629
.500	-1.680	0.009	2.125	-0.573	-4.576	1.478	2.612	-1.252
.560	-1.111	-0.497	0.355	1.344	-4.573	1.664	-1.548	1.725
.620	-1.854	-0.006	1.792	0.474	-4.116	1.564	1.718	0.838
.700	-2.378	0.918	2.955	-0.021	-3.437	1.538	3.853	0.466
.800	-0.436	-0.883	4.957	-0.910	-1.803	2.267	4.802	-0.243
.900	-1.528	-0.944	4.124	-0.624	-1.503	0.100	3.295	-0.658

x/c	y/s = 0.809				y/s = 0.951			
	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.197	0.122			-0.173	0.016		
.025	-3.143	1.188	3.641	-1.399	-4.455	1.473	3.602	-1.283
.050	-4.582	1.640	2.925	-1.145	-3.091	0.986	2.867	-1.100
.100	-3.142	1.015	4.003	-1.176	-3.666	1.086	3.902	-1.632
.200	-2.946	0.867	2.050	-1.332	-3.042	0.730	2.011	-0.895
.260	-3.030	0.778	1.364	-1.172	0.012	-0.463	1.389	-0.409
.320	-3.463	0.954	1.835	-1.157	-1.390	0.046	1.728	-0.946
.380	-3.029	0.783	1.407	-0.889	-1.274	-0.044	1.209	-0.898
.440	-1.763	0.343	-1.274	0.000	-1.094	-0.125	1.058	-0.711
.500	-1.548	0.226	1.495	-0.477	-0.866	-0.074	1.375	-0.746
.560	-1.316	0.206	-0.251	2.279	-0.579	0.004	1.298	-0.498
.620	-1.197	0.215	1.198	0.782	1.321	0.174	-0.540	1.344
.700	-0.620	0.689	2.818	0.416	0.731	0.899	2.790	0.779
.800	-2.396	1.728	2.913	-0.896	-1.711	1.647	3.066	-0.161
.900	-0.346	0.036	1.528	-0.991	-3.940	1.965	1.605	-0.237

(u-1) Tabulated data for test case 6E48 (point 263)
Figure 9. Continued.



(u-2) Plot of data for test case 6E48 (point 263)
Figure 9. Continued.

Point Number = 265 Mach Number = 0.902 Alphao = 2.01, deg.

	q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
118.3	402.1	452.2	.400E+07	1.132	19.99	0.278	1.055	


	y/s = 0.309				y/s = 0.588			
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.083	0.070			-0.123	0.107		
.025	-3.312	2.276	3.982	-2.226	-2.680	1.947	4.343	-2.579
.050	-3.408	2.230	3.503	-2.284	-4.262	2.810	3.355	-2.008
.100	-3.189	2.167	4.032	-2.135	-2.957	1.826	4.196	-2.612
.200	-3.020	2.029	3.579	-1.282	-2.612	1.557	3.189	-1.514
.260	-2.897	1.606	2.995	-1.764	-4.006	1.945	3.146	-1.201
.320	-3.102	1.901	2.697	-0.632	-2.863	1.440	3.031	-1.038
.380	-3.172	1.891	2.349	-0.674	-3.542	1.899	2.845	-1.075
.440	-2.204	0.772	1.933	-0.296	-3.494	1.985	2.764	-1.133
.500	-1.729	-0.179	1.900	-0.070	-3.670	2.223	2.318	-0.775
.560	-1.515	-0.958	1.639	0.850	-3.454	2.260	-0.444	0.931
.620	-1.891	-0.189	1.159	0.596	-3.034	2.008	1.451	0.957
.700	-1.882	0.971	2.215	-0.225	-1.128	0.755	2.076	0.422
.800	-1.176	-1.205	3.195	-1.742	0.189	1.399	2.714	-0.081
.900	-2.400	-1.019	2.673	-1.207	-0.419	0.499	2.214	-0.233

	y/s = 0.809				y/s = 0.951			
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.129	0.100			-0.095	0.052		
.025	-2.680	1.947	3.562	-2.317	-4.024	2.476	3.549	-2.000
.050	-3.979	2.745	2.819	-1.834	-2.822	1.736	2.749	-1.645
.100	-2.772	1.712	3.836	-1.785	-3.222	1.913	3.740	-2.212
.200	-2.550	1.449	2.183	-1.743	-2.522	1.387	2.377	-0.768
.260	-2.683	1.183	1.769	-1.294	1.381	-1.142	1.898	0.099
.320	-2.819	1.405	1.762	-0.926	-1.139	0.361	1.831	0.238
.380	-2.383	1.056	1.355	-0.134	-0.906	0.366	1.352	0.121
.440	-1.217	0.283	1.056	0.000	-0.825	0.415	1.041	0.784
.500	-1.292	0.172	1.303	0.011	-0.634	0.311	1.167	0.580
.560	-0.923	-0.002	-0.277	1.112	-0.741	0.338	0.922	0.842
.620	-0.977	0.036	1.355	0.889	-0.753	0.312	-1.243	1.291
.700	-0.953	0.218	0.475	0.816	0.707	-1.346	0.105	0.533
.800	3.716	-0.803	2.151	0.423	0.111	0.476	1.927	-1.319
.900	0.001	0.652	1.955	0.018	-1.660	1.793	1.955	-0.041

(v-1) Tabulated data for test case 6E49 (point 265)
Figure 9. Continued.



(v-2) Plot of data for test case 6E49 (point 265)

Figure 9. Continued.

Point Number = 481 Mach Number = 0.823 Alphao = -0.03, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
107.6	408.3	412.4	.399E+07	1.132	15.01	0.229	1.023


x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t
	y/s = 0.309				y/s = 0.588			

.000	0.056	0.005			0.042	0.038		
.025	-3.888	3.874	4.322	-3.905	-4.491	4.538	4.647	-4.379
.050	-3.163	3.252	3.157	-3.258	-3.014	2.762	2.968	-2.730
.100	-3.606	4.716	4.663	-4.762	-3.527	4.278	4.259	-4.681
.200	-3.214	7.152	5.146	-6.355	-3.264	7.129	4.446	-5.836
.260	-4.713	5.253	7.356	-8.373	-5.236	8.219	7.462	-7.974
.320	-6.035	5.434	9.107	-4.324	-8.910	7.241	11.508	-5.788
.380	-8.012	5.548	10.150	1.426	-6.706	-2.012	9.288	3.621
.440	-8.718	3.540	4.021	6.535	-3.604	-3.279	0.690	7.304
.500	-5.087	-4.645	-1.768	4.420	-3.792	-3.148	-1.068	3.539
.560	-5.616	-6.172	-1.692	-0.388	-3.310	-3.264	0.088	0.666
.620	-4.725	-4.858	-3.380	-2.679	-2.719	-3.275	-0.347	-0.886
.700	-2.028	-6.935	2.358	3.744	-2.413	-6.032	0.127	2.797
.800	5.266	-2.741	3.040	5.099	3.492	-2.233	0.253	4.137
.900	-0.235	1.210	2.321	3.701	0.439	0.716	0.395	2.772

x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t
	y/s = 0.809				y/s = 0.951			

.000	0.023	0.110			0.048	-0.029		
.025	-4.586	4.522	3.861	-3.588	-3.516	2.867	3.824	-3.020
.050	-3.062	2.875	2.759	-2.381	-4.315	3.996	2.668	-2.223
.100	-3.506	4.076	3.983	-3.837	-4.077	4.544	4.143	-3.427
.200	-4.917	7.154	1.514	-6.979	-1.075	-0.316	2.094	-0.796
.260	-4.353	1.465	3.109	-1.104	-4.247	1.429	3.185	-0.212
.320	-3.647	-0.604	2.216	0.803	-1.957	-0.120	2.236	0.137
.380	-3.162	-0.961	1.252	2.912	-1.780	-0.497	1.744	0.765
.440	-2.774	-1.463	0.280	0.000	-1.494	-0.884	0.884	1.295
.500	-2.582	-2.062	-0.078	2.293	-1.120	-1.176	0.402	1.341
.560	-2.013	-2.182	-1.363	1.018	-0.670	-1.356	-0.783	1.612
.620	-1.556	-2.462	-2.463	-0.060	0.011	-1.512	-1.396	2.031
.700	-0.494	-2.471	0.341	1.513	0.458	-1.264	0.624	0.475
.800	1.234	-1.523	0.388	1.463	0.601	-0.504	0.606	-0.290
.900	0.295	0.258	1.184	1.176	-1.434	0.978	1.014	-1.196

(w-1) Tabulated data for test case 6E50 (point 481)
Figure 9. Continued.



(w-2) Plot of data for test case 6E50 (point 481)

Figure 9. Continued.

Point Number = 469 Mach Number = 0.822 Alphao = 3.99, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
107.2	407.4	411.4	.399E+07	1.132	15.04	0.230	1.018

y/s = 0.309				y/s = 0.588				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t


.000	-0.633	0.469			-0.715	0.449		
.025	-3.791	2.323	5.513	-2.559	-3.396	2.106	5.602	-2.636
.050	-3.724	1.988	5.394	-2.678	-3.805	2.075	5.156	-2.393
.100	-3.763	2.034	5.163	-1.941	-3.987	2.093	4.798	-1.948
.200	-3.527	1.995	4.334	-0.993	-3.650	2.006	4.189	-0.867
.260	-3.594	1.871	4.493	-0.291	-3.142	1.519	4.501	-0.118
.320	-3.338	1.873	3.696	0.375	-3.084	1.633	3.395	0.513
.380	-3.989	2.742	3.386	0.844	-2.834	1.730	3.212	1.044
.440	-4.175	2.967	2.922	1.325	-3.331	3.194	2.614	1.437
.500	-2.730	3.219	2.337	1.761	-6.216	15.699	2.094	1.707
.560	-1.450	1.161	1.166	1.926	-6.837	12.233	1.022	1.749
.620	-18.208	17.279	-0.325	1.771	-3.237	-4.326	-0.266	1.496
.700	-1.515	-5.945	1.453	1.064	-1.753	-5.526	0.739	1.063
.800	1.559	-6.918	1.393	0.608	0.505	-5.549	0.736	0.696
.900	1.292	0.084	0.603	0.814	1.102	0.230	0.480	0.552

y/s = 0.809				y/s = 0.951				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.735	0.416			-0.523	0.331		
.025	-3.061	1.789	4.793	-2.421	-3.834	2.021	4.782	-2.129
.050	-3.634	1.916	4.874	-2.256	-3.423	1.835	4.866	-2.076
.100	-4.105	2.110	3.931	-1.842	-3.501	2.256	4.004	-1.148
.200	-3.330	1.770	2.716	-0.655	-0.981	1.233	2.758	-0.043
.260	-3.403	1.871	2.532	0.105	-0.628	1.132	2.488	0.475
.320	-4.820	7.338	2.415	0.673	-0.414	2.213	2.410	0.570
.380	-0.017	4.784	1.712	1.112	-0.886	2.008	1.447	1.164
.440	-1.570	2.602	-1.610	0.000	-1.273	1.429	1.051	1.321
.500	-2.179	1.399	1.049	1.768	-1.418	0.917	0.716	1.467
.560	-2.305	0.109	0.029	2.307	-1.311	0.511	-0.068	1.687
.620	-1.922	-0.938	-0.850	1.487	-1.002	-0.148	-0.630	1.195
.700	-1.367	-1.339	0.665	1.053	-1.166	-0.193	-0.073	0.954
.800	-0.614	-1.328	0.663	0.255	-1.680	0.174	0.071	0.672
.900	0.094	0.726	0.386	0.116	-4.675	2.091	0.148	0.365

(x-1) Tabulated data for test case 6E51 (point 469)

Figure 9. Continued.



(x-2) Plot of data for test case 6E51 (point 469)
Figure 9. Continued.

Point Number = 269 Mach Number = 0.901 Alphao = -0.03, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
118.2	402.4	451.8	.399E+07	1.132	14.98	0.208	1.065

y/s = 0.309				y/s = 0.588				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t


.000	0.000	0.000			-0.023	0.049		
.025	-4.140	1.673	4.387	-1.631	-4.662	2.095	4.878	-2.001
.050	-3.554	1.400	2.969	-1.266	-2.947	1.026	2.794	-0.973
.100	-3.406	1.335	4.016	-1.391	-3.095	1.090	3.351	-1.174
.200	-3.726	1.683	3.430	-1.421	-3.417	1.450	3.310	-1.284
.260	-3.693	1.337	3.532	-1.307	-3.132	0.981	2.945	-0.856
.320	-3.346	1.017	3.623	-1.369	-3.080	0.965	3.066	-0.822
.380	-2.485	0.469	2.925	-0.724	-2.968	0.964	2.508	-0.616
.440	-1.979	0.215	1.719	0.093	-2.885	1.039	2.640	-0.747
.500	-2.036	0.189	1.450	0.086	-2.762	1.060	0.831	0.224
.560	-2.202	0.135	-0.432	-0.550	-3.138	1.544	-2.140	1.802
.620	-1.882	-0.072	0.968	-0.041	-3.410	2.257	0.965	-0.076
.700	-1.999	0.429	0.749	-0.083	-0.395	-1.116	1.804	-0.704
.800	8.847	-6.404	1.717	-0.120	4.405	-0.239	1.929	-1.551
.900	-1.340	0.115	1.866	-0.694	0.372	-0.460	1.617	-1.337

y/s = 0.809				y/s = 0.951				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.046	0.029			0.000	0.000		
.025	-4.546	1.958	3.614	-1.551	-3.310	1.127	3.618	-1.225
.050	-3.717	1.427	2.578	-0.815	-4.169	1.600	2.563	-0.818
.100	-3.167	1.047	3.163	-1.110	-2.979	0.928	3.208	-0.914
.200	-3.537	1.294	2.006	-1.128	-2.491	0.681	2.083	-0.539
.260	-3.365	0.952	1.442	-0.995	-1.778	0.430	1.490	-0.223
.320	-3.594	1.126	0.970	-1.115	0.692	-0.297	-0.628	0.807
.380	-3.592	1.300	0.726	-0.671	-1.560	0.044	0.736	0.160
.440	-1.722	0.003	0.049	0.000	-1.560	-0.022	0.326	0.281
.500	-1.376	-0.250	-0.340	-0.185	-1.237	-0.043	0.335	0.172
.560	-1.275	-0.429	0.090	-0.426	-1.057	-0.200	-0.636	-0.113
.620	-1.147	-0.292	0.494	-0.444	-0.429	-0.553	0.497	-0.321
.700	-0.633	-0.298	0.834	0.145	3.919	-2.459	0.416	-0.754
.800	5.114	-1.040	0.925	0.384	1.010	0.160	0.328	-0.911
.900	-0.069	0.534	0.306	-0.552	0.117	0.690	-0.289	0.145

(y-1) Tabulated data for test case 6E52 (point 269)

Figure 9. Continued.



(y-2) Plot of data for test case 6E52 (point 269)
Figure 9. Continued.

Point Number = 258 Mach Number = 0.900 Alphao = 4.03, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
117.8	401.1	451.1	.399E+07	1.132	14.95	0.208	1.024

x/c	y/s = 0.309				y/s = 0.588			
	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t


.000	-0.436	0.252			-0.553	0.271		
.025	-3.813	1.754	4.267	-1.528	-3.147	1.461	4.361	-1.596
.050	-3.438	1.347	4.041	-1.649	-3.800	1.497	3.769	-1.424
.100	-3.654	1.410	3.612	-1.195	-3.723	1.385	3.155	-1.148
.200	-3.084	1.178	3.923	-1.490	-3.247	1.221	4.165	-1.925
.260	-3.351	1.095	2.292	-0.092	-2.958	0.848	2.374	-0.393
.320	-3.174	1.093	2.058	0.532	-3.000	0.906	2.499	0.311
.380	-3.717	1.555	2.115	0.219	-2.798	0.797	2.198	0.419
.440	-3.791	1.664	2.636	-0.512	-2.643	0.728	2.404	0.088
.500	-3.353	1.409	2.301	-0.477	-2.688	0.776	2.126	-0.011
.560	-1.618	0.446	1.305	0.316	-2.725	0.849	0.665	-0.096
.620	-1.556	-0.180	1.299	-1.312	-1.516	0.579	0.808	-1.142
.700	3.475	0.866	1.877	0.311	-0.541	0.143	1.739	0.427
.800	-1.365	0.308	3.072	0.177	0.011	0.503	2.574	-0.018
.900	-1.547	0.650	2.355	0.492	-1.788	1.252	1.568	0.976

x/c	y/s = 0.809				y/s = 0.951			
	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.558	0.259			-0.524	0.197		
.025	-2.828	1.349	3.580	-1.497	-3.567	1.477	3.562	-1.339
.050	-3.446	1.477	3.635	-1.377	-3.151	1.312	3.592	-1.415
.100	-3.746	1.483	2.860	-1.244	-3.258	1.192	2.864	-0.964
.200	-3.136	1.198	1.352	-1.997	-2.539	0.874	1.496	-0.208
.260	-3.167	0.932	2.077	-0.513	-2.676	0.990	2.003	-0.713
.320	-3.110	0.927	1.213	0.672	-1.586	0.343	0.902	0.995
.380	-4.425	1.743	1.109	0.801	-1.636	0.378	0.694	1.017
.440	-2.935	1.097	-0.719	0.000	-1.585	0.346	0.637	0.352
.500	-1.993	0.291	0.441	0.240	-1.765	0.302	0.392	0.217
.560	-1.932	0.320	-0.278	-0.493	-1.621	-0.062	0.279	-0.012
.620	-1.733	0.076	-0.064	0.391	-0.812	-1.274	-1.744	-0.607
.700	-1.634	-0.383	1.040	0.208	0.167	-1.220	0.210	-1.156
.800	5.480	2.270	1.570	-0.494	0.049	0.276	1.577	-0.382
.900	-0.760	0.969	0.808	-1.626	-1.869	3.185	0.749	0.587

(z-1) Tabulated data for test case 6E53 (point 258)

Figure 9. Continued.



(z-2) Plot of data for test case 6E53 (point 258)
Figure 9. Continued.


Point Number = 632 Mach Number = 0.825 Alphao = 1.98, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
108.7	410.9	413.7	.401E+07	1.132	10.03	0.152	1.014

x/c	y/s = 0.309				y/s = 0.588			
	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t
.000	-0.315	0.324			-0.424	0.374		
.025	-4.957	2.828	6.145	-2.866	-4.078	2.317	6.412	-2.963
.050	-6.858	4.056	5.476	-2.694	-7.082	4.007	5.059	-2.252
.100	-3.974	2.033	5.694	-2.347	-3.826	1.950	4.975	-1.860
.200	-4.708	2.806	3.684	-0.577	-4.134	2.445	3.648	-0.429
.260	-5.251	3.218	5.786	-1.314	-4.838	2.919	5.702	-0.842
.320	-0.277	0.196	3.272	0.194	-0.269	0.206	3.176	0.537
.380	-4.289	3.037	3.133	0.446	-14.473	12.805	2.371	0.920
.440	-10.220	7.562	1.948	0.759	-12.228	7.406	1.560	0.915
.500	-15.071	7.253	1.172	0.682	-2.619	-3.754	0.566	0.912
.560	-10.809	-0.927	-0.083	0.502	-0.710	-5.321	-0.404	0.395
.620	1.063	-8.181	-0.111	0.496	0.138	-5.253	-0.095	0.140
.700	4.069	-7.371	1.297	0.559	1.694	-4.069	0.991	0.750
.800	3.353	-0.799	1.725	0.541	1.879	-0.399	1.340	0.841
.900	0.303	0.911	1.822	0.397	0.003	0.735	1.324	0.758

x/c	y/s = 0.809				y/s = 0.951			
	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t
.000	-0.459	0.329			-0.311	0.245		
.025	-3.938	2.219	5.071	-2.509	-5.264	2.613	5.078	-2.062
.050	-7.291	4.210	5.096	-2.226	-4.581	2.457	5.085	-2.044
.100	-3.881	2.089	4.128	-2.157	-6.482	3.803	4.251	-1.163
.200	-4.509	2.807	1.751	-0.054	-2.760	1.969	1.752	0.015
.260	-10.386	8.808	1.861	-0.310	-3.463	2.241	1.827	0.375
.320	-0.277	0.195	1.134	0.535	-0.107	0.036	0.994	0.648
.380	-3.559	0.062	0.846	0.777	-2.025	0.191	0.758	0.590
.440	-2.438	-1.189	-0.448	0.000	-1.716	-0.349	0.420	0.602
.500	-1.470	-2.212	0.199	0.803	-1.133	-0.844	0.185	0.593
.560	-0.807	-2.292	-0.646	0.439	-0.609	-1.018	-0.688	0.495
.620	-0.318	-2.352	-0.961	0.277	-0.278	-1.037	-0.905	0.577
.700	0.028	-1.751	0.292	0.560	-0.053	-0.846	0.029	0.451
.800	0.380	-0.338	0.435	0.585	-0.678	-0.015	0.283	0.423
.900	-0.195	0.470	0.530	0.709	-3.380	1.118	0.549	0.292

(aa-1) Tabulated data for test case 6E54 (point 632)
Figure 9. Continued.



(aa-2) Plot of data for test case 6E54 (point 632)

Figure 9. Continued.

Point Number = 633 Mach Number = 0.826 Alphao = 1.98, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
108.9	411.1	414.1	.401E+07	1.132	15.03	0.228	0.984


y/s = 0.309				y/s = 0.588				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.020	0.174			-0.167	0.238		
.025	-3.850	2.922	5.580	-3.487	-3.175	2.366	5.714	-3.710
.050	-5.022	3.785	4.960	-3.371	-5.754	4.165	4.590	-2.981
.100	-3.148	2.204	5.428	-3.058	-2.945	1.986	4.667	-2.630
.200	-3.375	2.862	4.524	-1.111	-3.019	2.283	4.793	-1.811
.260	-3.355	2.795	6.340	-1.758	-3.350	2.617	6.153	-1.297
.320	-0.156	0.173	5.110	-0.384	-0.114	0.132	5.581	-0.312
.380	-1.869	1.289	4.487	1.633	-3.987	12.419	3.479	2.233
.440	-1.736	5.375	2.502	2.092	-6.047	12.792	2.350	2.261
.500	-5.623	15.365	0.917	1.949	-4.377	-1.214	0.357	1.947
.560	-9.299	8.641	-0.303	1.245	-3.623	-3.623	-0.620	0.916
.620	-5.506	-6.246	-0.175	0.915	-3.098	-4.441	-0.309	0.754
.700	-2.801	-8.885	1.517	1.082	-1.206	-4.800	1.221	1.167
.800	2.655	-2.778	2.068	1.072	1.848	-1.601	1.846	1.322
.900	0.773	0.708	2.183	0.812	0.364	0.664	1.921	0.680

y/s = 0.809				y/s = 0.951				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.149	0.179			-0.071	0.160		
.025	-3.011	2.294	4.782	-3.058	-4.404	2.731	4.837	-2.561
.050	-5.415	4.037	4.894	-2.842	-3.557	2.327	4.908	-2.676
.100	-3.022	2.180	4.358	-2.981	-5.197	4.223	4.608	-1.806
.200	-3.122	2.528	2.375	-0.288	-0.863	1.314	2.387	-0.004
.260	-4.926	9.383	3.044	-0.961	-0.640	2.421	3.050	0.472
.320	-0.065	0.284	1.821	1.230	-0.083	0.082	1.784	0.985
.380	-2.641	1.912	1.510	1.530	-1.283	1.006	1.391	1.151
.440	-2.748	0.509	-1.437	0.000	-1.264	0.443	0.952	1.395
.500	-2.546	-1.003	0.359	1.527	-1.162	-0.075	0.440	1.449
.560	-2.148	-1.601	-0.677	1.018	-0.891	-0.431	-0.392	1.158
.620	-1.651	-2.183	-0.976	0.667	-0.642	-0.592	-0.915	1.056
.700	-0.849	-1.916	0.600	0.980	-0.333	-0.547	0.224	0.904
.800	0.239	-0.657	0.740	1.082	-0.798	0.168	0.561	0.816
.900	-0.103	0.394	0.785	0.766	-2.965	1.491	0.776	0.401

(bb-1) Tabulated data for test case 6E55 (point 633)
Figure 9. Continued.



(bb-2) Plot of data for test case 6E55 (point 633)

Figure 9. Continued.

Point Number = 634 Mach Number = 0.826 Alphao = 1.98, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
108.9	411.1	414.1	.401E+07	1.132	20.09	0.305	1.005


	y/s = 0.309				y/s = 0.588			
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	0.030	0.168			-0.135	0.184		
.025	-3.311	3.219	4.942	-4.132	-2.849	2.629	5.057	-4.350
.050	-4.336	4.044	4.336	-4.044	-5.198	4.535	4.038	-3.523
.100	-2.735	2.328	4.891	-3.740	-2.632	2.094	4.269	-3.240
.200	-2.903	2.903	4.658	-1.705	-2.807	2.241	4.154	-1.586
.260	-2.872	2.688	6.246	-2.498	-2.970	2.492	6.165	-2.232
.320	-0.137	0.182	5.548	-0.662	-0.108	0.133	5.243	-0.137
.380	-1.639	0.489	5.511	1.855	0.545	12.473	4.399	2.165
.440	0.435	4.597	3.099	3.109	-2.268	6.334	2.936	3.030
.500	0.714	15.148	0.862	3.310	-4.179	-0.580	0.593	3.079
.560	-5.578	7.996	-0.628	1.773	-4.363	-2.109	-0.616	1.656
.620	-8.027	-3.557	-0.450	1.292	-4.218	-3.020	-0.320	1.035
.700	-7.085	-7.185	1.660	1.564	-2.643	-4.398	1.333	1.561
.800	2.308	-4.131	2.407	1.527	1.844	-1.944	2.013	1.590
.900	0.951	0.384	2.191	0.815	0.457	0.789	2.015	0.940

	y/s = 0.809				y/s = 0.951			
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.170	0.152			-0.127	0.114		
.025	-2.796	2.518	4.404	-3.717	-4.114	3.066	4.415	-3.137
.050	-5.136	4.433	4.428	-3.485	-3.406	2.585	4.371	-3.294
.100	-2.823	2.221	3.895	-3.798	-4.890	4.281	4.226	-2.372
.200	-2.983	2.199	2.406	-0.626	-0.634	0.384	2.439	-0.248
.260	-3.816	7.269	3.175	-1.718	0.351	1.025	3.306	0.069
.320	0.089	0.146	2.175	1.337	-0.028	0.050	2.101	1.025
.380	-1.053	1.627	1.817	2.018	-0.629	0.737	1.645	1.410
.440	-1.673	0.727	1.064	0.000	-0.768	0.591	1.099	1.800
.500	-2.103	-0.162	0.289	2.702	-0.954	0.170	0.276	1.803
.560	-2.114	-0.854	-0.854	1.611	-0.884	-0.224	-0.680	1.507
.620	-1.859	-1.416	-1.084	0.894	-0.692	-0.398	-0.913	1.168
.700	-1.248	-1.557	0.599	1.425	-0.538	-0.509	0.164	1.071
.800	-0.107	-0.676	0.773	1.387	-0.854	0.045	0.432	0.931
.900	-0.317	0.606	0.804	1.051	-2.675	1.405	0.675	0.614

(cc-1) Tabulated data for test case 6E56 (point 634)
Figure 9. Continued.



(cc-2) Plot of data for test case 6E56 (point 634)

Figure 9. Continued.


Point Number = 180 Mach Number = 0.802 Alphao = 3.30, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
108.0	423.1	405.4	.404E+07	1.133	15.12	0.234	0.500

y/s = 0.309					y/s = 0.588				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	
.000	-0.539	0.742			-0.724	0.562			
.025	-4.508	3.348	5.758	-2.563	-3.849	2.695	6.186	-2.728	
.050	-4.165	2.841	5.653	-2.517	-4.649	2.939	5.607	-2.334	
.100	-4.722	3.443	5.260	-1.608	-4.507	2.949	5.131	-1.637	
.200	-4.091	3.324	3.985	-0.454	-3.777	2.795	4.109	-0.367	
.260	-3.835	3.094	3.658	0.249	-3.625	2.988	3.875	0.407	
.320	-4.754	5.280	2.802	0.596	-4.943	4.943	3.073	0.922	
.380	-12.307	26.881	2.561	1.003	-22.578	44.698	2.499	1.149	
.440	-16.535	13.630	2.168	1.287	-3.343	-5.744	2.185	1.474	
.500	-3.889	-10.291	1.743	1.304	-2.249	-7.221	1.589	1.315	
.560	-2.091	-10.099	1.033	1.073	-1.647	-6.557	0.859	1.489	
.620	-1.058	-8.875	0.243	1.237	-0.950	-5.999	0.078	1.488	
.700	0.916	-5.656	0.841	1.088	0.451	-4.216	0.555	1.132	
.800	2.282	-1.915	0.972	0.972	2.180	-2.195	0.685	0.919	
.900	0.929	1.014	0.519	0.612	0.961	1.425	0.430	0.677	

y/s = 0.809					y/s = 0.951				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	
.000	-0.656	0.640			-0.411	0.399			
.025	-3.475	2.223	5.058	-2.087	-4.493	2.531	5.064	-1.833	
.050	-4.271	2.679	5.122	-1.771	-3.623	2.203	5.134	-1.629	
.100	-4.666	3.124	3.810	-1.081	-4.835	4.043	3.869	-0.461	
.200	-3.578	3.553	2.521	0.056	-1.659	3.270	2.498	0.342	
.260	-9.721	23.012	2.218	0.751	-2.138	4.692	2.055	1.015	
.320	-3.243	1.451	2.344	1.152	-1.931	1.620	2.591	0.480	
.380	-2.862	-0.115	1.568	1.187	-1.356	0.618	1.121	1.451	
.440	-2.736	-1.178	-1.349	0.000	-1.588	0.226	0.688	1.449	
.500	-2.156	-1.887	0.520	1.735	-1.489	0.042	0.229	1.588	
.560	-1.534	-2.283	0.016	1.490	-1.073	-0.403	-0.042	1.145	
.620	-1.193	-2.478	-0.949	1.624	-1.039	-0.484	-0.898	1.466	
.700	-0.738	-2.049	0.609	1.017	-0.849	-0.346	-0.197	1.012	
.800	-0.136	-0.674	0.776	0.293	-1.375	0.029	-0.098	0.796	
.900	0.178	0.782	0.667	-0.140	-4.277	2.207	-0.047	0.686	

(dd-1) Tabulated data for test case 6E57 (point 180)
Figure 9. Continued.



(dd-2) Plot of data for test case 6E57 (point 180)

Figure 9. Continued.

Point Number = 184 Mach Number = 0.801 Alphao = 3.30, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
107.8	423.4	404.9	.404E+07	1.133	15.03	0.233	0.983


y/s = 0.309				y/s = 0.588				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.478	0.588			-0.633	0.603		
.025	-4.589	3.201	5.880	-2.557	-3.795	2.608	6.098	-2.639
.050	-3.986	2.530	5.751	-2.560	-4.651	2.895	5.551	-2.288
.100	-4.414	3.045	5.392	-1.700	-4.409	3.053	5.114	-1.612
.200	-3.807	2.985	4.218	-0.563	-3.634	2.922	4.066	-0.341
.260	-3.594	2.879	4.011	0.295	-3.538	2.666	3.972	0.629
.320	-0.192	0.219	3.124	0.721	-3.996	4.864	2.954	0.903
.380	-5.116	10.084	2.721	1.044	-11.721	23.204	2.504	1.248
.440	-10.257	22.612	2.276	1.304	-7.373	4.589	1.942	1.490
.500	-13.639	10.278	1.799	1.390	-3.768	-4.523	1.409	1.554
.560	-4.764	-8.421	0.839	1.332	-2.509	-6.027	0.595	1.457
.620	-2.610	-9.740	0.158	1.272	-1.756	-6.045	-0.110	1.395
.700	-0.664	-8.075	0.818	1.062	-0.275	-4.772	0.531	1.103
.800	2.709	-3.357	0.940	0.784	2.018	-2.639	0.654	0.665
.900	0.964	1.169	0.518	0.705	0.969	0.926	0.514	0.557

y/s = 0.809				y/s = 0.951				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-0.615	0.536			-0.435	0.388		
.025	-3.447	2.290	4.996	-2.244	-4.542	2.740	5.026	-1.869
.050	-4.297	2.801	5.009	-1.917	-3.630	2.330	5.042	-1.648
.100	-4.580	3.112	3.733	-1.283	-4.971	4.231	3.816	-0.489
.200	-3.664	3.915	2.390	-0.012	-1.637	2.824	2.313	0.602
.260	-8.595	17.468	2.111	0.632	-2.484	4.354	1.935	0.952
.320	-3.357	1.755	2.151	0.922	-1.960	1.466	2.270	0.532
.380	-3.139	-0.225	1.302	1.212	-1.616	0.497	0.866	1.314
.440	-2.873	-1.285	-1.443	0.000	-1.688	0.091	0.460	1.383
.500	-2.252	-2.028	0.689	1.490	-1.544	-0.303	0.362	1.411
.560	-1.524	-2.346	-0.056	1.456	-1.237	-0.517	-0.425	1.333
.620	-1.153	-2.485	-0.891	1.430	-0.927	-0.606	-0.962	1.095
.700	-0.645	-1.997	0.432	1.014	-0.810	-0.571	-0.179	0.856
.800	0.150	-1.038	0.664	0.348	-1.454	0.091	-0.022	0.699
.900	0.046	0.756	0.523	-0.044	-4.247	2.062	-0.100	0.515

(ee-1) Tabulated data for test case 6E58 (point 184)
Figure 9. Continued.




(ee-2) Plot of data for test case 6E58 (point 184)

Figure 9. Continued.

Point Number = 189				Mach Number = 0.802				Alphao = 3.29, deg.			
q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg				
108.2	424.3	405.4	.404E+07	1.133	14.99	0.232	1.531				
y/s = 0.309						y/s = 0.588					
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t
.000	-0.490	0.566			-0.595	0.622					
.025	-4.652	3.209	5.894	-2.587	-3.709	2.597	6.056	-2.684			
.050	-3.909	2.500	5.823	-2.654	-4.629	2.972	5.550	-2.345			
.100	-4.282	2.954	5.490	-1.752	-4.225	2.970	5.155	-1.695			
.200	-3.802	3.035	4.272	-0.524	-3.485	2.832	4.205	-0.449			
.260	-3.693	3.110	4.148	0.217	-3.461	2.743	4.138	0.670			
.320	-4.010	4.346	3.239	0.778	-4.868	8.640	3.068	0.973			
.380	-5.765	14.341	2.733	1.127	-8.402	16.004	2.541	1.278			
.440	-8.107	14.931	2.250	1.341	-8.381	9.019	1.973	1.486			
.500	-9.867	7.489	1.738	1.422	-4.249	-2.802	1.310	1.683			
.560	-8.209	-3.552	0.845	1.500	-2.830	-5.277	0.639	1.558			
.620	-2.899	-8.974	0.169	1.374	-2.035	-5.592	-0.136	1.528			
.700	-1.045	-8.393	0.831	1.060	-0.456	-4.731	0.595	1.039			
.800	3.085	-3.107	0.927	0.633	1.932	-2.238	0.697	0.505			
.900	1.078	1.245	0.642	0.574	0.834	1.152	0.571	0.424			
y/s = 0.809						y/s = 0.951					
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t
.000	-0.615	0.548			-0.498	0.453					
.025	-3.417	2.296	4.812	-2.270	-4.724	2.963	4.825	-1.842			
.050	-4.259	2.787	4.804	-1.979	-3.524	2.404	4.829	-1.607			
.100	-4.277	2.895	3.546	-1.405	-5.007	4.337	3.640	-0.447			
.200	-3.548	3.752	2.245	-0.006	-1.712	2.636	2.178	0.547			
.260	-6.323	12.738	1.972	0.710	-2.596	3.433	1.774	0.967			
.320	-3.282	3.939	1.690	0.986	-2.056	1.300	1.712	0.657			
.380	-2.956	0.474	1.159	1.344	-1.787	0.409	0.787	1.184			
.440	-2.822	-0.746	-1.172	0.000	-1.833	-0.054	0.426	1.159			
.500	-2.346	-1.673	0.553	1.640	-1.532	-0.354	0.097	1.231			
.560	-1.733	-2.014	-0.103	1.566	-1.344	-0.570	-0.416	1.163			
.620	-1.333	-2.299	-0.912	1.378	-0.917	-0.770	-0.986	1.025			
.700	-0.754	-1.875	0.397	1.066	-0.886	-0.627	-0.202	0.759			
.800	0.000	-0.861	0.528	0.406	-1.421	-0.045	-0.026	0.561			
.900	0.047	0.785	0.405	-0.117	-4.005	2.032	-0.007	0.412			

(ff-1) Tabulated data for test case 6E59 (point 189)
Figure 9. Continued.




(ff-2) Plot of data for test case 6E59 (point 189)
Figure 9. Continued.

Point Number = 613 Mach Number = 0.402 Alphao = 11.99, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
54.4	652.8	202.4	.402E+07	1.132	5.00	0.155	1.004

y/s = 0.309					y/s = 0.588				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	
.000	-13.696	-0.024			-13.949	0.951			
.025	-19.415	-14.631	2.054	0.036	-25.675	-1.795	2.452	-0.086	
.050	-7.048	-2.128	2.796	0.024	-7.906	0.650	3.195	-0.089	
.100	-6.113	2.225	3.023	0.100	-5.237	1.161	3.025	0.021	
.200	-3.432	1.249	2.379	0.292	-2.737	0.119	2.385	0.238	
.260	-2.449	0.158	2.012	0.417	-2.383	-0.255	1.604	0.409	
.320	-2.111	-0.059	1.762	0.479	-1.797	-0.563	1.780	0.408	
.380	-1.619	-0.341	1.564	0.542	-1.471	-0.624	1.578	0.498	
.440	-1.217	-0.628	1.367	0.577	-1.223	-0.618	1.441	0.545	
.500	-0.997	-0.763	1.217	0.628	-1.112	-0.584	1.197	0.538	
.560	-0.657	-0.863	1.125	0.676	-0.830	-0.605	0.892	0.382	
.620	-0.264	-1.052	0.853	0.758	-0.452	-0.727	0.766	0.596	
.700	0.236	-1.523	0.466	0.718	0.028	-0.798	0.451	0.589	
.800	0.973	-1.679	0.238	0.703	0.597	-0.905	0.302	0.550	
.900	1.355	-1.137	0.133	0.672	0.978	-0.787	0.172	0.484	
y/s = 0.809					y/s = 0.951				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	
.000	-13.478	1.679			-9.101	1.263			
.025	-12.293	0.903	3.016	-0.218	-14.201	1.870	3.007	-0.327	
.050	-7.515	0.525	3.190	-0.197	-5.224	0.521	3.183	-0.284	
.100	-4.109	0.014	2.397	-0.026	-2.738	0.067	2.396	-0.050	
.200	-2.036	-0.272	1.534	0.208	-1.531	-0.172	1.532	0.169	
.260	-1.863	-0.278	1.183	0.298	-1.240	-0.194	1.168	0.268	
.320	-1.363	-0.422	0.723	0.375	-1.414	-0.191	0.668	0.322	
.380	-1.162	-0.474	0.789	0.237	-0.671	-0.316	0.728	0.329	
.440	-0.926	-0.445	-0.690	0.000	-0.456	-0.343	0.628	0.395	
.500	-0.778	-0.478	0.450	0.522	-1.181	-0.204	0.327	0.396	
.560	-0.713	-0.474	0.378	0.545	-1.026	-0.351	0.248	0.383	
.620	-0.727	-0.452	0.303	0.521	-1.407	-0.235	-0.045	0.397	
.700	-0.608	-0.426	0.277	0.528	-1.936	-0.122	-0.298	0.419	
.800	-0.500	-0.276	0.232	0.488	-3.024	-0.069	-0.604	0.431	
.900	-0.282	-0.044	0.196	0.375	-4.159	0.240	-0.455	0.344	

(gg-1) Tabulated data for test case 6E60 (point 613)
Figure 9. Continued.



(gg-2) Plot of data for test case 6E60 (point 613)

Figure 9. Continued.

Point Number = 614 Mach Number = 0.401 Alphao = 12.00, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
54.2	652.9	202.1	.401E+07	1.132	10.02	0.312	0.998


y/s = 0.309				y/s = 0.588				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-14.035	3.266			-13.688	3.236		
.025	-24.314	-2.641	2.116	-0.185	-30.145	2.584	2.445	-0.344
.050	-8.252	0.505	2.861	-0.235	-7.726	1.755	3.194	-0.364
.100	-5.063	1.030	3.100	-0.016	-4.495	1.400	3.041	-0.101
.200	-2.870	0.025	2.492	0.413	-2.794	-0.660	2.442	0.361
.260	-2.175	-0.736	2.092	0.620	-2.328	-0.628	1.741	0.746
.320	-2.059	-0.878	1.780	0.800	-1.881	-0.987	1.854	0.775
.380	-1.808	-1.002	1.543	0.887	-1.472	-1.000	1.616	0.874
.440	-1.264	-1.170	1.430	0.961	-1.330	-1.002	1.430	0.961
.500	-1.049	-1.141	1.279	1.066	-1.135	-0.969	1.255	1.005
.560	-0.819	-1.316	1.121	1.152	-0.852	-0.933	0.990	1.193
.620	-0.465	-1.358	0.915	1.251	-0.520	-1.151	0.867	1.071
.700	-0.017	-1.607	0.545	1.203	-0.121	-1.257	0.521	1.087
.800	0.478	-1.833	0.340	1.157	0.245	-1.239	0.346	1.034
.900	0.758	-1.610	0.208	1.071	0.584	-1.054	0.221	0.892

y/s = 0.809				y/s = 0.951				
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-13.141	3.743			-8.761	2.562		
.025	-11.921	2.972	2.877	-0.544	-13.707	3.853	2.845	-0.693
.050	-7.383	1.435	3.066	-0.518	-5.116	1.059	3.047	-0.570
.100	-4.127	0.238	2.351	-0.159	-2.696	0.122	2.349	-0.148
.200	-2.126	-0.491	1.476	0.331	-1.572	-0.334	1.462	0.300
.260	-1.827	-0.500	1.219	0.527	-1.251	-0.423	1.174	0.467
.320	-1.381	-0.704	0.914	0.606	-1.383	-0.384	0.751	0.623
.380	-1.260	-0.800	0.940	0.693	-0.689	-0.691	0.785	0.673
.440	-0.936	-0.848	-0.726	0.000	-0.479	-0.716	0.613	0.684
.500	-0.795	-0.829	0.665	0.911	-1.140	-0.393	0.416	0.819
.560	-0.694	-0.842	0.503	0.986	-1.004	-0.557	0.284	0.752
.620	-0.595	-0.773	0.398	0.972	-1.304	-0.446	0.020	0.746
.700	-0.528	-0.680	0.258	0.979	-1.713	-0.180	-0.232	0.769
.800	-0.358	-0.449	0.154	0.907	-2.870	-0.070	-0.527	0.821
.900	-0.165	-0.048	0.097	0.799	-3.756	0.501	-0.398	0.764

(hh-1) Tabulated data for test case 6E61 (point 614)
Figure 9. Continued.



(hh-2) Plot of data for test case 6E61 (point 614)

Figure 9. Continued.


Point Number = 615 Mach Number = 0.401 Alphao = 12.01, deg.

q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
54.2	652.8	202.0	.401E+07	1.132	14.99	0.466	1.012

x/c	y/s = 0.309				y/s = 0.588			
	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t
.000	-13.887	5.527			-13.375	5.871		
.025	-26.214	2.432	2.177	-0.368	-26.931	9.431	2.478	-0.590
.050	-8.191	1.474	2.962	-0.480	-7.371	1.540	3.222	-0.632
.100	-5.128	0.503	3.225	-0.113	-4.921	0.223	3.107	-0.212
.200	-2.989	-0.641	2.608	0.526	-2.995	-0.853	2.561	0.475
.260	-2.542	-1.245	2.264	0.896	-2.462	-1.010	1.871	1.063
.320	-2.051	-1.312	1.943	1.163	-1.911	-1.318	1.904	1.117
.380	-1.747	-1.350	1.671	1.264	-1.530	-1.431	1.718	1.295
.440	-1.419	-1.691	1.527	1.351	-1.348	-1.529	1.488	1.393
.500	-1.156	-1.609	1.359	1.519	-1.064	-1.396	1.295	1.500
.560	-0.960	-1.669	1.215	1.636	-0.739	-1.402	1.122	1.633
.620	-0.580	-1.776	0.939	1.680	-0.462	-1.457	0.853	1.598
.700	-0.296	-1.959	0.705	1.669	-0.142	-1.693	0.592	1.592
.800	-0.036	-2.038	0.514	1.619	0.138	-1.579	0.450	1.579
.900	0.210	-1.514	0.424	1.528	0.297	-1.093	0.275	1.273

x/c	y/s = 0.809				y/s = 0.951			
	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t
.000	-12.682	5.620			-8.794	3.769		
.025	-11.704	4.423	3.055	-0.802	-13.878	5.551	3.003	-1.017
.050	-7.336	2.145	3.257	-0.778	-5.209	1.553	3.231	-0.848
.100	-4.176	0.343	2.539	-0.255	-2.822	0.217	2.538	-0.226
.200	-2.296	-0.809	1.722	0.462	-1.691	-0.469	1.705	0.416
.260	-1.921	-0.835	1.369	0.792	-1.284	-0.596	1.289	0.711
.320	-1.448	-1.181	1.093	0.952	-1.457	-0.624	0.827	0.931
.380	-1.267	-1.215	1.061	1.082	-0.775	-1.047	0.870	0.969
.440	-0.981	-1.173	-0.894	0.000	-0.479	-1.026	0.656	1.059
.500	-0.790	-1.309	0.776	1.409	-1.099	-0.698	0.561	1.175
.560	-0.638	-1.326	0.558	1.429	-0.949	-0.891	0.291	1.094
.620	-0.524	-1.254	0.430	1.467	-1.294	-0.702	-0.032	1.132
.700	-0.411	-1.055	0.303	1.418	-1.568	-0.486	-0.210	1.113
.800	-0.258	-0.749	0.182	1.344	-2.641	-0.324	-0.469	1.154
.900	-0.021	-0.111	0.136	1.180	-3.376	0.373	-0.340	1.080

(ii-1) Tabulated data for test case 6E62 (point 615)
Figure 9. Continued.



(ii-2) Plot of data for test case 6E62 (point 615)
Figure 9. Continued.

Point Number = 616 Mach Number = 0.401 Alphao = 12.02, deg.

	q,psf	H,psf	V,fps	Rn	gamma	freq,Hz	k	theta,deg
54.3	652.7	202.2	.402E+07	1.132	19.99	0.621	1.055	


	y/s = 0.309				y/s = 0.588			
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-12.855	7.602			-12.556	7.574		
.025	-25.030	5.779	2.307	-0.622	-27.955	11.125	2.625	-0.883
.050	-8.539	2.336	3.050	-0.789	-7.880	2.962	3.349	-0.929
.100	-5.517	0.502	3.354	-0.299	-4.962	0.583	3.291	-0.381
.200	-3.524	-1.104	2.824	0.559	-3.166	-0.974	2.825	0.549
.260	-2.803	-1.765	2.423	1.099	-2.587	-1.381	2.055	1.220
.320	-2.274	-1.764	2.126	1.413	-2.052	-1.778	2.184	1.424
.380	-1.852	-1.911	1.869	1.574	-1.632	-1.891	1.914	1.606
.440	-1.558	-2.090	1.660	1.719	-1.367	-1.960	1.639	1.739
.500	-1.159	-2.152	1.541	1.966	-0.983	-1.937	1.481	1.875
.560	-0.899	-2.214	1.294	2.009	-0.641	-1.904	1.335	2.047
.620	-0.589	-2.260	1.036	2.153	-0.359	-1.977	0.971	2.064
.700	-0.482	-2.285	0.805	2.076	-0.223	-2.052	0.736	2.044
.800	-0.235	-2.160	0.596	1.976	0.024	-1.738	0.571	1.927
.900	-0.081	-1.192	0.465	1.787	0.146	-0.967	0.433	1.627

	y/s = 0.809				y/s = 0.951			
x/c	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t	ReCpu/t	ImCpu/t	ReCpl/t	ImCpl/t

.000	-12.027	7.603			-8.354	5.384		
.025	-10.539	5.027	3.080	-1.160	-13.430	7.911	2.962	-1.483
.050	-7.433	2.913	3.308	-1.135	-5.249	2.228	3.243	-1.251
.100	-4.374	0.467	2.637	-0.437	-2.916	0.312	2.633	-0.389
.200	-2.516	-1.022	1.862	0.535	-1.838	-0.665	1.833	0.505
.260	-2.063	-1.206	1.525	1.037	-1.467	-0.826	1.443	0.867
.320	-1.550	-1.599	1.267	1.292	-1.452	-0.852	0.998	1.148
.380	-1.379	-1.679	1.210	1.460	-0.870	-1.442	0.987	1.227
.440	-0.974	-1.757	1.263	0.000	-0.521	-1.371	0.854	1.388
.500	-0.801	-1.843	0.799	1.822	-1.040	-1.033	0.494	1.381
.560	-0.575	-1.812	0.667	1.855	-0.913	-1.216	0.345	1.481
.620	-0.426	-1.685	0.528	1.885	-1.182	-0.957	0.003	1.521
.700	-0.327	-1.541	0.399	1.934	-1.422	-0.678	-0.130	1.461
.800	-0.042	-1.140	0.265	1.767	-2.390	-0.512	-0.373	1.530
.900	0.235	-0.365	0.170	1.563	-2.860	0.326	-0.308	1.322

(jj-1) Tabulated data for test case 6E63 (point 616)
Figure 9. Continued.



(jj-2) Plot of data for test case 6E63 (point 616)

Figure 9. Concluded.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188
<p>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</p>			
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE	3. REPORT TYPE AND DATES COVERED	
	April 1999	Technical Memorandum	
4. TITLE AND SUBTITLE		5. FUNDING NUMBERS	
Computational Test Cases For a Rectangular Supercritical Wing Undergoing Pitching Oscillations		WU 522-31-81-03	
6. AUTHOR(S)			
Robert M. Bennett and Charlotte E. Walker			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)		8. PERFORMING ORGANIZATION REPORT NUMBER	
NASA Langley Research Center Hampton, VA 23681-2199		L-17830	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)		10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
National Aeronautics and Space Administration Washington, DC 20546-0001		NASA/TM-1999-209130	
11. SUPPLEMENTARY NOTES			
Bennett: Langley Research Center, Hampton, VA Walker: Cooperative Engineering Education Student, University of Tennessee, Knoxville, TN			
12a. DISTRIBUTION/AVAILABILITY STATEMENT		12b. DISTRIBUTION CODE	
Unclassified-Unlimited Subject Category 02 Distribution: Standard Availability: NASA CASI (301) 621-0390			
13. ABSTRACT (Maximum 200 words)			
<p>Proposed computational test cases have been selected from the data set for a rectangular wing of panel aspect ratio two with a twelve-percent-thick supercritical airfoil section that was tested in the NASA Langley Transonic Dynamics Tunnel. The test cases include parametric variation of static angle of attack, pitching oscillation frequency, and Mach numbers from subsonic to transonic with strong shocks. Tables and plots of the measured pressures are presented for each case. This report provides an early release of test cases that have been proposed for a document that supplements the cases presented in AGARD Report 702.</p>			
14. SUBJECT TERMS		15. NUMBER OF PAGES	
Unsteady aerodynamics; Transonic flow; Computational fluid dynamics		132	
		16. PRICE CODE	
		A07	
17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT
Unclassified	Unclassified	Unclassified	UL